

MeetMind — Mobile API Reference

This app is prepared to serve a companion mobile app. The mobile client shares this app's backend, accounts, and database. All endpoints below are described formally in `openapi.json` (at the project root), which is the source of truth for request/response shapes. This file is a human-readable index.

Authentication (mobile)

The mobile client authenticates through the dedicated mobile-auth bridge, which issues a bearer token. Send that token as `Authorization: Bearer <token>` on every guarded request.

Method	Path	Auth	Description
POST	<code>/api/mobile-auth/signup</code>	none	Create an account, returns a bearer token.
POST	<code>/api/mobile-auth/login</code>	none	Exchange email + password for a bearer token.
GET	<code>/api/mobile-auth/me</code>	bearer	Return the current signed-in user.

The web app continues to use its own session-cookie auth (`/api/auth/*`, `/api/signup`) unchanged. The mobile-auth bridge is additive and does not alter web behaviour.

Meetings

Method	Path	Auth	Description
GET	<code>/api/meetings</code>	bearer	List the current user's meetings.
POST	<code>/api/meetings</code>	bearer	Create a meeting.
GET	<code>/api/meetings/{id}</code>	bearer	Get one meeting (with action items).
PATCH	<code>/api/meetings/{id}</code>	bearer	Update a meeting.
DELETE	<code>/api/meetings/{id}</code>	bearer	Delete a meeting.
GET	<code>/api/meetings/stats</code>	bearer	Dashboard stats for the current user.

Documents (library)

Method	Path	Auth	Description
GET	/api/documents	bearer	List the current user's documents.
POST	/api/documents	bearer	Create a document record.
DELETE	/api/documents/{id}	bearer	Delete a document.

Notes (composer)

Method	Path	Auth	Description
GET	/api/notes	bearer	List the current user's composer notes.
POST	/api/notes	bearer	Create a composer note.
PATCH	/api/notes/{id}	bearer	Update a composer note.
DELETE	/api/notes/{id}	bearer	Delete a composer note.

Uploads

Method	Path	Auth	Description
POST	/api/upload/presigned	bearer	Get a presigned upload URL and the resulting <code>cloud_storage_path</code> .

AI & processing

Method	Path	Auth	Response	Description
POST	/api/transcribe	bearer	text/plain stream	Stream a transcript from uploaded audio.
POST	/api/summarize	bearer	text/event-stream (SSE)	Stream a meeting summary; persists to the meeting.
POST	/api/ai-ask	bearer	text/plain stream	Stream an AI answer for the smart composer.
POST	/api/ffmpeg-process	bearer	JSON	Server-side audio extraction from a media file.
POST	/api/generate-pdf	bearer	JSON	Start a PDF export job.
GET	/api/generate-pdf/status	bearer	JSON	Poll a PDF export job's status.

Notes for mobile integration

- Every guarded route returns `401` when the bearer token is missing, invalid, or tampered.
- `DateTime` fields are serialized as ISO-8601 strings.
- `cloud_storage_path` (snake_case) is the stored object key; never store local paths.
- Streaming endpoints must be consumed as streams, not awaited as a single JSON body.