

Topic 6A

Storing Data Using SQL Database

Topics

- ❑ Create database in Visual Studio
- ❑ Working with database in C# application

Objectives:

- ❑ Be able to work with database

Working with Database using SQL database

- ❑ Why do we need a database?
 - ❑ Recap the concept you have learnt in Database Management System module
 - ❑ Need a database to store our data
 - ❑ Helps to organise large amount of data
 - ❑ Stores it for long term usage (unlike class variable, information is gone when the application ends)




Working with Database using SQL database

□ How to work with database in C# using Visual Studio?

In 3 simple steps:

1. Create a new SQL database
2. Connect database objects with a data source
3. Create controls to bind the table



Example1:

Application to store customer data in SQL database

- ❑ Create a simple database to store Customer data.
- ❑ Every customer has:
 - ❑ Customer ID (unique primary key)
 - ❑ Name
 - ❑ Birthday
 - ❑ Telephone number

Customer ID	Name	Birthday	Tele Phone
1	Mary	1 jan 1970	1234567
2	Sally	9 jan 1970	5534567


- ❑ Navigate the customer data using a window form.

About SQL database

- ❑ It stores data for you in an organised and interrelated way
- ❑ Visual Studio provides tools to help you to maintain your data in database
- ❑ Data in a SQL database are stored in **tables**
- ❑ A database can have 1 or many tables.

Customer ID	Name	Birthday	Tele Phone
1	Mary	1 jan 1970	1234567
2	Sally	9 jan 1970	5534567

Customer table



Accessing Records in Database

❑ Creating Client Data Applications

Most applications revolve around:

- ❑ To read and update information in databases.
- ❑ To allow data integration in applications


Visual Studio provides tools and support for working with data using **ADO.NET** and Windows Forms Data Binding.

What is **ADO.NET**?

- ❑ ADO stands for **ActiveX Data Objects**
- ❑ It provides consistent access to data sources such as SQL Server and XML, and to data sources exposed through OLE DB and ODBC.
- ❑ Data-sharing consumer applications can use ADO.NET to connect to these data sources and retrieve, handle, and update the data that they contain.


Example1- Step1: Create a new SQL database

1. Create a new project in **C:\Temp** and name it as **DATABASE**.
2. In **Solution Explorer**, right-click the project. Select **Add**, then choose **New Item**.




Example1- Step1: Create a new SQL database

1. Choose the **Service-based Database** icon and name it as **school.mdf**
2. Click on the **Add** button



Example1- Step1: Create a new SQL database

4. Open the **Server Explorer** (View → Server Explorer)
5. Expand **Data Connections** if necessary.
6. You may see a red cross at the school.mdf. Double click on it and the red cross should disappear.



Example1:

Create Table in SQL database

1. Add a table to the database. Right click on **Tables** and select **Add New Table**. In the CREATE TABLE window change the table name to **Customer**.
2. Define the column (fields) of the table (see next slide for details)

The screenshot displays the SQL Server Enterprise Designer interface. The top pane shows the table design for 'dbo.Customer [Design]*'. The table has three columns: 'custID' (int, primary key, not null), 'custName' (varchar(50), nullable), and 'custTel' (varchar(10), nullable). The bottom pane shows the T-SQL script for creating the table.

(2) Add 3 data fields here

	Name	Data Type	Allow Nulls	Default
PK	custID	int	<input type="checkbox"/>	
	custName	varchar(50)	<input checked="" type="checkbox"/>	
	custTel	varchar(10)	<input checked="" type="checkbox"/>	
			<input type="checkbox"/>	

(3) Click Update to create the table.

```
CREATE TABLE [dbo].[Customer]
(
    [custID] INT NOT NULL PRIMARY KEY,
    [custName] VARCHAR(50) NULL,
    [custTel] VARCHAR(10) NULL
)
```

(1) Change the table name to Customer here.

Create Table in SQL database: Data Field Definitions

custID field – Data Type → **int**
 – **Allow Nulls** → no tick
 – Set as **Primary Key**


custName field - Data Type = **varchar**(50)
 - Allow Nulls → ticked

custTel field - Data Type = **varchar**(10)
 - Allow Nulls → ticked

- **int** → integer (ie. whole number).
- **varchar(50)** → Variable Character type can hold letters and numbers. 50 means it can hold max 50 characters.
- **Allow Nulls** → if ticked (ie. selected) means the data field can be empty. If not ticked, then the data field must have a value. So in our table, when you create a Customer record, you must provide a custID but the Name and Tel can be blank (ie. empty)
- **Primary Key** → use as Index; must be unique.

Example1:

Create Table in SQL database



(4) Click Update Database

Example1: Create table in SQL database

Completed table shown below.

The screenshot displays the SQL Server Enterprise Designer interface. On the left, the Server Explorer shows the database structure: Azure > Data Connections > school.mdf > Tables > Customer. The Customer table has three columns: custID (primary key), custName, and custTel. The main pane shows the 'Design' view of the 'dbo.Customer' table. The columns are defined as follows:

Name	Data Type	Allow Nulls	Default
custID	int	<input type="checkbox"/>	
custName	varchar(50)	<input checked="" type="checkbox"/>	
custTel	varchar(10)	<input checked="" type="checkbox"/>	

Below the design view, the T-SQL view shows the following CREATE TABLE script:

```
CREATE TABLE [dbo].[Customer]
(
    [custID] INT NOT NULL PRIMARY KEY,
    [custName] VARCHAR(50) NULL,
    [custTel] VARCHAR(10) NULL
)
```

The status bar at the bottom indicates 'Connection Ready' and 'Data Tools Operations'.


Please make sure you have the screen above.

Call your tutor if your screen looks different.


Example1- Step2:

Add database driven control

1. Select the Windows Form **Form1**.
2. Select View → Other Windows → Data Sources
3. Select **Add New Data Source**.
(if you don't see it, right-click schoolDataSet)
4. Select Database → Next
5. Select Dataset → Next
6. Select school.mdf → Next
7. Click Next to accept the default **schoolConnectionString**
8. Select everything (see picture below) in the [Choose Your Database Objects] window → **Finish**.




Example1- Step2: Add database driven control



- You should see the above screen.
- Call your tutor if you do not see it.

Example1- Step3: Create controls to bind the table




- Click on the **Customer** object and drag it into the **Form1**.
- You should get a table as shown above.

Example1- Step3: Create controls to bind the table

3. Press Ctrl F5 and run the application.

VS creates this toolbar for navigating through the Customer table



When you dragged the Customer table onto the form a control was created for each column in the table

Example1- Step4: Create the Form to Insert and Retrieve data

2. Amend the form as follows:

Form1

Retrieved Data

	custID	custName	custTel
*			

Connection String

label7

INSERT RECORD

ID:

Name:

Telephone:

INSERT

Textbox: tbID

Textbox: tbName


Textbox: tbTel

Label: lblConnect

Button: btnInsert

Example1- Step 4: Connection String

1. Open the **Server Explorer**.
2. Right click on school.mdf and select **Properties**.




Connection String

1. Copy the entire Connection String text:

Data Source.....Integrated.....

You will paste it in the codes later.




Copy this ENTIRE string

The connection string specifies the location of the database.

Insert Record - Additional Libraries Needed

- Double click the **INSERT** button on the form.
- You need to use some additional System files.
- Go to Form1.cs and scroll to the top.
- Add below 2 lines:
using System.Data.SqlClient;
using System.Configuration;



```
Form1.cs - Notepad
File Edit Format View Help
using System;
using System.Collections.Generic;
using System.ComponentModel;
using System.Data;
using System.Drawing;
using System.Linq;
using System.Text;
using System.Threading.Tasks;
using System.Windows.Forms;
using System.Data.SqlClient;
using System.Configuration;
```

Explanation:

using System.Data.SqlClient;

Add the SqlConnection namespace which interacts with the SQL Server and allows the development of data-driven applications.

- It creates database connections with SqlConnection.
- It inserts data with SqlCommand.
- It handles rows with SqlDataReader.

using System.Configuration;

Access the ConfigurationManager class which provides methods to access configuration information.


Example 1:

Application to Insert Record to Database

```
private void btnInsert_Click(object sender, EventArgs e)
{
    int varID;           //create variables first
    string varName;
    string varTel;

    // read in name and telephone fields
    varID = int.Parse(tbID.Text);
    varName = tbName.Text;
    varTel = tbTel.Text;

    // paste the connection string you copied earlier to below
    // add another '\' to all the back-slashes
    string connect = "Data
Source=(LocalDB)\v11.0;AttachDbFilename=c:\\temp\\d
atabase\\database\\school.mdf;Integrated
Security=True";
    // Display the connection string to check
    lblConnect.Text = connect;

    // → 
}
```

Run the program to make sure your Connection String is working before continuing

Insert Record - Testing the Connection String

The screenshot shows a Windows Forms application window titled 'Form1'. The form is divided into two main sections: 'Retrieved Data' on the left and 'INSERT RECORD' on the right. The 'Retrieved Data' section contains a table with three columns: 'custID', 'custName', and 'custTel'. The first row of the table is highlighted in blue and contains an asterisk (*) in the 'custID' column. Below the table is a large grey rectangular area. The 'INSERT RECORD' section contains three text boxes: 'ID:' with the value '1', 'Name:' with the value 'ali', and 'Telephone:' with the value '11111'. Below these text boxes is an 'INSERT' button. At the bottom of the form, there is a label 'Connection String' followed by the text: 'Data Source=(LocalDB)\v11.0;AttachDbFilename=c:\temp\WindowsFormsApplication1\WindowsFormsApplication1\school.mdf;Integrated Security=True'.

custID	custName	custTel
*		

INSERT RECORD

ID: 1

Name: ali

Telephone: 11111

INSERT

Connection String

Data Source=(LocalDB)\v11.0;AttachDbFilename=c:\temp\WindowsFormsApplication1\WindowsFormsApplication1\school.mdf;Integrated Security=True

- ❑ Enter some data and click Insert button.
- ❑ You should see the Connection String as shown above.
- ❑ Note the example above has the location in **C:\temp**, the Project name is **database** and the database is called **school.mdf**
- ❑ Your connection string may be different.

Insert Record – Continue After Connection String is Working

Add the codes below at  in slide 24.

```
//creates a SQL connection object and opens  
//the connection
```

```
SqlConnection myConnect = new  
    SqlConnection(connect);  
myConnect.Open();
```

```
//creates a SQL command object
```

```
SqlCommand cmd = new SqlCommand();  
cmd.Connection = myConnect;
```

```
//forms the SQL command and parameters
```

```
cmd.CommandText = "INSERT INTO  
Customer(custID, custName, custTel) values (@xid,  
@xname, @xtel)";
```

```
cmd.Parameters.Add(new SqlParameter("@xid",  
varID));
```

```
cmd.Parameters.Add(new SqlParameter("@xname",  
varName));
```

```
//continue next slide
```

Insert Record continue

```
cmd.Parameters.Add(new SqlParameter("@xtel",  
varTel));
```

```
//runs the SQL command  
cmd.ExecuteNonQuery();
```

```
//Refresh the DataGrid  
DataTable dt = new DataTable();
```

```
SqlDataAdapter orange = new  
SqlDataAdapter("Select * from Customer",  
myConnect);
```

```
orange.Fill(dt);  
customerDataGridView.DataSource = dt;  
customerDataGridView.Update();  
customerDataGridView.Refresh();
```

```
//close database connection  
myConnect.Close();
```

```
} // end of Insert button
```

The entire program is in Annex A

Test Your Application

Form1

0 of 0

Retreived Data

	custID	custName	custTel
▶	1	ALI	11111
	2	BENNY	22222
	3	CHARLES	33333
*			

INSERT RECORD

ID: 3

Name: CHARLES

Telephone: 33333

INSERT

Connection String

Data Source=(LocalDB)\v11.0;AttachDbFilename=c:\temp\WindowsFormsApplication1\Windows

- ❑ Enter a record and click Insert button.
- ❑ Your data should appear in the table on the left.
- ❑ For more records, make sure your Customer ID is **UNIQUE** (ie. cannot be same)

More methods for accessing database using C# code

- ❑ To learn more about editing data in your application
- ❑ Refer to MSDN(Microsoft Developer Network) website:
 - ❑ [http://msdn.microsoft.com/en-us/library/ms171928\(v=vs.80\)](http://msdn.microsoft.com/en-us/library/ms171928(v=vs.80))

The screenshot shows the MSDN website interface. At the top is a navigation bar with links: Home, Library, Learn, Downloads, Support, and Community. On the right of the navigation bar are links for Sign in, United States - English, and icons for settings and a printer. The main heading is "Editing Data in Your Application" with the "msdn" logo on the right. Below the heading, it specifies ".NET Framework 2.0" and "Other Versions" with a dropdown arrow, followed by "2 out of 9 rated this helpful - Rate this topic". The main text states: "After your dataset is populated with data, you will typically add, edit, or delete some of the data before sending it back to the data source or to another process or application. Since each record in a dataset is represented by a DataRow object, changes to a dataset are accomplished by working with individual rows." Below this is a yellow "Note" box with a pencil icon, stating: "In Windows Forms, the data-binding architecture takes care of sending changes from data-bound controls to the dataset, and you do not have to explicitly update the dataset with your own code. For more information, see Windows Forms Data Binding." The main text continues: "Datasets maintain multiple versions of data rows in order to locate the original records in a data source. Before performing an update to the data source, you may want to examine specific rows. The topics in this section provide details on determining if records have changed, as well as retrieving particular versions of records. The following topics provide details on adding, editing, and deleting rows in data tables, and how to work with rows in various stages of an application." Below this is the "In This Section" heading, followed by a link "Editing Data in Datasets Overview" and a description: "Provides information on the many tasks that manipulate data in a dataset." Finally, there is a link "How to: Add Rows to a DataTable" and a description: "Provides the steps to create DataRow objects and add them to a data table."

Home Library Learn Downloads Support Community Sign in | United States - English | ⚙️ | 🖨️

Editing Data in Your Application msdn

.NET Framework 2.0 | Other Versions ▾ | 2 out of 9 rated this helpful - Rate this topic

After your dataset is populated with data, you will typically add, edit, or delete some of the data before sending it back to the data source or to another process or application. Since each record in a dataset is represented by a [DataRow](#) object, changes to a dataset are accomplished by working with individual rows.

Note

In Windows Forms, the data-binding architecture takes care of sending changes from data-bound controls to the dataset, and you do not have to explicitly update the dataset with your own code. For more information, see [Windows Forms Data Binding](#).

Datasets maintain multiple versions of data rows in order to locate the original records in a data source. Before performing an update to the data source, you may want to examine specific rows. The topics in this section provide details on determining if records have changed, as well as retrieving particular versions of records. The following topics provide details on adding, editing, and deleting rows in data tables, and how to work with rows in various stages of an application.

In This Section

[Editing Data in Datasets Overview](#)

Provides information on the many tasks that manipulate data in a dataset.

[How to: Add Rows to a DataTable](#)

Provides the steps to create DataRow objects and add them to a data table.

Summary

❑ Working with database in C# application

❑ In 3 simple steps:

1. Create a new SQL database
2. Connect database objects with a data source
3. Create controls to bind the table

❑ MSDN

❑ MS development network

❑ <http://msdn.microsoft.com/en-us/default.aspx>

❑ Learn more about C#

Practical 6A

Project Work

- ❑ Apply the lesson learnt into your project.
- ❑ Add a customer database to store customer details.
- ❑ Retrieve the customer data from the database for existing customer.



Annex A: Entire Program of Insert Button

```
private void btnInsert_Click(object sender, EventArgs e)
{
    int varID;
    string varName;
    string varTel;

    varID = int.Parse(tbID.Text);
    varName = tbName.Text;
    varTel = tbTel.Text;


    string connect = "Data Source = (LocalDB)\\v11.0;
AttachDbFilename=c:\\temp\\database\\database\\school.mdf; Integrated
Security=True";
    lblConnect.Text = connect;

    SqlConnection myConnect = new SqlConnection(connect);
    myConnect.Open();
    SqlCommand cmd = new SqlCommand();
    cmd.Connection = myConnect;
    cmd.CommandText = "INSERT INTO Customer(custID, custName, custTel)
values (@xid, @xname, @xtel)";
    cmd.Parameters.Add(new SqlParameter("@xid", varID));
    cmd.Parameters.Add(new SqlParameter("@xname", varName));
    cmd.Parameters.Add(new SqlParameter("@xtel", varTel));
    cmd.ExecuteNonQuery();

    DataTable dt = new DataTable();
    SqlDataAdapter orange = new SqlDataAdapter("Select * from Customer",
myConnect);

    orange.Fill(dt);
    customerDataGridView.DataSource = dt;
    customerDataGridView.Update();
    customerDataGridView.Refresh();
    myConnect.Close();
}
```


End of Topic 6A



Storing Data
Using SQL Database