

Types of selectors

Tag Selector	<code>h1 { }</code>
Class Selector	<code>.main-heading { }</code>
ID Selector	<code>#reasons-dection { }</code>
Attribute Selector	<code>a[href] { }</code>
Pseudo-classes	<code>a:hover { }</code>
Pseudo-elements	<code>p::first-line { }</code>
Comment	<code>/* comment */</code>
Universal Selector	<code>* { }</code>

Selector Combinators

descendant	space	body article p	an elements are nested inside each other
child	>	article > p	an element is an immediate child
adjacent sibling	+	p + img	an element that comes immediately after
general sibling	~	p ~ img	an element located anywhere below the code, inside a common parent

CSS Specificity

important	inline styles	id	class - attribute - pseudo-class	elements - pseudo-elements
10000	1000	100	10	1

CSS Emmet cheat sheet

Hex color	c	color: #000;
Rgb color	c:r	color: rgb(0, 0, 0);
Opacity	op	opacity;;
borders	bd	border;;
	bd+	border: 1px solid #000;
	bd:n	border: none;
	bdrs	border-radius;;
fonts	fw	font-weight;;
	fw:n	font-weight: normal;
	fw:b	font-weight: bold;
	fs	font-style: italic;
	fs:n	font-style: normal;
	fz	font-size;;
	ff	font-family;;
	ff:a	font-family: Arial, "Helvetica Neue", Helvetica, sans-serif;
	ff:t	font-family: "Times New Roman", Times, Baskerville, Georgia, serif;
text	ta	text-align: left;
	ta:c	text-align: center;
	ta:r	text-align: right;
	td:n	text-decoration: none;
	td:u	text-decoration: underline;
	tt	text-transform: uppercase;
line-height	lh	line-height;;
letter-spacing	lts	letter-spacing;;
lists	lis	list-style;;
	lis:n	list-style: none;