EQUIPMENT LIST — LINE 2

Asset register for stations ST-10 to ST-70, Plant 2

Document number	NVE-LST-001
Revision	Rev 07
Effective date	2026-08-17
Next review	2027-08-16
Document owner	Maintenance (T. Bereczki)
Applies to	All equipment on Line 2, Plant 2
Supersedes	NVE-LST-001 Rev 06, effective 2026-03-02

1. SCOPE

Asset register for Line 2. Every item that is maintained, calibrated or referenced by a Line 2 procedure appears here. Preventive maintenance for the machining centres is defined in NVE-SOP-103; start-up verification in NVE-FRM-012.

2. EQUIPMENT REGISTER

Table 1 — Line 2 equipment, by station

Asset ID	Name	Type and model	Station	PM interval	Calibration
BR-101	Bin rack, kitting	Static rack, 48 bin	ST-10	Annual	—
SC-101	Kitting scanner	Handheld 2D barcode	ST-10	—	—
MC-201	Vertical Machining Centre 1	Steinvald VMC-650, 3-axis	ST-20	Weekly + monthly + 500 h	Geometric accuracy, annual (ISO 230)
MC-202	Vertical Machining Centre 2	Steinvald VMC-650, 3-axis	ST-20	Weekly + monthly + 500 h	Geometric accuracy, annual (ISO 230)
DB-301	Deburring station	Bench, pneumatic tooling	ST-30	Monthly	—
WC-302	Parts wash cabinet	Aqueous, heated, 80 L	ST-30	Monthly	—
WS-401	Assembly bench 1	ESD bench with TDR-3000 driver	ST-40	Quarterly	Torque, 6 monthly
WS-402	Assembly bench 2	ESD bench with TDR-3000 driver	ST-40	Quarterly	Torque, 6 monthly
WS-403	Assembly bench 3	ESD bench with TDR-3000 driver	ST-40	Quarterly	Torque, 6 monthly
FCT-401	Functional test fixture	In-circuit and functional tester	ST-50	Quarterly	Annual
IB-501	Inspection bench	Bench, 1000 lx task lighting, 2× magnifier	ST-60	Annual	Lux check, annual
LP-601	Label printer	Thermal transfer, 300 dpi	ST-70	Monthly	—

Asset ID	Name	Type and model	Station	PM interval	Calibration
CV-101	Line conveyor	Belt, variable speed	ST-10–ST-70	Monthly	—

3. MACHINING CENTRE DETAIL

MC-201 and MC-202 are identical. The features below are the ones referenced by the weekly checks in NVE-SOP-103 section 6 and by the start-up checks in NVE-FRM-012.

Feature	Detail
Coolant reservoir	120 L, fill line marked on the sight glass at the machine front
Chip and sludge tray	Draw-out tray beneath the bed; emptied weekly
Cabinet air filter	Panel filter behind an external grille on the cabinet rear door; inspected through the grille, replaced by Maintenance under lock-out. Consumable NVE-SPR-0912.
Way lubrication oil reservoir	On the machine front. Sight gauge graduated 0 to 100 %; the 40 % graduation carries the MIN mark. **These machines have no hydraulic circuit.**
Power and signal cables	Routed in a drag chain along the X axis, together with the coolant hose. Exposed runs at each chain end are inspectable with the machine stopped; the enclosed run is inspected at the 500-hour service, where the chain is opened.
Guards and interlocks	Front door interlock on spindle rotation; fixed side guards
Tool carousel	20 positions, automatic tool change
Spindle	12 000 rpm, BT30 taper

4. CONSUMABLES AND SPARES HELD ON SITE

Part number	Description	Used on	Min stock
NVE-SPR-0912	Cabinet air filter, panel	MC-201, MC-202	4
NVE-SPR-0918	Coolant concentrate, 20 L	MC-201, MC-202	2
NVE-SPR-0925	Way lubricant, 5 L	MC-201, MC-202	2
NVE-SPR-1104	Driver bit, hex 3 mm	TDR-3000	10
NVE-SPR-1106	Driver bit, hex 2.5 mm	TDR-3000	10
NVE-SPR-1201	Label ribbon, thermal transfer	LP-601	6

5. RELATED DOCUMENTS

- NVE-SOP-103 Rev 05 — Preventive Maintenance, Machining Centres
- NVE-FRM-012 Rev 04 — Operator Station Setup Check
- NVE-LAY-001 — Plant 2 Floor Layout, Line 2
- NVE-SOP-104 — Operator Roles and Responsibilities, Line 2

- Steinvald VMC-650 Operation and Maintenance Manual, SVM-650-OM issue 4
- TDR-3000 Torque Driver Operating Instructions, TDR-OI-14

REVISION HISTORY

Rev	Date	Changed by	Reason for change
04	2024-08-19	T. Bereczki	MC-202 added on installation.
05	2025-06-30	T. Bereczki	WS-403 added. Wash cabinet WC-302 recorded against ST-30.
06	2026-03-02	T. Bereczki	Calibration cadence column added. Consumable part numbers recorded for the machining centres.
07	2026-08-17	T. Bereczki	Machining centre detail corrected: way lubrication reservoir in place of a hydraulic reservoir, which these machines do not have; air filter inspected through the external grille; drag chain inspection split between the exposed and enclosed runs. Monthly interval added to the PM column.

APPROVALS

Prepared by	Approved by
T. Bereczki Maintenance Lead	P. Vargha Production Supervisor
Date: 2026-08-04	Date: 2026-08-11