


# 2019-04-22 Optimal BSTs

Monday, April 22, 2019 4:23 PM

- Scenario: we're trying to build a tree that translates words from English to Spanish.
- Question: how should this tree be arranged?
  - Obvious approach: make it well-balanced ((a-z)/2 is root)
    - Good average search time
  - Based on rate of occurrence
    - Prioritizes faster lookups for more common words
  - Which would be faster overall?
- To answer this question conclusively, we would need not only a dictionary of words but also frequency of usage


Word	Probability
A	0.22
AM	0.18
AND	0.20
EGG	0.05
IF	0.25
THE	0.02
TWO	0.08



## Evaluating the trees

Word	Probability	Balanced Tree # of checks	Balanced Tree Cost	Greedy Tree # edges	Greedy Tree cost
A	0.22	3	$0.22 * 3 = 0.66$	2	$0.22 * 2 = 0.44$
AM	0.18	2	$0.18 * 2 = 0.36$	4	$0.18 * 4 = 0.72$
AND	0.20	3	$0.20 * 3 = 0.6$	3	$0.20 * 3 = 0.6$
EGG	0.05	1	$0.05 * 1 = 0.05$	4	$0.05 * 4 = 0.2$
IF	0.25	3	$0.25 * 3 = 0.75$	1	$0.25 * 1 = 0.25$
THE	0.02	2	$0.02 * 2 = 0.04$	3	$0.02 * 3 = 0.06$
TWO	0.08	3	$0.08 * 3 = 0.24$	2	$0.08 * 2 = 0.16$
TOTAL	1.00		2.70		2.43

Consider the following tree:








Word	Probability	Magic Tree # of checks	Magic Tree Cost
A	0.22	2	.44

AM	0.18	3	.54
AND	0.20	1	.20
EGG	0.05	3	.15
IF	0.25	2	.50
THE	0.02	4	.08
TWO	0.08	3	.24
<u>TOTAL</u>	1.00		2.15

### Brute Force Approach

A	AM	AND	EGG	IF	THE	TWO
---	----	-----	-----	----	-----	-----



start=0  
end=6