September 12, 2024

6.S894 Accelerated Computing

Lecture 2: Throughput Processors

Jonathan Ragan-Kelley

What is a **processor?**

a **programmable** computer

that runs a **sequence of instructions** over time

including control flow, computation & state updates

What is a **processor?**



1970s



2020s

A simple processor an **interpreter** for instructions!

1. Instr. fetch
2. Decode
3. Operand fetch
4. Execute
5. Write back

Processor

```
ld      r3, mem[r0+r2]
ld      r4, mem[r1+r2]
mul     r3, r3, r4
add     r5, r5, r3
addi    r2, r2, 4
blt     r2, $400, LOOP
st      addr[r6], r5
...
```

Program

Slides inspired by Kayvon Fatahalian

A simple processor an **interpreter** for instructions!



Processor

```
ld      r3, mem[r0+r2]
ld      r4, mem[r1+r2]
mul     r3, r3, r4
add     r5, r5, r3
addi    r2, r2, 4
blt     r2, $400, LOOP
st      addr[r6], r5
...
```

Program

Slides inspired by Kayvon Fatahalian

Optimization 1: Increase the **clock speed**



Processor

Higher **voltage**

↳ power grows with v^2

Faster **transistors**

↳ higher leakage

Deeper **pipelining**

↳ lower average IPC

Optimization 2: Execute **multiple** instructions per cycle (**superscalar**)



Processor

```
ld      r3, mem[r0+r2]
ld      r4, mem[r1+r2]
mul     r3, r3, r4
add     r5, r5, r3
addi    r2, r2, 4
blt     r2, $400, LOOP
st      addr[r6], r5
...
```

Optimization 2: Execute **multiple** instructions per cycle (**superscalar**)



Processor

```
ld      r3, mem[r0+r2]
ld      r4, mem[r1+r2]
mul     r3, r3, r4
add     r5, r5, r3
addi    r2, r2, 4
blt     r2, $400, LOOP
st      addr[r6], r5
...
```

Optimization 3: Avoid **stalls** through **ILP** & **speculation**



Processor

```
ld      r3, mem[r0+r2]
ld      r4, mem[r1+r2]
mul     r3, r3, r4
add     r5, r5, r3
addi    r2, r2, 4
blt     r2, $400, LOOP
st      addr[r6], r5
...
```

Optimization 3: Avoid **stalls** through **ILP** & **speculation**



Processor

```
ld      r3, mem[r0+r2]
ld      r4, mem[r1+r2]
mul     r3, r3, r4
add     r5, r5, r3
addi    r2, r2, 4
blt     r2, $400, LOOP
st      addr[r6], r5
...
```

This makes sense when you have only **one processor**



Processor

This makes sense when you have only **one processor**

Processor **(to scale)**

The reality today:



Silicon Chip

At the same time:

We **most need performance** when processing **lost of stuff**

↳ abundant **data-parallelism**

A **throughput-oriented** view of performance:

Optimize **aggregate rate** of processing **many items**

Three things drive throughput:

1 Amount of **work** to be done

2 Amount of **resources** to be applied (silicon, energy)

} **Constraints** set by application, Si process node

3 **Efficiency** of applying them to useful work ← Goal: **optimize this!**

What to do with twice the silicon?



What to do with twice the silicon?



≪**2**× the performance of smaller core

=

equal area



Double the performance of one core

Diminishing returns to **scaling single-core** performance



If we want to optimize **throughput,** is there a **better way** to **scale performance?**

Idea 1: remove hardware to optimize single-thread performance



Slides inspired by Kayvon Fatahalian

Idea 1: remove hardware to optimize single-thread performance



Invest savings in **parallelism**

Slides inspired by Kayvon Fatahalian

```
for (int i = 0; i < N; ++i)
  for (int k = 0; k < N; ++k)
    for (int j = 0; j < N; ++j)
      C[i*N + j] += A[i*N + k] * B[k*N + j];
```

```
for (int j = 0; j < N; ++j)
  C[i*N + j] += A[i*N + k] * B[k*N + j];
```

```
for all (int j = 0; j < N; ++j)
  C[i*N + j] += A[i*N + k] * B[k*N + j];
```

```
ld     r3, mem[r0+r2]
ld     r4, mem[r1+r2]
mul    r3, r3, r4
add    r5, r5, r3
addi   r2, r2, 4
blt    r2, $400, LOOP
st     addr[r6], r5
...
```




```
ld     r3, mem[r0+r2]
ld     r4, mem[r1+r2]
mul    r3, r3, r4
add    r5, r5, r3
addi   r2, r2, 4
blt    r2, $400, LOOP
st     addr[r6], r5
...
```

Idea 2: amortize **control overhead** with **SIMD execution**



Slides inspired by Kayvon Fatahalian

Idea 2: amortize **control overhead** with **SIMD execution**

SIMD can be **explicit in ISA**

or **implicit in hardware**

Intel AVX, ARM NEON, etc.

many GPUs





```
ld      r3, mem[r0+r2]
ld      r4, mem[r1+r2]
mul     r3, r3, r4
add     r5, r5, r3
addi    r2, r2, 4
blt     r2, $400, LOOP
st      addr[r6], r5
...
```

SIMD execution requires **coherent control**



Slides inspired by Kayvon Fatahalian

SIMD execution requires **coherent control**




```
<unconditional code>

if (x > 0) {
    y = pow(x, exp);
    y *= Ks;
    refl = y + Ka;
} else {
    x = 0;
    refl = Ka;
}

<resume unconditional
        code>
```

Not all ALUs do useful work every cycle!
Worst case: 1/n peak performance

Slide adapted from Kayvon Fatahalian

Diminishing returns,
scale further with **multicore**



Typical SIMD width: 8 ~ 64

How to deal with **latency** without **stalling**



Opportunity:
exploit **parallelism**
to hide latency

Idea 3: Interleave parallel tasks to hide latency



Slide adapted from Kayvon Fatahalian

Idea 3: Interleave parallel tasks to hide latency





Slide adapted from Kayvon Fatahalian

Interleaving requires more **state storage**





Multithreading requires **extra state storage** for idle threads

Slide adapted from Kayvon Fatahalian

Interleaving requires more **state storage**

DRAM latency:
100s of cycles

AMD/Intel Hyperthreadng:
2 threads

NVIDIA H100:
16k 32-bit words per warp scheduler (core)
↳ **32MB** per GPU



Slide adapted from Kayvon Fatahalian

Tradeoff: per-thread state vs. latency hiding

Few, large contexts:
limited latency hiding



Slide adapted from Kayvon Fatahalian

Tradeoff: per-thread state vs. latency hiding

Many, small contexts:
maximal latency hiding



Slide adapted from Kayvon Fatahalian

A **throughput-oriented processor** exploits abundant parallelism for efficiency

1. Scale performance with **multicore**, not instruction-level parallelism
2. Amortize **control overhead** with **SIMD execution**
3. Hide **latency** with **concurrent threads**, not speculation

Idea 4: amortize instruction overheads with **more complex instructions**

Primitive op:
("RISC")

"ASIC-in-an-Instruction"

Complex op:
("CISC++")



e.g., AES, video encode/decode, DSP, texture filtering, …

and especially **matrix multiply!**

Why yes,
I am still
basically a
PDP-11



You will **rewrite**
all your code in
CUDA . . .
and pray I don't
alter the deal
any further!



How do these ideas appear in **real hardware?**

Our GPU: NVIDIA RTX 4000 Ada (AD104 chip)





One “core” of our GPU

(“warp scheduler”)

32 x 32-bit Exec. Units (ALUs / vector lanes)

512 x 32 x 32-bit regs

1 warp instruction / clock (32 lanes)

Up to 12 live threads (independent warps)



One "SM" is a cluster of 4 warp schedulers

Our whole GPU

48 SMs
x 4 = 192 cores
x32 = 6144 exec. units

@ 2.175 GHz
= 26.7 TFLOPS

192x12 = 2,304 threads

96k 1024-bit registers
= 12 MB

48 MB L2 cache



Our CPU: AMD Ryzen 7 7700

One core of our CPU (AMD Zen 4)

Huge, complex control logic (6-wide, OoO, …)

Two 256-bit vector ALUs = 16 x 32-bit exec. units

192 vector registers

1 MB cache

2 “hyperthreads”



Our whole CPU

8 “Zen 4” cores
x 16 = 128 exec units

@ 3.8 ~ 5.5 GHz
= 0.97 ~ 1.4 TFLOPS

8 x 2 = 16 threads

1.5k 512-bit registers
= 24 KB

40 MB total L2+L3



Our CPU

8 “Zen 4” cores
x 16 = 128 exec units

@ 3.8 ~ 5.3 GHz
= 0.97 ~ 1.4 TFLOPS

8 x 2 = 16 threads

1.5k 512-bit registers
= 24 KB

40 MB total L2+L3

Our GPU

48 SMs
x 4 = 192 cores
x32 = 6144 exec. units

@ 2.175 GHz
= 26.7 TFLOPS

192x12 = 2,304 threads

96k 1024-bit registers
= 12 MB

48 MB L2 cache

Our CPU

70 mm^2
(CCD only)

70 mm^2

/ 8 cores

= 8.75 mm^2

6-7x faster
on Mandelbrot

Our GPU

294 mm^2
(full die)

~200 mm^2

/ 192 cores

= 1.05 mm^2 / core

8x smaller

A **throughput processor** is **still a processor!**

(or actually, many of them)

But we need to **change our programs** to use it efficiently

expose **explicit parallelism**
within & across instruction streams