

Hardware Prerequisites

AccuKnox Control Plane, Production Deployment

These are the minimum hardware resources needed to deploy and run the AccuKnox control plane in production mode. Check your infrastructure against these numbers before you start the installation.

Per-Node Requirements

Resource	Minimum Requirement
CPU	8 vCPUs / cores
Memory	32 GB RAM
Node Storage	80 GB
Number of Nodes	15

Cluster-Wide Requirements

Resource	Minimum Requirement
Total CPU	120 vCPUs / cores (8 × 15 nodes)
Total Memory	480 GB RAM (32 GB × 15 nodes)
PVC Storage	1.36 TB (1,396 Gi of PVCs)

PVC Storage Breakdown

Storage is listed per service, with every replica of a service summed into a single figure. The divy backend line covers its media, static file, and Celery Flower volumes.

Service	Storage
divy backend	25 Gi
mongod	600 Gi
postgres	200 Gi
neo4j	150 Gi
rabbitmq	300 Gi
keydb	70 Gi
redis	20 Gi
vault	30 Gi
obs-nfs	1 Gi
Total	1,396 Gi (1.36 TB)

Replica counts behind the totals

Three services run as multi-replica stateful sets, so their storage figure above is the sum of the per-replica volumes.

- **mongod:** 3 replicas × 200 Gi
- **rabbitmq:** 3 replicas × 100 Gi
- **vault:** 3 replicas × 10 Gi