



Functional Features

- 10.2 LED Touch-screen, 90 rotation screen.
- CTG waveforms can be frozen.
- Thermal printer with 112 mm, synchronization print
- Auto interpretation and N T Grade.
- Equipped with High performance waterproof.
- Probe Upto 500 patients data saving, USB can be supported Data transmitting to PC via USB Patient's information can be input.
- Historical data can be reviewed and printed.
- Built-in rechargeable li-ion battery, AC/DC power conversion. Battery Backup Up to 2.50 hours.
- Sleep mode to save energy and extend LED screens life.
- Portable design with hidden handle, convenient to carry.
- Multiple language support 7 level printing thickness can be chosen.
- Adapt to 110 230V 50/60Hz AC Power supply.

Optional:-

Twin FHR facility



Specification

Ultrasonic Operating Frequency	0-100 Unit	FHR Range	50-240 beats/min
Systolic Pressure	3MHz, 110%	Paper Speed	3.2.3cm/min(0.3%)
Specification of Fuse	Manual/Audio	Recorder	High resolution Thermal Printer
Operation Mode	T1, GA 250V	Battery	Built in rechargeable Li-ion battery 11.1v(220 mAh)
Recording Paper	112* 100MM 2 Fold Thermal Paper	Machine Size	107mm-255mm-91mm

Registered Address: Ground Floor Plot no-183 Pocket N, Sector-2, DSIDC Industrial Area, North West, Delhi, 110039

Work Address: Industrial Unit-39, Block-B, Sector-63, Noida, Gautam Buddha Nagar, Uttar Pradesh-201301

Web: www.accuremedical.in, **Contact:** +91 8077818101, 0120 4916914

Email: info@accuremedical.in, ampl2207@gmail.com

Tollfree No.: 1800-419-9029