

AC 600- I INFUSION PUMP



- Removable pump body
Convenient for cleaning



- Free flow protection
The built-in flow stop feature helps to reduce the risk of accidental free flow



- History Record
Event logs and alarm information can be transferred to computer for review



- Rotatable pole clamp
Fixation on vertical pole or horizontal bar

INFUSION PUMP FEATURES

- | | | | |
|--|---------------------------------------|-------------------------------------|--|
| • History records | • Anti-reverse rotation detection | • Real time display | • Double CPU ensuring safe infusion |
| • Various infusion modes to meet different clinical requirements | • Various visual and audible alarms | • Compact and light weight design | • Removable pump body, convenient for cleaning |
| • KVO, Bolus Anti-bolus | • Drop sensor (optional) | • Soft key design, easy for operate | • Docking station (optional) |
| | • IV stand stainless steel (optional) | • Free-flow protection | |

AC 600- I INFUSION PUMP

SPECIFICATION

Infusion rate	0.1-1200ml/h
Infusion accuracy	± 5%
Applicable infusion set	Various brands of standard infusion set
Volume to be infused (VTBI)	0-9999(ml)
Volume infused	0-36000(ml)
KVO rate	1-5ml/h
Bolus rate	300-1200ml/h
Infusion mode	Rate mode
	Drip mode
	Time mode
	Body Weight mode
	Drug library mode (optional)
	Intermittent infusion mode (optional)
	Sequential mode
Purge rate	600ml/h
Air bubble detection	Ultrasound sensor detection with four levels of air in line alarm
Occlusion pressure	(40.0-160.0) KPa 3 adjustable occlusion pressure: low-middle(default)-high
Alarm	Use battery, Door open, Occlusion, Almost done, Forget operate, Infusion completion, Low Battery, Battery exhausted, malfunction etc.
	Anti-bolus (diminishes the unwanted volume of Bolus after removal of occlusion)
	Ultrasound sensor detection with four levels of air in line alarm adjustable
	Intelligent pressure detection alarm
	Anti-reverse detection
	History records and can be transferred to computer
	Screen simultaneously display the infusion rate, drip rate, VTBI, volume infused, real time etc.
Function	Bolus
	Adjustable buzzer volume
	KVO
	Removable pump body for easy cleaning
Power supply	DC:12±1.2V AC:100~240V, 50/60HZ
Battery	Rechargeable Li Polymer battery, 7.4V 1900mAh
Battery charging time	10 hours with power on, 3 hours with power off
Battery operating time	About 6 hours at 25ml/h
Power consumption	25VA
Classification	Class I, type CF
Waterproof	IPx3
Dimension	145×100×120mm (LxWxH)
Weight	1.4Kg
Operating conditions	Temperature:5°C-40°C, Relative humidity:10-95%, Atmosphere pressure:86-106kPa
Transport conditions	Temperature:-20°C-60°C, Relative humidity:10-95%, Atmosphere pressure:50-106kPa
Storage conditions	Temperature:-20°C-45°C, Relative humidity:10-95%, Atmosphere pressure:50-106kPa

AccureMedicalPvt.Ltd.

Address:GroundFloorPlotno-183PocketN,Sector-2,DSIIDCIndustrialArea,NorthWest,
Delhi,110039

Web:www.accuremedical.in ,Contact:+918077818101,01204916914

Tollfree No.: 1800-419-9029

