



- 8-inch high-resolution color TFT/ LCD display
- Lasting working capability with built-in rechargeable lithium battery
- 400 groups of NIBP list, 60 alarm event record
- Central monitoring system applicable to ICU/CCU/OT
- Support solution: wall mounting, mobile trolley



Features :

- 8 inch high definition color TFT display
- Standard 3-parameter : NIBP, SPO2 & PR
- 2-4 hours battery power supply
- Sound, light & text alarm, adjustable volume
- Connected to central monitoring System

NIBP:

Method: Oscillometry

Modes: Manual/Auto/Continuous

Auto measure: time Adjustable

Measurement range : 10-270mmHg

SP02:

Measurement range: 0-100%

Accuracy: 70-100%, $\pm 2\%$ 0-69%,
unspecified

Pulse rate:

Range 20-254bpm

Accuracy ± 3 bpm

Respiration:

Method RA-LL impedance

Range

Adult: 0-120bpm

pediatric/neonatal:0-150bpm

Apnea alarm: Yes

Size: L9.5 * W6.5 * H8.5 inch

Weight: 1.700 kg

Electrical Specification:

100-240v AC, 50/60Hz

Max Input Power: 70VA

Battery:

11.1V 4000mAh rechargeable
lithium battery

Standard configuration:

SpO2, PR, NIBP