

Fetal Monitor F- 12 T



Functional Features

- 10.2 LED Touch-screen, 90 rotation sceen.
- CTG waveforms can be frozen.
- Thermal printer with 112 mm, synchronization print
- Auto interpretation and N T Grade.
- Equipped with High performance waterproof.
- Probe Upto 500 patie ts data saving, USB can be supported Data trransmitting to PC via USB Patie t's informaationan be input.
- Historical data can be reviewed and printed.
- Built-in rechargeable li-ion batery, AC/DC power conversion. Baaery Backup Up to 2.50 hours.
- Sleep mode to save energy and extend LED screens life.
- Portable design with hidden handle, convenient to carry.
- Multiple langua e support 7 level prinnting thicknessan be chosen.
- Adapt to 110 230V 50/60Hz AC Power supply.

Optional:-

Twin FHR facility



Specificaation			
Ultrasonic Operating Fequent	0"100 Unit	FHR Range	50-240 beats/min
Systolic Pressure	3MHz,110%	Paper Speed	3.2.3cm/min(0.3%)
Specificaation of Fuse	Manual/Audio	Recorder	High resolution Thermal Pri ter
Operation Mode	T1,GA 250V	Batery	Built in rechargeable Li-on batery 11.1v(220 mHh)
Recording Paper	112* 100MM 2 Fold Thermal Paper	Machine Site	107mm-255mm-91mm

Tollfree No.: 1800-419-9029