









*Compact and Sleek Design *Pressure Range-0 To 35 *With Humidifier *With Advance T, S/T, PC And TVAPS Mode

User-friendly Designed Humidifier

CONSTANT TEMPERATURE AND HUMIDIFICATION WITH MULTIPLE PROTECTION

- Open Tank, Mute Design
- The S-type Airway Ensures The Smooth Breathing







Easy Clean



Metal Material



Fast Heating



Good Humidification

Parameters	S/T TVAPS 25/30/35
CPAP	YES
AUTO	YES
S	YES
AUTO S	YES
S/T	YES
Т	YES
PC	YES
TVAPS	YES
ALARMS	YES
REAL TIME WAVEFORM	YES
PRESSURE RANGE	4-25/30/35
HUMIDIFICATION	0-5
EPFlex	
AUTO ALTITUDE COMENSATION	YES
AUTO LEAK COMPENSATION	YES
NOISE	30dB
WEIGHT	0.95kg (without humidifier)
DIMENSIONS	140mm* 156mm* 94mm(without humidifier)
LANGUAGE	Multiple





Pressure Range	4 to 35 cmH₂O (hPa)
Pressure Accuracy	± (0.5 hPa+4%)
Ramp Time	0 to 60 Min (5-min increments)
Starting Ramp Pressure	4 cmH2O to CPAP/Auto Pressure (CPAP/APAP mode);
	4cmH2O to IPAP(S,Auto S, S/T, T &VT Mode)
Res. Rate	540 BPM
Ti	0.1s- 4.0s
I Sensitive	Low, Medium, High
E Sensitive	Low, Medium, High
Leak Compensation	Automatic
Altitude Compensation	Automatic
Humidification	0 to 5
Data Storage Capacity	SD Card(4GB) & On-board :>1 Year
Dimensions	14x15.6x9.4cm (w/o humidifier) 26.2x15.6x9.4cm (w/ humidifier)
Weight	950g (w/o humidifier) 1500g (w/ humidifier)
Electrical Requirements	100-240 VAC, 50/60 Hz, 2.0- 1.0 A
Noise Level	<30 dB @ 10 cmH2O
Data Analysis Software	PC Based
Filter	Reusable Pollen/Fine Filter
Tubing	22mm, 6ft. (1.8m)
Device Controls	Control Dial/Push Button
Language	Chinese/English/Spanish
Operating Temperature	5° to 35° C (41° to 95° F)
Storage Temperature	-20° to 60° C (-4° to 140° F)
Relative Humidity (operating & storage)	10 to 93% (non-condensing)
	101 to 77 kPa (0-2286 m/0-7500 ft)
Risk Classification	Class IIa, Type BF, IP22

RegisteredAddress: Ground Floor Plot no -183 Pocket N, Sector-2, DSIIDC Industrial Area, North West, Delhi, 110039 **WorkAddress:** Industrial Unit - 39 Block- B, Sector- 63 Noida, Gautam Buddh Nagar, Uttar Pradesh- 201301

E-mail: info@accuremeidcal.in

Web: www.accuremedical.in, www.accu-mart.com

Service Helpline 18004199029

