



Accurate, Efficient and Durable Product features

- Classic display: 12 inch LCD display with multiple display format.
- HD display High definition display 1024 * 768.
- Simplified operation: Based on classic clinical design, UI operation is ultra simplified.
- Reliable quality: passed the rigorous multi application scenarios test, proved to be durable and helpful.
- Long operation hour: with inbuilt 8000mAh lithium battery, machine can be last for 4 hour after fully charged.
- Patented ECG specialized algorithm, passed AHA/MIT-BIH database verification.
- NIBP with anti-interference and anti-motion algorithm, generating accurate blood readings fastly.
- SpO2 with advanced anti-interference and lower perfusion detection technology.
- Based on black body light source technology, CO2 is with improved accuracy and reliability.
- Display 12 inch TFT screen, 1024*768, multiple displays including.
- Big font display, Oxy CRG display, etc Waveform: 7 lead wave form.
- Indicator alarm indicator, power indicator, battery indicator.
- Pulse rate sound, alarm sound Port specification port, AC port, LAN port, USB port.

Technical Specifications

Physical specs

Display 12 inch TFT screen, 1024*768, multiple displays including big font display, Oxy CRG display, etc Waveform: 7 lead wave form Indicator alarm indicator, power indicator, battery indicator, pulse rate sound, alarm sound Port specification port, AC port, LAN port, USB port

ECG

Lead- 3/5 lead

Waveform- 2 channel

Gain- X0.25, X0.5, X1, X2, X4 Speed, 12.5mm/s, 25mm/s, 20mm/s

HR range: 15~300BPM, (AUD); 15~350BPM (NEO)

Filter mode: DIA (0.05~100Hz); MON(0.5~40Hz); SUR(1~25Hz)

Protection: Anti-electric knife; Anti-defibrillation protection; 5000V isolation strength

ST diagnosis:- 2.5mV~2.5mV; Arrhythmia analysis; Pacing detection

NIBP

Principle: Oscillatio

Measurement mode: Manul/Auto/Continuous Pressure unit mmHg/Kpa

Measurement parameter: systolic, diastolic, mean

Systolic range: ADU 40~270mmHg, PED:40~200mmHg, NEO:

40~135mmHg

Diastolic range: ADU:10~210mmHg, PED:10~150mmHg,

NEO:10~100mmHg

Mean range: ADU:20~230mmHg, PED:20~165mmHg, NEO:

20~110mmHg

Accuracy: ± 3 mmHg Double over voltage protection

Co2

CO2 range: 0~150mmHg, accuracy, ± 2 mmHg, 0~40mmHg,

$\pm 5\%$ (41~100mmHg), $\pm 8\%$ 101~150mmHg

Respiratory rate range 0~150RPM Accuracy ± 2 RPM

Sampling flow 50ml/Min Applicable to ADU, PED, and NEO

RESP

Principle: Impedance Breathing

Range 0~120RPM

Choking alarm: 20s~60s optional, interval 5s

SpO2

SPO2:range(0~100) ,Resolution(1%)

Accuracy: $\pm 2\%$ (70~100%)

PR: range(20~254BPM), accurate (± 2 BPM)

AG Gas

Mode:Main stream/side stream

ISO: range:0-5% accuracy: 0.15Vol%+ reading 5%

SEV:range: 0-8% accuracy: 0.15xVol%+reading 5%

Co2: range :0-20% accuracy: 0.20Vol%+ reading 5%:

(0~5%) 0.20Vol%+ reading 8%: 5.1~20%

RESP:

range: 0~120RPM, accuracy: ± 2 RPM

Anesthetic gas ID automatic identification



Accure Medical Pvt. Ltd.

Registered Address: Ground Floor Plot no- 183 Pocket N, Sector- 2, DSIIIDC Industrial Area, North West, Delhi, 110039

Work Address: Industrial Unit-39, Block-B, Sector-63, Noida, Gautam Buddha Nagar, Uttar Pradesh- 201301

Web: www.accuremedical.in, **Contact:** +91 8077818101, 0120 4916914

Service Helpline
18001499029

