
Constraint Satisfaction

CS5491: Artificial Intelligence

ZHICHAO LU

Content Credits: Prof. Wei's CS4486 Course
and Prof. Boddeti's AI Course



WHAT ARE CONSTRAINT SATISFAC

Special kind of search problems.

- N variables
- Values from domain D
- assignment satisfies constraints

States: partial assignment

Goal Test: satisfies all constraints

Successor Function: assign an unassigned variable




TODAY

Constraint Satisfaction

Reading

- Today's Lecture: RN Chapter 6



XKCD

WHAT IS SEARCH FOR?



WHAT IS SEARCH FOR?

Given assumptions about the world: a single agent, deterministic actions, fully observed state, discrete state space



WHAT IS SEARCH FOR?

Given assumptions about the world: a single agent, deterministic actions, fully observed state, discrete state space

- Planning: sequences of actions
 - The path to the goal is the important thing
 - Paths have various costs, depths
 - Heuristics give problem-specific guidance



WHAT IS SEARCH FOR?

Given assumptions about the world: a single agent, deterministic actions, fully observed state, discrete state space

- Planning: sequences of actions
 - The path to the goal is the important thing
 - Paths have various costs, depths
 - Heuristics give problem-specific guidance
- Identification: assignments to variables
 - The goal itself is important, not the path
 - All paths at the same depth (for some formulations)
 - CSPs are a specialized class of identification problems



CONSTRAINT SATISFACTION PROBLEMS



WHAT ARE CONSTRAINT SATISFAC



WHAT ARE CONSTRAINT SATISFACTION PROBLEMS?

Standard search problems:

- State is a "black box": arbitrary data structure
- Goal test can be any function over states
- Successor function can also be anything



WHAT ARE CONSTRAINT SATISFACTION PROBLEMS?

Standard search problems:

- State is a "black box": arbitrary data structure
- Goal test can be any function over states
- Successor function can also be anything

Constraint satisfaction problems (CSPs):

- A special subset of search problems
- State is defined by variables $\mathbf{X}_i$ with values from a domain $\mathbf{D}$ (sometimes $\mathbf{D}$ depends on i)
- Goal test is a set of constraints specifying allowable combinations of values for subsets of variables



WHAT ARE CONSTRAINT SATISFACTION PROBLEMS?

Standard search problems:

- State is a "black box": arbitrary data structure
- Goal test can be any function over states
- Successor function can also be anything


Constraint satisfaction problems (CSPs):

- A special subset of search problems
- State is defined by variables $\mathbf{X}_i$ with values from a domain $\mathbf{D}$ (sometimes $\mathbf{D}$ depends on i)
- Goal test is a set of constraints specifying allowable combinations of values for subsets of variables


Allows useful general-purpose algorithms with more power than standard search algorithms



CSP EXAMPLE




EXAMPLE: MAP COLORING



EXAMPLE: MAP COLORING


Variables: WA, NT, Q, NSW, V, SA, T



EXAMPLE: MAP COLORING

Variables: WA, NT, Q, NSW, V, SA, T

Domains: $D = \{red, green, blue\}$




EXAMPLE: MAP COLORING

Variables: WA, NT, Q, NSW, V, SA, T

Domains: $D = \{red, green, blue\}$

Constraints: adjacent regions must have different colors




EXAMPLE: MAP COLORING

Variables: WA, NT, Q, NSW, V, SA, T

Domains: $D = \{red, green, blue\}$

Constraints: adjacent regions must have different colors

- Implicit: $WA \neq NT$
- Explicit: $(WA, NT) \in (red, green), (red, blue), \dots$



EXAMPLE: MAP COLORING


Variables: WA, NT, Q, NSW, V, SA, T

Domains: $D = \{red, green, blue\}$

Constraints: adjacent regions must have different colors

- Implicit: $WA \neq NT$
- Explicit: $(WA, NT) \in (red, green), (red, blue), \dots$

Solutions: Assignments that satisfy all constraints, e.g.:



EXAMPLE: MAP COLORING

Variables: WA, NT, Q, NSW, V, SA, T


Domains: $D = \{red, green, blue\}$

Constraints: adjacent regions must have different colors

- Implicit: $WA \neq NT$
- Explicit: $(WA, NT) \in (red, green), (red, blue), \dots$

Solutions: Assignments that satisfy all constraints, e.g.:

- $\{WA=red, NT=green, Q=red, NSW=green, V=red, SA=blue, T=green\}$



CONSTRAINT GRAPHS



CONSTRAINT GRAPHS

Binary CSP: each constraint relates two variables



CONSTRAINT GRAPHS

Binary CSP: each constraint relates two variables

Constraint Graph: nodes are variables, arcs are constraints



CONSTRAINT GRAPHS

Binary CSP: each constraint relates two variables

Constraint Graph: nodes are variables, arcs are constraints

General-purpose CSP algorithms use the graph structure to speed up search. E.g., Tasmania is an independent subproblem.




CONSTRAINT GRAPHS


Binary CSP: each constraint relates two variables

Constraint Graph: nodes are variables, arcs are constraints

General-purpose CSP algorithms use the graph structure to speed up search. E.g., Tasmania is an independent subproblem.




EXAMPLE: N QUEENS



EXAMPLE: N QUEENS

Formulation 1:



EXAMPLE: N QUEENS

Formulation 1:

- Variables: X_{ij}
- Domains: $\{0, 1\}$
- Constraints:


$$\forall i, j, k \quad (X_{ij}, X_{ik}) \in (0, 0), (0, 1), (1, 0)$$

$$\forall i, j, k \quad (X_{ij}, X_{kj}) \in (0, 0), (0, 1), (1, 0)$$


$$\forall i, j, k \quad (X_{ij}, X_{i+k, j+k}) \in (0, 0), (0, 1), (1, 0)$$

$$\forall i, j, k \quad (X_{ij}, X_{i+k, j-k}) \in (0, 0), (0, 1), (1, 0)$$

$$\sum_{ij} X_{ij} = N$$




EXAMPLE: N QUEENS



EXAMPLE: N QUEENS


Formulation 2:



EXAMPLE: N QUEENS

Formulation 2:

- Variables: Q_k
- Domains: $1, 2, 3, \dots, N$
- Constraints:
 - Implicit: $\forall(i, j)$ non – threatening (Q_i, Q_j)
 - Explicit: $(Q_1, Q_2) \in \{(1, 3), (1, 4), \dots\}$



VARIETY OF CSPS

Discrete Variables



VARIETY OF CSPS

Discrete Variables

- Finite domains



VARIETY OF CSPs

Discrete Variables

- Finite domains
 - Size d means $O(d^n)$ complete assignments
 - E.g., Boolean CSPs, including Boolean satisfiability (NP-complete)



VARIETY OF CSPS

Discrete Variables

- Finite domains
 - Size d means $O(d^n)$ complete assignments
 - E.g., Boolean CSPs, including Boolean satisfiability (NP-complete)
- Infinite domains (integers, strings, etc.)
 - E.g., job scheduling, variables are start/end times for each job
 - Linear constraints solvable, nonlinear undecidable



VARIETY OF CSPS

Discrete Variables

- Finite domains
 - Size d means $O(d^n)$ complete assignments
 - E.g., Boolean CSPs, including Boolean satisfiability (NP-complete)
- Infinite domains (integers, strings, etc.)
 - E.g., job scheduling, variables are start/end times for each job
 - Linear constraints solvable, nonlinear undecidable

Continuous variables

- E.g., start/end times for Hubble Telescope observations
- Linear constraints solvable in polynomial time by LP methods



VARIETIES OF CONSTRAINTS

Varieties of Constraints



VARIETIES OF CONSTRAINTS

Varieties of Constraints

- Unary constraints involve a single variable (equivalent to reducing domains), e.g.: $SA \neq green$



VARIETIES OF CONSTRAINTS

Varieties of Constraints

- Unary constraints involve a single variable (equivalent to reducing domains), e.g.: $SA \neq \textit{green}$
- Binary constraints involve pairs of variables, e.g.: $SA \neq WA$



VARIETIES OF CONSTRAINTS

Varieties of Constraints

- Unary constraints involve a single variable (equivalent to reducing domains), e.g.: $SA \neq green$
- Binary constraints involve pairs of variables, e.g.: $SA \neq WA$
- Higher-order constraints involve 3 or more variables: e.g., cryptarithmic column constraints



VARIETIES OF CONSTRAINTS

Varieties of Constraints

- Unary constraints involve a single variable (equivalent to reducing domains), e.g.: $SA \neq \textit{green}$
- Binary constraints involve pairs of variables, e.g.: $SA \neq WA$
- Higher-order constraints involve 3 or more variables: e.g., cryptarithmic column constraints

Preferences (soft constraints):

- E.g., red is better than green
- Often representable by a cost for each variable assignment
- Leads to constrained optimization problems



REAL-WORLD CSPS

Scheduling problems: e.g., when can we all meet?

Timetabling problems: e.g., which class is offered when and where?

Assignment problems: e.g., who teaches what class

Hardware configuration

Transportation scheduling

Factory scheduling

Circuit layout

Fault diagnosis

...



SOLVING CSPPS



EXAMPLE: MAP COLORING

Variables: WA, NT, Q, NSW, V, SA, T


Domains: $D = \{red, green, blue\}$

Constraints: adjacent regions must have different colors

- Implicit: $WA \neq NT$
- Explicit: $(WA, NT) \in (red, green), (red, blue), \dots$

Solutions: Assignments that satisfy all constraints, e.g.:

- $\{WA=red, NT=green, Q=red, NSW=green, V=red, SA=blue, T=green\}$



STANDARD SEARCH FORMULATION

Standard search formulation of CSPs



STANDARD SEARCH FORMULATION

Standard search formulation of CSPs

States defined by the values assigned so far (partial assignments)

- Initial state: the empty assignment, $\{\}$
- Successor function: assign a value to an unassigned variable
- Goal test: the current assignment is complete and satisfies all constraints



STANDARD SEARCH FORMULATION

Standard search formulation of CSPs

States defined by the values assigned so far (partial assignments)


- Initial state: the empty assignment, $\{\}$
- Successor function: assign a value to an unassigned variable
- Goal test: the current assignment is complete and satisfies all constraints

Start with straightforward search and then improve.



SEARCH METHODS


What would BFS do?



SEARCH METHODS

What would BFS do?

What would DFS do?




SEARCH METHODS

What would BFS do?

What would DFS do?

What problems does naïve search have?



Q & A



XKCD

