

Electronic Bidet

◆ Specification

Item	Content
Model name	BIDET-ELEC-3616-WH / BIDET-ELEC-3618-WH
Rated power	AC 220-240V 50/60Hz 1550W
Power cord	1.6 m
Water pressure	0.1 ~ 0.7MPa
Warm washing	Water flow rate
	Washing 0.40~0.65L/min
	Bidet washing 0.40~0.65L/min
	Water pressure control
	Anus washing, bidet washing for 4 steps, control led by micro computer
	Temperature control
	4-step adjustment (OFF, about 34°C, 37°C and 40°C)
Warm seat	Tank capacity
	325mL
	Power
	1500W
	Safety device
	Float switch, temp sensor, Bi-metal sensor, temp fuse
	45W
Warm wind	Soft seat
	When closing, the seat and cover fall down slowly
	Temperature control
	4-step adjustment (OFF, about 34°C, 37°C and 40°C)
Scope of Use:	Power
	270W (max)
	Temperature control
	BIDET-ELEC-3616-WH: 4-step adjustment (OFF, about 40°C, 50°C, and 55°C) BIDET-ELEC-3618-WH: 5-step adjustment (OFF, about 40°C, 45°C, 50°C, and 55°C)
Safety device	
Temp fuse	
Max ambient: 40 °C Medium temperature: 35 °C max. Inlet water pressure (Min-Max): 0.10 Mpa – 0.70 Mpa	

The standard for this machine: EN60335-1:2002 EN60335-2-84:2003