
## Search Algorithms


### iform Cost Search

```
if child not in union (frontier, explored)
                                                                                                                                                                                                                                                                                                                                                                                                                           frontier.decide_and_replace(child)
                                                                                                                                                                          if IS GOAL (node): return SOLUTION (node)
                                                                                                                                                                                                                                                                                child = APPLY(node, action)
                                                                                                                                                                                                                                               for action in node.get_actions():
                                                                                                                                                                                                                                                                                                                                                                                        if child in frontier:
                                                                                                                                                                                                                                                                                                                                                      frontier.add(child)
                                                                                                                                      node = frontier.pop()
                                                                                                   .e not empty(frontier):
                                                                                                                                                                                                            explored.add (node)
                                ltier = heap({node})
                                                                                                                                                                                                                                                                                                                                                                                          else
                                                                  ored = {}
start
```


Path Cost
Path Cost
Path Cost
Path Cost
Path Cost





Path Cost
Path Cost
Path Cost
Path Cost
Path Cost





Path Cost
Path Cost
Path Cost
Path Cost
Path Cost


























## directional Uniform Cost Search


## η manner of expanding frontiers is OK

- Alternating both frontiers good for parallel computing
- Taking the min good in weighted graphs where hubs have high cost

#### opping criterion:

```
min(forward) + min(reverse) > shortest_path_in_graph
```

 Note: intersection of explored sets, means you check for your stopping criterion when you POP from the queue.



#### Search


nange the heap sort to include a heuristic function


$$f(state) = h(state) + g(state)$$


noice of a good heuristic:


- Admissible: underestimates
- Consistent (strict): monotonic


ne better the heuristic, the quicker the search





















Path Cost
Path Cost
Path Cost
Path Cost
Path Cost


Path Cost
Path Cost
Path Cost
Path Cost
Path Cost

Path Cost
Path Cost
Path Cost
Path Cost
Path Cost 40 +8 60+2 48+2


Path Cost
Path Cost
Path Cost
Path Cost
Path Cost 40 +8 60+2 48+2



# hoosing Good Heuristics



Start State



Goal State

