

26-Port Gigabit Unmanaged Ethernet Switch

24*10/100/1000M RJ45 ports + 2*1000M SFP ports



S200-26GP-S2-AC



Non-blocking, low delay design



Plug and Play, PoE watch dog



Eco-friendly and energy-saving



| Product Overview

The S200 series of Ethernet switches adopts low power consumption design, which meets the requirements of green environmental protection and energy saving; all ports support auto-MDI/MDI-X and wire-speed forwarding, ensuring stable and reliable data transmission.

| Key Features

- Supports IEEE 802.3 af/at, PoE management, and PoE Watchdog;
- 4KV port lightning protection;
- ESD: contact 8KV, air 15KV;
- -10~50°C wide operating temperature range;
- Support MDI/MDIX.

| Hardware Features

Model	S200-26GP-S2-AC
Interface	24*10/100/1000M RJ45 ports + 2*1000M SFP ports
Switching Capacity	52Gbps
Packets Forwarding Rate	38.6Mpps
MAC	8K
Port Buffer	4.1M
Transfer Delay	<10us
Power Supply	AC 100-240V 50/60Hz
	Empty Load Power: <15W
LED Indicators	PWR,Link/ACT
PoE	1-24 ports support PoE
	IEEE 802.3 af/at standards
	PoE power: 300W
	PIN Sequence: 1,2+/3,6-
Environment	Working Temperature: -10°C ~ 50°C
	Storage Temperature: -40°C ~ 70°C
	Working Humidity: 10%~95% non-condensing
	Storage Humidity: 10%~95% non-condensing

Model	S200-26GP-S2-AC
DIP Specification	AI POE Port 250m transmission Port port isolation Storm control
Size(W*D*H)	440*280*44mm
Weight	3.9KG
EMC	Power Surge Protection: 6KV/2KV Ethernet Port Surge Protection: 4KV/2KV Anti-static Interference: 8KV/15KV Free Drop: 0.5M
Certificate Compliance	CE/FCC/RoHS

Product Dimensions

