

S200-28XGCPM-X4C8-ACR L3 Managed PoE Switch

Input Voltage: AC 100~240V/50-60HZ

Operating Temperature: -10°C ~ +50°C

Heat Dissipation mode: fan for heat dissipation

Certificate: CE/FCC/RoHS

Anti-Static: 8KV-15KV

MTBF: 100000 hours



Product Description

L3 managed switch with 4*1G/10G Base-X+16*10/100/1000 Base-T+8*100/1000M RJ45/SFP combo. Each RJ45 port supports MDI/MDIX auto flip and wire speed forwarding function. Using store-and-forward mode, combined with QOS technology, to ensure the effective allocation of bandwidth to each port provides security monitoring equipment such as high-power AP, network cameras, PTZ dome cameras, and POE lighting, providing improved ease of use, highly secure business operations, improved sustainability, and a borderless network experience. For stable and reliable power and data transmission.

Parameter



Interfaces

Fixed port	4*1G/10G Base-X+8*100/1000 Combo+ 16*10/100/1000 Base - T
Management Port	Support console + USB port
Power interface	220V/AC
LED Indicator	PWR, SYS, Link/ACT LED

Cable Type & Transmission Distance

Twisted-pair	0-100m (CAT5e,CAT6)
Monomode optical fiber	20/40/60/80/100KM
Multimode optical fiber	550m

Network Topology

Ring topology	Support
Star topology	Support
Bus topology	Support
Tree Topology	Support
Hybrid topology	Support

Electrical Specifications

Input voltage	AC 100-240V 50/60Hz
Total Power consumption	≤400W
Main board power	<34W

PoE

PoE port	1-24
PoE Protocol	IEEE802.3af, IEEE802.3at
Pin Assignment	1,2+;3,6-
PoE Management	Support

Layer 2 Switching

Switching capacity	128Gbps
Packet forwarding rate	95.23Mpps
MAC address table	16K
Buffer	12M Bit

Forwarding delay	<10us
MDI/MDIX	Support
VLAN	4000
GARP VLAN	Support
Protocol VLAN	Support
Voice VLAN	Support
Surveillance VLAN	Support
MAC VLAN	Support
Ethernet channel/ 802 .3ad	Support
LACP	Support
Interface Speed	Support
Duplex Mode	Support
Flow Control	Support
Jumbo frame	Support
DHCP Client	Support
SNTP Client	Support
Port Statistics	Support
Protected Ports	Support
EEE	Support
ERPS	Support
LLDP	Support
LLDP 802.1 TLV	Support
MSTP / RSTP / STP	Support
STP BPDU Filter	Support
STP BPDU guard	Support
(STP Port Fast	Support
IGMP Snooping	Support
MLD Snooping	Support
MVR	Support
DHCP Interface Preferred IP Binding	Support
Device scan	Support

Layer 3 Route

IPV4 management address	Support
IPV6 management address	Support
Dynamic routing	OSPF, RIP

Static routes IPv6	Support
VRRP	Support
ARP	Support
Lookback interface	Support

Convergence

ACL	Support MAC Standard/Extended ACL
	Support IPV4 Standard/Extended ACL
	Support IPV6 Standard/Extended ACL
QoS	Support QoS Remarking
	Support Port Trust
	Support Port bandwidth
	Support egress queuing bandwidth
	Support SP, WRR
	Support COS, DSCP, IP Priority

Management

User Management	Support
System Log	Support
Upgrade Firmware	Support
Configuration File Download/Upload	Support
SNMP	Support SNMP V1/V2/V3
WEB management	Support
Console	Support
CLI	Support
Telnet/SSH	Support
RMON	Support

Security

Management channel configuration	Support
AAA Authentication	Support
802.1X Authentication	Support
MAC-Based Authentication	Support
WEB-Based Authentication	Support
DoS anti-attack	Support
Dynamic ARP Inspection	Support
DHCP Snooping	Support

IP Source Guard	Support
Port Security	Support
Protected Ports	Support
Storm control	Support

Equipment Diagnosis

Console log	Support
RAM log	Support
Flash log	Support
Port mirroring	Support 1:1 or M:1
Ping	Support
Traceroute	Support
Ethernet port test	Support
DDM	Support
UDLD protocol	Support

Environment

Operating temperature	-10°C~+50°C
Storage temperature	-40°C~+75°C
Relative humidity	10% to 90% RH
Thermal methods	Fan for heat dissipation
MTBF	100,000 hours

Mechanical Dimensions

Product size	440*280*44mm
Installation Method	Rack mounted
Weight	3.15KG

EMC & Ingress Protection

Surge protection of Power	Common mode 6KV, differential mode 2KV
Surge protection of Ethernet port	Common mode 4KV, differential mode 2KV
ESD	Contact 8K, Air 15K
Free fall	0.5m

Certificate

Certificate	CE/FCC/RoHS
-------------	-------------

Accessories

Accessories

Devices, power cord, inspection certificate, user manual, dust plug

Size

