

S200-54XGPM-X6-ACR L3 Managed POE Switch

Input Voltage: AC 100~240V/50-60HZ

Working Temp: -10°C ~ +55°C

Heat dissipation method: Fan

Report : CCC/CE/FCC/ROHS

ESD: 8KV-15KV



Describe



S200-54XGPM-X6-ACR

L3 managed switch with 6*10G Base-X+48*10/100/1000 Base-T. Each RJ45 port supports MDI/MDIX auto flip and wire speed forwarding function. Using store-and-forward mode, combined with QOS technology, to ensure the effective allocation of bandwidth to each port provides security monitoring equipment such as high-power AP, network cameras, PTZ dome cameras, and POE lighting.providing improved ease of use, highly secure business operations, improved sustainability, and a borderless network experience.For stable and reliable power and data transmission.

Parameter



(Provider Mode Ports)

(Fixed port)	6*10G Base-X+48*10/100/1000 Base - T
(Management Port)	Support console + USB Ports
(Power interface)	220V/AC
(LED Indicators)	PWR, SYS, Link/ACT LED

(Cable type&Transmission distance)

(Twisted-pair)	0-100m (CAT5e,CAT6)
(Mono mode optical fiber)	20/40/60/80/100KM
(Multi mode optical fibre)	550m

(Network Topology)

(Ring topology)	Support
(Star topology)	Support
(Bus topology)	Support
(Tree Topology)	Support
(Hybrid topology)	Support

(Electrical Specifications)

(input voltage)	AC 100-240V 50/60Hz
(Total Power consumption)	≤400 W
(POE port)	1-48 Ports
(POE Protocol)	IEEE 802.3af, 802.3at
(Pin Assignment)	1,2+;3,6-
(POE Management)	Support

(Layer 2 Switching)

(Switching capacity)	216 G
(Packet forwarding rate)	160.7Mpps
(MAC address table)	32 K
(Buffer)	16 M
(Forwarding delay)	<10us
(MDX/MIDX)	Support
(VLAN)	3 k
(GVRP)	Support

(Protocol VLAN)	Support
(Voice VLAN)	Support
(Surveillance VLAN)	Support
MAC VLAN	Support
(Ether channel/ 802 .3ad)	Support
(LACP)	Support
(Interface Speed)	Support
(Duplex Mode)	Support
(Flow Control)	Support
(Jumbo frame)	Support 10K byte
(DHCP Server)	Support
(DHCP Client)	Support
(DNS Client)	Support
SNTP Client	Support
(Port Statistics)	Support
(Protected Ports)	Support
(EEE)	Support
(Ethernet Ring Protection Switching)	Support
(LLDP)	Support
(LLDP 802.1 TLV)	Support
(MSTP / RSTP / STP)	Support
(STP BPDU Filter)	Support
(STP BPDU guard)	Support
(STP Port Fast)	Support
(IGMP Snooping)	Support
(MLD Snooping)	Support
(MVR)	Support

(Layer 3 Route)

(IPV4 Managed)	Support
(IPV6 Managed)	Support
(IPV4 Dynamic Routing)	OSPF、RIP
(Static Routes IPv6)	Support
(ARP)	Support
(Loop back Interface)	Support
(DHCP Server)	Support
(DNS Server)	Support

(DNS Client)	Support
(Convergence)	
(ACL)	Support MAC Standard/ Expand ACL
	Support IPv4 Standard/ Expand ACL
	Support IPv6 Standard/ Expand ACL
(QOS)	Support QOS Remark
	Support Port Trust
	Support Port Speed Limited
	Support Port Queue Limited
	Support SP, WRR
	Support COS Mapping, DSCP Mapping, IP Priority Mapping
(Management)	
(User Management)	Support
(System Log)	Support
(Upgrade Firmware)	Support
(Configuration File Download/Upload)	Support
(SNMP)	Support SNMP V1/V2/V3
(WEB Managed)	Support
(Console)	Support
(CLI)	Support
(Telnet/SSH)	Support
(RMON)	Support
(Security)	
(Managed Channel Configuration)	Support
(AAA Certification)	Support
(802.1X Certification)	Support
(MAC-Based Certification)	Support
(WEB-Based Certification)	Support
(Dos Proof)	Support
(ARP Detection)	Support
(DHCP Snooping)	Support
(IP Source Guard)	Support
(Port Security)	Support
(Protected Ports)	Support
(storm control)	Support

(Equipment diagnosis)

(Console Log)	Support
(RAM Log)	Support
(Flash Log)	Support
(Port Mirror)	Support 1: 1 or 1: M
(Ping)	Support
(Trace route)	Support
(Port Detection)	Support
Optical Module	Support
UDLD Protocol	Support

(Environment)

(Temperature)	Working Temp: -10°C ~ 55°C Storage Temp: -40°C ~ 75°C
(Relative humidity)	Working Humidity: 10% ~90% RH Storage Humidity: 5% ~90% RH
(Thermal methods)	Fan
(MTBF)	100,000 Hours

(Mechanical Dimensions)

(Product size)	440*280*44mm
(Installation Method)	Rack-Mount
(Weight)	3.1KG

(EMC&INGRESS PROTECTION)

(Surge protection of Power)	IEC 61000-4-5 Level 4 (6KV/4KV)
(Surge protection of Ethernet port)	IEC 61000-4-5 Level 4 (6KV/4KV)
(ESD)	IEC 61000-4-2 Level 4 (8K/15K)
(Free fall)	0.5m

(Accessories)

(Accessories)	Device, Terminals, Specification, Certificate ,Adapter(optional)
---------------	--

Sizes

