

Unmanaged Industrial Switch

XPTN-9000-45-1GX8GP

XPTN-9000-45-1GX8GT

Features & Benifits

- Input Voltage: DC12~58V for Non-PoE, DC48~58V for PoE
- Operating Temperature: -40°C~75°C
- Shell: IP40 protection
- Fanless design, low power consumption
- ESD: contact 8KV, air 15KV
- MTBF: 100,000 hours



| Product Introduction

The XPTN-9000 45 Series is specially designed for harsh industrial environments, which provides economic solutions for industrial Ethernet networking. Support wide working temperature -40°C~75°C.

Redundant DC power supply, adopts rugged aluminum alloy housing, and passed high level tests of EMI/EMC. It also has gone through the strict aging test, meeting the requirements of transportation industry.

| Technical Reference

- | | |
|-----------------------------|------------------------------|
| ● IEEE 802.3 CSMA/CD method | ● IEEE 802.3 10Base-T |
| ● IEEE 802.3 af PoE | ● IEEE 802.3u 100Base-X |
| ● IEEE 802.3 at PoE+ | ● IEEE 802.3u 100Base-FX |
| ● IEEE 802.3x Flow Control | ● IEEE 802.3z Gigabit SX/LX |
| ● IEEE 802 Networks | ● IEEE 802.3ab Gigabit 1000T |

| EMC & Protection

- IP Class: IP40
- Surge of Power: IEC 61000-4-5 Level 3 (4KV/2KV (1.2/50us)
- Surge of Ethernet Port: IEC 61000-4-5 Level 3 (4KV/2KV) (10/700us)
- ESD: IEC 61000-4-2 Level 4 (8K/15K)
- Free Fall: 0.5m

| Hardware Specifications

Items	XPTN-9000-45-1GX8GT	XPTN-9000-45-1GX8GP
Interface	1*1000M SFP port, 8*10/100/1000 Base-TX	
Switching	20Gbps	
Packets Forwarding Rate	14.88Mpps	
MAC	16K	
Port Buffer	2M	
Forwarding Delay	<5us	
Power Supply	Phenix terminal, DC redundant input	
	Input Voltage: DC12-58V	Input Voltage: DC48-58V
	Empty Load Power: <5W	
LED Indicators	PWR, Link/ACT	
PoE	—	1-8 ports support PoE
		PoE budget: 240W
		IEEE802.3 af/at standard
		PIN Sequence: 1,2+/3,6-
Environment	Working Temperature: -40°C ~ 75°C	
	Storage Temperature: -40°C ~ 85°C	
	Working Humidity: 5%~95% non-condensing	
	Storage Humidity: 5%~95% non-condensing	
SIZE(W*D*H)	143*104*46mm	
Weight	0.55KG	0.60KG
Installation Method	Din Rail	
Certificate Compliance	CE/FCC/RoHS	
MTBF	100,000 hours	

| Product Dimension

