

Unmanaged Industrial Switch

XPTN-9000-45-2GX4GP
XPTN-9000-45-2GX4GT

Features & Benefits

- Input Voltage: DC12~58V for Non-PoE, DC48~58V for PoE
- Operating Temperature: -40°C~75°C
- Shell: IP40 protection
- Fanless design, low power consumption
- ESD: contact 8kV, air 15kV
- MTBF: 100,000 hours



| Product Introduction

The XPTN-9000 45 Series is specially designed for harsh industrial environments, which provides economic solutions for industrial Ethernet networking. Support wide working temperature - 40 °C~75°C.

Redundant DC power supply, adopts rugged aluminum alloy housing, and passed high level tests of EMI/EMC. It also has gone through the strict aging test, meeting the requirements of transportation industry.

| Technical Reference

- | | |
|-----------------------------|------------------------------|
| ● IEEE 802.3 CSMA/CD method | ● IEEE 802.3 10Base-T |
| ● IEEE 802.3 af PoE | ● IEEE 802.3u 100Base-X |
| ● IEEE 802.3 at PoE+ | ● IEEE 802.3u 100Base-FX |
| ● IEEE 802.3x Flow Control | ● IEEE 802.3z Gigabit SX/LX |
| ● IEEE 802 Networks | ● IEEE 802.3ab Gigabit 1000T |

| EMC & Protection

- IP Class: IP40
- Surge of Power: IEC 61000-4-5 Level 3 (4kV/2kV (1.2/50us)
- Surge of Ethernet Port: IEC 61000-4-5 Level 3 (4kV/2kV) (10/700us)
- ESD: IEC 61000-4-2 Level 4 (8k/15k)
- Free Fall: 0.5m

| Hardware Specifications

Model	XPTN-9000-45-2GX4GT	XPTN-9000-45-2GX4GP
Interface	2*1000 Base-FX + 4*10/100/1000 Base-TX	
Switching	12Gbps	
Packets Forwarding Rate	8.92Mpps	
MAC	2K	
Port Buffer	1M	
Forwarding Delay	<5us	
Power Supply	Phoenix terminal, DC redundant input	
	Input Voltage: DC12-58V	Input Voltage: DC48-58V
	Empty Load Power: <5W	
LED Indicators	PWR, Link/ACT	
PoE	—	1-4 ports support PoE
		PoE budget: 125W
		IEEE802.3 af/at standard
		PIN Sequence: 1,2+/3,6-
Environment	Working Temperature: - 40 °C ~ 75°C	
	Storage Temperature: - 40 °C ~ 75°C	
	Working Humidity: 5%~95% non-condensing	
	Storage Humidity: 5%~95% non-condensing	
DIP Specification	· QoS · Storm Control · Port Isolation · Flow Control	· PoE Watchdog · 250m Extend · Port Isolation · Flow Control

SIZE(W*D*H)	143*104*46mm	
Weight	0.55KG	0.57KG
Installation Method	DIN Rail	
Certificate Compliance	CE/FCC/RoHS	
MTBF	100,000 hours	

| Product Dimension

