

## Unmanaged Industrial Switch

**XPTN-9000-45-5TP**  
**XPTN-9000-45-5TX**

### Features & Benifits

- Input Voltage: DC12~58V for Non-PoE, DC48~58V for PoE
- Operating Temperature: -40°C~75°C
- Shell: IP40 protection
- Fanless design, low power consumption
- ESD: contact 8KV, air 15KV
- MTBF: 100,000 hours



### | Product Introduction

The XPTN-9000 45 Series is specially designed for harsh industrial environments, which provides economic solutions for industrial Ethernet networking. Support wide working temperature -40°C~75°C.

Redundant DC power supply, adopts rugged aluminum alloy housing, and passed high level tests of EMI/EMC. It also has gone through the strict aging test, meeting the requirements of transportation industry.

### | Technical Reference

- |                             |                          |
|-----------------------------|--------------------------|
| ● IEEE 802.3 CSMA/CD method | ● IEEE 802.3 10Base-T    |
| ● IEEE 802.3 af PoE         | ● IEEE 802.3u 100Base-X  |
| ● IEEE 802.3 at PoE+        | ● IEEE 802.3u 100Base-FX |
| ● IEEE 802 Networks         |                          |

## | EMC & Protection

- IP Class: IP40
- Surge of Power: IEC 61000-4-5 Level 3 (4KV/2KV (1.2/50us)
- Surge of Ethernet Port: IEC 61000-4-5 Level 3 (4KV/2KV) (10/700us)
- ESD: IEC 61000-4-2 Level 4 (8K/15K)
- Free Fall: 0.5m

## | Hardware Specifications

| Model                   | XPTN-9000-45-5TX                                                                                                                                | XPTN-9000-45-5TP         |
|-------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|
| Interface               | 5*10/100M RJ45 ports                                                                                                                            |                          |
| Switching               | 1Gbps                                                                                                                                           |                          |
| Packets Forwarding Rate | 0.744Mpps                                                                                                                                       |                          |
| MAC                     | 2K                                                                                                                                              |                          |
| Port Buffer             | 768K                                                                                                                                            |                          |
| Forwarding Delay        | <5us                                                                                                                                            |                          |
| Power Supply            | Phenix terminal, DC redundant input                                                                                                             |                          |
|                         | Input Voltage: DC12-58V                                                                                                                         | Input Voltage: DC48-58V  |
|                         | Empty Load Power: <5W                                                                                                                           |                          |
| LED Indicators          | P1,P2,Link/ACT LED                                                                                                                              |                          |
| PoE                     | —                                                                                                                                               | 1-4 ports support PoE    |
|                         |                                                                                                                                                 | PoE budget: 125W         |
|                         |                                                                                                                                                 | IEEE802.3 af/at standard |
|                         |                                                                                                                                                 | PIN Sequence: 1,2+/3,6-  |
| Environment             | Working Temperature: -40°C ~ 75°C                                                                                                               |                          |
|                         | Storage Temperature: -40°C ~ 75°C                                                                                                               |                          |
|                         | Working Humidity: 5%~95% non-condensing<br>Storage Humidity: 5%~95% non-condensing                                                              |                          |
| DIP Specification       | <ul style="list-style-type: none"> <li>• LFD (Link Fault Diversion )</li> <li>• Reserve</li> <li>• Port Isolation</li> <li>• Reserve</li> </ul> |                          |

| Model                  | XPTN-9000-45-5TX | XPTN-9000-45-5TP |
|------------------------|------------------|------------------|
| SIZE(W*D*H)            | 118*91*31mm      |                  |
| Weight                 | 0.36KG           | 0.38KG           |
| Installation Method    | Din Rail         |                  |
| Certificate Compliance | CE/FCC/RoHS      |                  |
| MTBF                   | 100,000 hours    |                  |

## | Product Dimension

