

L2 Managed Industrial Switch

**XPTN-9000-85-4XG24GX-HR-V**  
**XPTN-9000-85-4XG24GX-R-V**

## Features & Benifits

- Input Voltage: DC12~58V/AC 100~240V 50-60Hz
- Operating Temperature: -40°C~75°C
- Shell: IP40 protection
- Fanless design, low power consumption
- ESD: contact 8KV, air 15KV
- MTBF: 100,000 hours



## | Product Introduction

The XPTN-9000 85 Series is specially designed for harsh industrial environments, which provides economic solutions for industrial Ethernet networking. Support wide working temperature -40°C~75°C.

Redundant AC+DC power supply, adopts rugged aluminum alloy housing, and passed high level tests of EMI/EMC. It also has gone through the strict aging test, meeting the requirements of transportation industry.

## | Technical Reference

- IEEE 802.3 10BASE-T
- IEEE 802.3u 100BASE-TX
- IEEE 802.3z Gigabit SX/LX
- IEEE 802.3ab Gigabit 1000T
- IEEE 802.3bz 2.5GBASE-X
- IEEE 802.3x flow control and back pressure
- IEEE 802.3ad port trunk with LACP
- IEEE 802.1D Spanning Tree Protocol
- IEEE 802.1w Rapid Spanning Tree Protocol
- IEEE 802.1s Multiple Spanning Tree Protocol
- IEEE 802.1p Class of Service

- IEEE 802.1Q VLAN tagging
- IEEE 802.3ae 10G BASE-X
- IEEE 802.1X Port Authentication Network Control
- IEEE 802.1ab LLDP
- IEEE 802.1ag Connectivity Fault
- Management(CFM)
- RFC 1112 IGMP v1
- RFC 3376 IGMP v3
- RFC783 TFTP
- RFC 791 IP
- RFC 792 ICMP
- RFC 2068 HTTP
- RFC 2616 HTTPS
- ITU-T G.8032 ERPS Ring
- RFC 2236 IGMP v2

## | EMC & Protection

- IP Class: IP40
- Surge of Power: AC: IEC 61000-4-5 Level 3 (4KV/2KV) (1.2/50us)  
DC: IEC 61000-4-5 Level X (8KV/8KV) (1.2/50us)
- Surge of Ethernet Port: IEC 61000-4-5 Level 3 (4KV/2KV) (10/850us)
- RS: IEC 61000-4-3 Level 3 (10V/m)
- EFI: IEC 61000-4-4 Level 3 (1V/2V)
- CS: IEC 61000-4-6 Level 3 (10V/m)
- PFMF: IEC 61000-4-8 Level 4 (30A/m)
- DIP: IEC 61000-4-11 Level 3 (10V)
- ESD: IEC 61000-4-2 Level 4 (8K/15K)
- Free Fall: 0.5m

## | Hardware Specifications

| Model                   | XPTN-9000-85-4XG24GX-HR-V                   | XPTN-9000-85-4XG24GX-R-V |
|-------------------------|---------------------------------------------|--------------------------|
| Interface               | 4*10G SFP ports + 24*10/100/1000M SFP ports |                          |
| Switching               | 128Gbps                                     |                          |
| Packets Forwarding Rate | 95.23Mpps                                   |                          |
| MAC                     | 16K                                         |                          |
| Port Buffer             | 12M                                         |                          |
| Forwarding Delay        | <10us                                       |                          |

|                        |                                            |                         |
|------------------------|--------------------------------------------|-------------------------|
| Power Supply           | Phenix terminal, AC+DC power supply        |                         |
|                        | Input Voltage:DC12-58V/AC 100-240V 50-60HZ | Input Voltage: DC48-58V |
|                        | Empty Load Power: <36W                     |                         |
| LED Indicators         | PWR, Link/ACTLED                           |                         |
| Environment            | Working Temperature: -40°C ~ 75°C          |                         |
|                        | Storage Temperature: -40°C ~ 75°C          |                         |
|                        | Working Humidity: 5%~95% non-condensing    |                         |
|                        | Storage Humidity: 5%~95% non-condensing    |                         |
| SIZE(W*D*H)            | 440*245*44mm                               |                         |
| Weight                 | 3.6KG                                      | 3.62KG                  |
| Installation Method    | Rack mounted                               |                         |
| Certificate Compliance | CE/FCC/RoHS                                |                         |
| MTBF                   | 100,000 hours                              |                         |

## Software Specifications

| Model | XPTN-9000-85-4XG24GX-HR-V    | XPTN-9000-85-4XG24GX-R-V |
|-------|------------------------------|--------------------------|
| VLAN  | Support 4K IEEE 802.3Q VLAN  |                          |
|       | Support protocol VLAN        |                          |
|       | Support GARP                 |                          |
| LACP  | Support IEEE 802.3ad         |                          |
|       | Support static LACP          |                          |
|       | Support dynamic LACP         |                          |
| STP   | Support IEEE 802.1d STP      |                          |
|       | Support IEEE 802.1w RSTP     |                          |
|       | Support IEEE 802.1s MSTP     |                          |
| ERPS  | Support ITUT G.8032 protocol |                          |

| Model     | XPTN-9000-85-4XG24GX-HR-V          | XPTN-9000-85-4XG24GX-R-V |
|-----------|------------------------------------|--------------------------|
| Port      | Support Jumbo Frame                |                          |
|           | Support IEEE802.3X Flow Control    |                          |
|           | Support port statistics            |                          |
|           | Support Auto-MDI/MDIX              |                          |
| Multicast | Support IGMP Snooping              |                          |
|           | Support MVR                        |                          |
| ACL       | Support MAC Standard/Extended ACL  |                          |
|           | Support IPv4 Standard/Extended ACL |                          |
|           | Support IPv6 Standard/Extended ACL |                          |
| QoS       | Support QoS Re-marking             |                          |
|           | Support Port Trust                 |                          |
|           | Support Port Rate Limiting         |                          |
|           | Support Egress Queue Rate Limiting |                          |
| DHCP      | Support DHCP Snooping              |                          |
|           | Support DHCP Client                |                          |
|           | Support DHCP Server                |                          |
| Security  | Support IEEE802.1X                 |                          |
|           | Support MAC-Based IEEE802.1X       |                          |
|           | Support WEB-Based IEEE802.1X       |                          |
|           | IP Source Guard                    |                          |
|           | Port Security                      |                          |
|           | Port Isolation                     |                          |
| Diagnosis | Support Console Logs               |                          |
|           | Support RAM logs                   |                          |
|           | Support Flash logs                 |                          |
|           | Support Port Mirroring(1:1,N:1)    |                          |

| Model      | XPTN-9000-85-4XG24GX-HR-V          | XPTN-9000-85-4XG24GX-R-V |
|------------|------------------------------------|--------------------------|
| Diagnosis  | Support Ping                       |                          |
|            | Support Traceroute                 |                          |
|            | Support Cable Test                 |                          |
|            | Support Optical Module Information |                          |
| Management | Support User Management            |                          |
|            | Support System Log                 |                          |
|            | Support Firmware Upgrade           |                          |
|            | Support File Upgrade               |                          |
|            | Support SNMP                       |                          |
|            | Support WEB Management             |                          |

## | Product Dimension

