

L2+ Managed Industrial Switch

XPTN-9000-87-2GX8GP8B-VX

Features & Benifits

- Input Voltage: DC12~58V for Non-PoE, DC48~58V for PoE
- Operating Temperature: -40°C~85°C
- Shell: IP50 protection
- Fanless design, low power consumption
- ESD: contact 8KV, air 15KV
- MTBF: 100,000 hours



| Product Introduction

The XBlue-8 Series is L2+ managed switch, specially designed for harsh industrial environments, which provides economic solutions for industrial Ethernet networking. Support wide working temperature -40°C~85°C.

Redundant DC power supply, adopts rugged aluminum alloy housing, and passed high level tests of EMI/EMC. It also has gone through the strict aging test, meeting the requirements of transportation industry.

| Technical Reference

- | | |
|-----------------------------|---|
| ● IEEE 802.3 CSMA/CD method | ● IEEE 802.3z Gigabit SX/LX |
| ● IEEE 802.3 af PoE | ● IEEE 802.3ab Gigabit 1000T |
| ● IEEE 802.3 at PoE+ | ● IEEE 802.3bz 2.5G BASE-X |
| ● IEEE 802.3 bt PoE++ | ● IEEE 802.3ad port trunk with LACP |
| ● IEEE 802.3x Flow Control | ● IEEE 802.1D Spanning Tree Protocol |
| ● IEEE 802 Networks | ● IEEE 802.1w Rapid Spanning Tree Protocol |
| ● IEEE 802.3 10Base-T | ● IEEE 802.1s Multiple Spanning Tree Protocol |
| ● IEEE 802.3u 100Base-TX/FX | |

- IEEE 802.1p Class of Service
- IEEE 802.1Q VLAN tagging
- IEEE 802.1X Port Authentication Network Control
- IEEE 802.1ab LLDP
- IEEE 802.1ag Connectivity Fault Management(CFM)
- RFC 1112 IGMP v1
- RFC 2236 IGMP v2
- RFC 3376 IGMP v3
- RFC783 TFTP
- RFC 791 IP
- RFC 792 ICMP
- RFC 2068 HTTP
- RFC 2616 HTTPS
- ITU-T G.8032 ERPS Ring

| EMC & Protection

- IP Level: IP50
- Surge of Power: IEC 61000-4-5 Level 3 (6KV/2KV) (1.2/50us)
- Surge of Ethernet port: IEC 61000-4-5 Level 3 (6KV/2KV) (10/700us)
- RS: IEC 61000-4-3 Level 3 (10V/m)
- EFI: IEC 61000-4-4 Level 3 (1V/2V)
- CS: IEC 61000-4-6 Level 3 (10V/m)
- PFMF: IEC 61000-4-8 Level 4 (30A/m)
- DIP: IEC 61000-4-11 Level 3 (10V)
- ESD: IEC 61000-4-2 Level 4 (8K/15K)
- Free fall: 0.5m

| Hardware Specifications

Model	XPTN-9000-87-2GX8GP8B-VX
Interface	2*1000M SFP ports + 8*10/100/1000M RJ45 ports
Switching	36Gbps
Packets Forwarding Rate	26.78Mpps
MAC	16K
Port Buffer	12M
Forwarding Delay	<10us

Power Supply	Phenix terminal, DC redundant input
	Input Voltage: DC48-58V
	Empty Load Power: <10W
LED Indicators	PWR, Link/ACT
PoE	1-8 ports support PoE
	PoE budget: 730W
	IEEE802.3 af/at/bt standard
	PIN Sequence: 1,2,4,5+/3,6,7,8-
Environment	Working Temperature: -40°C ~ 85°C
	Storage Temperature: -40°C ~ 85°C
	Working Humidity: 5%~95% non-condensing
	Storage Humidity: 5%~95% non-condensing
SIZE(W*D*H)	143*104*108mm
Weight	1.15KG
Installation Method	Din Rail&Wall-mounted Installation
Certificate Compliance	CE/FCC/RoHS
MTBF	100,000 hours

| Software Specifications

Model	XPTN-9000-87-2GX8GP8B-VX
VLAN	Support 4K IEEE 802.3Q VLAN
	Support protocol VLAN
	Support GARP
LACP	Support IEEE 802.3ad
	Support static LACP
	Support dynamic LACP
STP	Support IEEE 802.1d STP
	Support IEEE 802.1w RSTP
	Support IEEE 802.1s MSTP
ERPS	Support ITUT G.8032 protocol

Model	XPTN-9000-87-2GX8GP8B-VX
Port	Support Jumbo Frame
	Support IEEE802.3X Flow Control
	Support port statistics
	Support Auto-MDI/MDIX
Multicast	Support IGMP Snooping
	Support MVR
ACL	Support MAC Standard/Extended ACL
	Support IPv4 Standard/Extended ACL
	Support IPv6 Standard/Extended ACL
QoS	Support QoS Re-marking
	Support Port Trust
	Support Port Rate Limiting
	Support Egress Queue Rate Limiting
DHCP	Support DHCP Snooping
	Support DHCP Client
	Support DHCP Server
L3 Route	IPv4 Management Address
	IPv6 Management Address
	Static IPv4 Route
	Static IPv6 Route
	ARP
	Loopback Interface
Security	Support IEEE802.1X
	Support MAC-Based IEEE802.1X
	Support WEB-Based IEEE802.1X
	IP Source Guard
	Port Security
	Port Isolation
Diagnosis	Support Console Logs
	Support RAM logs
	Support Flash logs
	Support Port Mirroring(1:1,N:1)

Model	XPTN-9000-87-2GX8GP8B-VX
Diagnosis	Support Ping
	Support Traceroute
	Support Cable Test
	Support Optical Module Information
Management	Support User Management
	Support System Log
	Support Firmware Upgrade
	Support File Upgrade
	Support SNMP
	Support WEB Management
	Support Console
	Support CLI
	Support Telnet/SSH

| Product Dimension

