

L2+ Managed Industrial Switch

XPTN-9000-87-4XG16GX8GC-HR-V
XPTN-9000-87-4XG16GX8GC-R-V

Features & Benifits

- Input Voltage: DC12~58V/AC 100~240V 50-60Hz
- Operating Temperature: -40°C~75°C
- Shell: IP40 protection
- Fanless design, low power consumption
- ESD: contact 8KV, air 15KV
- MTBF: 100,000 hours



| Product Introduction

The XPTN-9000 87 Series is specially designed for harsh industrial environments, which provides economic solutions for industrial Ethernet networking. Support wide working temperature -40°C~75°C.

Redundant AC+DC power supply, adopts rugged aluminum alloy housing, and passed high level tests of EMI/EMC. It also has gone through the strict aging test, meeting the requirements of transportation industry.

| Technical Reference

- | | |
|------------------------------|---|
| ● IEEE 802.3 10BASE-T | ● RFC 2616 HTTPS |
| ● IEEE 802.3u 100BASE-TX | ● ITU-T G.8032 ERPS Ring |
| ● IEEE 802.3u 100Base-FX | ● IEEE 802.1Q VLAN tagging |
| ● IEEE 802.3ab Gigabit 1000T | ● IEEE 802.1X Port Authentication Network Control |
| ● IEEE 802.3bz 2.5G BASE-X | ● IEEE 802.3x flow control and back pressure |
| ● IEEE 802.3ae 10G Base-X | |

- IEEE 802.3ad port trunk with LACP
- IEEE 802.1D Spanning Tree Protocol
- IEEE 802.1w Rapid Spanning Tree Protocol
- IEEE 802.1s Multiple Spanning Tree Protocol
- IEEE 802.1p Class of Service
- IEEE 802.1ab LLDP
- IEEE 802.1ag Connectivity Fault Management(CFM)
- RFC 1112 IGMP v1
- RFC 2236 IGMP v2
- RFC 3376IGMP v3
- RFC783 TFTP
- RFC 791 IP
- RFC 792 ICMP
- RFC 2068 HTTP

| EMC & Protection

- IP Class: IP40
- Surge of Power: AC: IEC 61000-4-5 Level X (6KV/2KV) (1.2/50us)
DC: IEC 61000-4-5 Level X (8KV/8KV) (1.2/50us)
- Surge of Ethernet Port: IEC 61000-4-5 Level 4 (6KV/2KV) (10/870us)
- RS: IEC 61000-4-3 Level 3 (10V/m)
- EFI: IEC 61000-4-4 Level 3 (1V/2V)
- CS: IEC 61000-4-6 Level 3 (10V/m)
- PFMF: IEC 61000-4-8 Level 4 (30A/m)
- DIP: IEC 61000-4-11 Level 3 (10V)
- ESD: IEC 61000-4-2 Level 4 (8K/15K)
- Free Fall: 0.5m

| Hardware Specifications

Model	XPTN-9000-87- 4XG16GX8GC-HR-V	XPTN-9000-87- 4XG16GX8GC-R-V
Interface	4*10G SFP ports + 16*1000M SFP ports+8*1000M Combo ports	
Switching	128Gbps	
Packets Forwarding Rate	95.23Mpps	
MAC	16K	

Port Buffer	12M	
Forwarding Delay	<10us	
Power Supply	Phenix terminal, AC+DC power supply	
	Input Voltage:DC12-58V/AC 100-240V 50-60HZ	Input Voltage: DC48-58V
	Empty Load Power: <36W	
LED Indicators	PWR, Link/ACT LED	
Environment	Working Temperature: -40°C ~ 75°C	
	Storage Temperature: -40°C ~ 75°C	
	Working Humidity: 5%~95% non-condensing	
	Storage Humidity: 5%~95% non-condensing	
SIZE(W*D*H)	440*245*44mm	
Weight	3.6KG	3.62KG
Installation Method	Rack mounted	
Certificate Compliance	CE/FCC/RoHS	
MTBF	100,000 hours	

| Software Specifications

Model	XPTN-9000-87- 4XG16GX8GC-HR-V	XPTN-9000-87- 4XG16GX8GC-R-V
VLAN	Support 4K IEEE 802.3Q VLAN	
	Support protocol VLAN	
	Support GARP	
LACP	Support IEEE 802.3ad	
	Support static LACP	
	Support dynamic LACP	
STP	Support IEEE 802.1d STP	
	Support IEEE 802.1w RSTP	
	Support IEEE 802.1s MSTP	

Model	XPTN-9000-87- 4XG16GX8GC-HR-V	XPTN-9000-87- 4XG16GX8GC-R-V
ERPS	Support ITUT G.8032 protocol	
Port	Support Jumbo Frame	
	Support IEEE802.3X Flow Control	
	Support port statistics	
	Support Auto-MDI/MDIX	
Multicast	Support IGMP Snooping	
ACL	Support MAC Standard/Extended ACL	
	Support IPv4 Standard/Extended ACL	
	Support IPv6 Standard/Extended ACL	
QoS	Support QoS Re-marking	
	Support Port Trust	
	Support Port Rate Limiting	
	Support Egress Queue Rate Limiting	
DHCP	Support DHCP Snooping	
	Support DHCP Client	
	Support DHCP Server	
L3 Route	IPv4 Management Address	
	IPV6 Management Address	
	Static IPv4 Route	
	Static IPv6 Route	
	ARP	
	Loopback Interface	
Security	Support IEEE802.1X	
	Support MAC-Based IEEE802.1X	
	Support WEB-Based IEEE802.1X	
	IP Source Guard	
	Port Security	
	Port Isolation	

Model	XPTN-9000-87- 4XG16GX8GC-HR-V	XPTN-9000-87- 4XG16GX8GC-R-V
Diagnosis	Support Console Logs	
	Support RAM logs	
	Support Flash logs	
	Support Port Mirroring(1:1)	
	Support Ping	
	Support Traceroute	
	Support Cable Test	
	Support Optical Module Information	
Management	Support User Management	
	Support System Log	
	Support Firmware Upgrade	
	Support File Upgrade	
	Support SNMP	
	Support WEB Management	
	Support Console	
	Support CLI	
EEE	Support Telnet/SSH	
	Support IEEE802.3az	

| Product Dimension

