

```

● jezrelacedelacruz@Jezrels-MacBook-Air-5 WEEK1_JS_OBJECTS % node objects_examples.js
object
{
  name: 'John',
  age: 30,
  city: 'New York',
  null: null,
  undefined: undefined,
  'full name': 'John Doe',
  displayInfo: [Function: displayInfo],
  displayArrow: [Function: displayArrow]
}
Name: John, Age: 30, City: New York
{}
Name: undefined, Age: undefined, City: undefined
John
John
null
John Doe
John Doe
John 30 New York null
this: [object global], Jezrel
First Name: Jezrel, Last Name: Ace, City: Toronto
[Arguments] { '0': 'Jezrel', '1': 'Ace', '2': 'Toronto' }
arguments[0]: Jezrel, arguments[1]: Ace, arguments[2]: Toronto
First Name: Jezrel, Last Name: Ace, City: Toronto
● jezrelacedelacruz@Jezrels-MacBook-Air-5 WEEK1_JS_OBJECTS %

```

```

● jezrelacedelacruz@Jezrels-MacBook-Air-5 comp3123 % cd '/Users/jezrelacedelacruz/Documents/sem5/comp3123/WEEK1_JS_OBJECTS'
● jezrelacedelacruz@Jezrels-MacBook-Air-5 WEEK1_JS_OBJECTS % node index.js
Hello, World!
Test
b re-declared
300
600
IN Block c: 400
OUT Block c: 300
string
number
boolean
function
Hello, World! Again
Hello, World! Again using Arrow Function
[
  1,      'TWO',
  3,      4,
  'FIVE', null,
  false,  undefined,
  {},     []
]
TWO
10
undefined
undefined
null
object
{}
object
[ 1, 2, 3, 4, 5 ]
[ 2, 4, 6, 8, 10 ]
[ 2, 4 ]
15
[ 4, 6, 8, 10 ]
● jezrelacedelacruz@Jezrels-MacBook-Air-5 WEEK1_JS_OBJECTS %

```