



	Q NOM	P MAX	FILTRATION	PORT
MODEL	LPM	BAR	MICRON	BSPP
IFR2 - 06	w *** • 80 · ·	* * * * * * * * * * * * * * * * * * *	W 8 8 8 8	1/2"-3/4"-1
* IFR2 - 10	150	a 20 8	* * * * * * * * * * * * * * * * * * *	. 1-1/4"
JFR2 - 12°V	300	A 2	10	1-1/2"
IFR2 - 12 H	300	* * * * * * * * * * * * * * * * * * *	25	1-1/2"
IFR3 - 03	30 *	10	A10	1/4"-3/8"
, IFR3 - 06	80		4 × A25	1/2"-3/4"-1
IFR3 - 10	150	Mark M	7. 2. 4.	1-1/4"
TFR3 - 06	80 .	W B A	n de la m	3/4"



	0.0	*	2 2 2	B WY X
TIF2 - 04	25	a e e a	W	1/2"
TIF2 - 06	60	X" 4 1 X 1 1 1 1	* 10 n a a	3/4"
TIF2 - 08	90	10	25	a 28 2 2 11 2
TIF2 - 08 / 06	90,	10	A10	1"-3/4"
TIF2 - 10	150		* A25	1-1/4"
TIF3 - 10	150	¥ 10 - 2 x		11/4" - 11/4"
	ON THE REAL PROPERTY.	- 0	N 11	- X



HFR - 05 - 04	25	2 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	10	1/2"
HFR - 10 - 06	80		25	3/4"
HFR - 10 - 08	80	20	A10 A25	20 00 10 20
HFR - 20 - 10	150		74	1-1/4"
HFR - 20 - 12	150	an it or	149	1-1/2"



CFR2 - 025 - 04	25	9b	** = 10 =	1/2"
CFR2 - 040 - 06	- 40	X = 1	25	3/4"
CFR2 - 100 - 08	100	20	A10 A25	1"
CFR2 - 250- 12	250	1.57	74	1-1/2"
CFR2 - 630 - 20	630		149	* 2-1/2" SAE

^{*} SAE FLANGE



MODEL	Q NOM	FILTRATION * MICRON	MALE THD.	FEMALE THD.
TMA - 16	40		2 1/2" UN	1 5/16" UN
TMA - 20	60] ,,,	2 1/2" UN	1 5/8" UN
TMA - 24	120	149	3 3/8" UN	1 7/8" UN
TMA - 32	160	1 . [3 3/8" UN	2 1/2" UN

^{*} CONSULT FACTORY FOR OTHER MICRON RATINGS



TMS - 005	20	Supplemental Control of the Control	1"	NPT	1/2"	NPT
TMS - 010	40		11/4"	NPT	3/4"	NPT
TMS - 015	60	State of his stripes	11/2"	NPT	1"	NPT
TMS - 025	100	149	2"	NPT	11/4"	NPT
TMS - 050	200	100	3"	NPT	2"	NPT
TMS - 100	400		4"	NPT	3"	NPT
TMS - 200	800	E TRUE A L	6"	NPT	4"	NPT



3011	BOTTABLE FOR HOSE CONNECTION						
	473	40	deres . The	1 7/8" UN			

40		1 7/8" UN	1"	DIA
60		2 1/2" UN	11/4"	DIA
80	149	3 3/8" UN	11/4"	DIA
120	al America	3 3/8" UN	11/2"	DIA
160		3 3/8" UN	2"	DIA
	60 80 120	60 80 149	60 2 1/2" UN 80 149 3 3/8" UN 3 3/8" UN	60 2 1/2" UN 11/4" 80 149 3 3/8" UN 11/4" 120 3 3/8" UN 11/2"



SC3 - 003	12		3/8"
SC3 - 005	20	The state of the s	1/2"
SC3 - 007	28		3/4"
SC3 - 010	40	emina M	1"
SC3 - 015	60	in a fin	1-1/4"
SC3 - 020	80	149	1-1/2"
SC3 - 030	120	Lan	1-1/2"
SC3 - 040	160	62.4	2"
SC3 - 050	200		2"
SC3 - 075	300	300	2-1/2"
SC3 - 100	400		3"
SC3 - 150	600	to the state of th	3"















