

Que 5 →

- Clone <https://github.com/zembutsu/docker-sample-nginx.git> on your local system.
- Initialize one repo on your local system named Cloudethix-nginx-yourname and then copy all the content from cloned repo to your local repo.
- Update the index.html and add the name CloudEthiX along with Hostname. Commit the change to your local repository. Then create and push the code from the local repository to your remote repository named Cloudethix-nginx-yourname under master branch.
- Once code is pushed, create a Docker hub public repository named Cloudethix-nginx-yourname.
- Then build the docker image out of the dockerfile. Once an image is built, tag the image and push that image to the docker hub repo you created.
- Create a deployment.yaml file with 2 replications in cloudethix_yourname Namespace and use the container image that you have pushed to your docker hub repo. Once a file is created, run the deployment in k8s cluster.
- Please prepare a document along with the snap and share it across

```
-----
achal@LAPTOP-HPUOTJF1:~$ mkdir Assignment-practice-1
achal@LAPTOP-HPUOTJF1:~$ cd Assignment-practice-1/
achal@LAPTOP-HPUOTJF1:Assignment-practice-1$ git clone
https://github.com/zembutsu/docker-sample-nginx.git
Cloning into 'docker-sample-nginx'...
remote: Enumerating objects: 22, done.
remote: Counting objects: 100% (12/12), done.
remote: Compressing objects: 100% (6/6), done.
remote: Total 22 (delta 7), reused 6 (delta 6), pack-reused 10 (from 1)
Receiving objects: 100% (22/22), done.
Resolving deltas: 100% (7/7), done.
-----

achal@LAPTOP-HPUOTJF1:Assignment-practice-1$ mkdir Cloudethix-nginx-achal
achal@LAPTOP-HPUOTJF1:Assignment-practice-1$ cd Cloudethix-nginx-achal/

achal@LAPTOP-HPUOTJF1:Assignment-practice-1$ cp docker-sample-nginx/*
Cloudethix-nginx-achal/
achal@LAPTOP-HPUOTJF1:Assignment-practice-1$ cd Cloudethix-nginx-achal/
achal@LAPTOP-HPUOTJF1:Cloudethix-nginx-achal$ ls
Dockerfile LICENSE README.md default.conf index.html
achal@LAPTOP-HPUOTJF1:Cloudethix-nginx-achal$ vim index.html
achal@LAPTOP-HPUOTJF1:Cloudethix-nginx-achal$ cat index.html
<html>
<body>
    <h1>Host: <!--#echo var=" CloudEthiX" --></h1>
    Version: 1.1
</body>
</html>
-----
```

```
achal@LAPTOP-HPUOTJF1:Cloudethix-nginx-achal$ git init
hint: Using 'master' as the name for the initial branch. This default branch
name
hint: will change to "main" in Git 3.0. To configure the initial branch name
```

```
hint: to use in all of your new repositories, which will suppress this
warning,
hint: call:
hint:
hint:   git config --global init.defaultBranch <name>
hint:
hint: Names commonly chosen instead of 'master' are 'main', 'trunk' and
hint: 'development'. The just-created branch can be renamed via this command:
hint:
hint:   git branch -m <name>
hint:
hint: Disable this message with "git config set advice.defaultBranchName
false"
Initialized empty Git repository in /home/achal/Ass
```

```
-----
achal@LAPTOP-HPUOTJF1:Cloudethix-nginx-achal$ git commit -m "files are added"
[master (root-commit) 1a412e0] files are added
 5 files changed, 46 insertions(+)
 create mode 100644 Dockerfile
 create mode 100644 LICENSE
 create mode 100644 README.md
 create mode 100644 default.conf
 create mode 100644 index.html
```

```
-----
achal@LAPTOP-HPUOTJF1:Cloudethix-nginx-achal$ git remote add origin
https://github.com/achalpadol/Cloudethix-nginx-achalpadol.git
achal@LAPTOP-HPUOTJF1:Cloudethix-nginx-achal$ git remote -v
origin  https://github.com/achalpadol/Cloudethix-nginx-achalpadol.git (fetch)
origin  https://github.com/achalpadol/Cloudethix-nginx-achalpadol.git (push)
```

```
-----
achal@LAPTOP-HPUOTJF1:Cloudethix-nginx-achal$ git push -u origin master
Username for 'https://github.com': achalpadol
Password for 'https://achalpadol@github.com':
Enumerating objects: 7, done.
Counting objects: 100% (7/7), done.
Delta compression using up to 12 threads
Compressing objects: 100% (7/7), done.
Writing objects: 100% (7/7), 1.35 KiB | 1.35 MiB/s, done.
Total 7 (delta 0), reused 0 (delta 0), pack-reused 0 (from 0)
To https://github.com/achalpadol/Cloudethix-nginx-achalpadol.git
 * [new branch]      master -> master
branch 'master' set up to track 'origin/master'.
```

```
-----
achal@LAPTOP-HPUOTJF1:Cloudethix-nginx-achal$ kubectl get ns
NAME                STATUS   AGE
default             Active   20h
kube-node-lease     Active   20h
kube-public         Active   20h
kube-system         Active   20h
```

```
-----
achal@LAPTOP-HPUOTJF1:Cloudethix-nginx-achal$ kubectl create ns cloudethix-
achal
namespace/cloudethix-achal created
achal@LAPTOP-HPUOTJF1:Cloudethix-nginx-achal$ kubens
cloudethix-achal
default
kube-node-lease
kube-public
kube-system
-----
```

```

achal@LAPTOP-HPU0TJF1:Cloudethix-nginx-achal$ kubens cloudethix-achal
✓ Active namespace is "cloudethix-achal"
-----

achal@LAPTOP-HPU0TJF1:Cloudethix-nginx-achal$ cat deployment.yml
apiVersion: apps/v1
kind: Deployment
metadata:
  name: cloudethix-nginx
  namespace: cloudethix-achal

spec:
  replicas: 2

  selector:
    matchLabels:
      app: cloudethix-nginx

  template:
    metadata:
      labels:
        app: cloudethix-nginx

    spec:
      containers:
        - name: nginx
          image: docker.io/achalpadol/cloudethix-nginx-achal:v1
          ports:
            - containerPort: 80
-----

achal@LAPTOP-HPU0TJF1:Cloudethix-nginx-achal$ cat index.html
<html>
<body>
  <h1>Host: <!--#echo var=" CloudEthiX" --></h1>
  Version: 1.1
</body>
</html>
-----

achal@LAPTOP-HPU0TJF1:Cloudethix-nginx-achal$ kubectl get pod
NAME                                READY   STATUS    RESTARTS   AGE
cloudethix-nginx-5d77d6699f-h8v4k   1/1     Running   0           19s
cloudethix-nginx-5d77d6699f-ml54z   1/1     Running   0           19s

```