ENHANCED DIVERSIONARY DEVICE

Interior Reload Technical Profile



Revision 2: 0320

Operational

Binary Explosive (A|B): | 6g (.21oz)

Sound Level: 172dB at 5' (1.5m)

Light Level: 6 - 8M cd

Fuse Delay: 1.5sec

Physical

Weight: 1.1 lbs (17.6oz)

Length: 5.75" (146.05mm)
Width: 2.8" (71.12mm)
Height: 1.25" (31.75mm)

Exhaust Port: Bi-Directional

Shipping

ECCN: 0A604

UN Number: 0425

Hazard Class: 1.4G Low Explosive

Quantity Per Package: 6 reloads
Net Explosive Weight: 6.26g (.22oz)

BATFE

Property Transfer: ATF E- Form 1 (5320.1)
Destructive device: Unassembled not a DD

Warranty Period:

Smart Initiator: 2 years from shipment date

Reload: 5 years from shipment date

SMART INITIATOR

RELOAD



Not to Scale

Performance: All specifications are average and are subject to change without notice. Performance specifications are based on testing conducted in Colorado Springs, Colorado, USA at an elevation of 6,305' (1.92k) above sea level.

WARNING: To be used by trained Law Enforcement, Correctional, or Military Personnel who have successfully completed a training program for the deployment of the Enhanced Diversionary Device. In rare circumstances, improper use of the Enhanced Diversionary Device may cause damage to property, serious bodily injury or death. The Enhanced Diversionary Device is restricted to Law Enforcement, Correctional, and Military Personnel to be used to gain compliance, disperse crowds, restore order, or temporarily incapacitate dangerous persons.

t: +1 (720) 779-8653 e: info@libertydynamic.com w: libertydynamic.com a: 2801 W. Mansfield Ave. Sheridan. Co 80110