O .	 1	 1 0 /.	1 1 .	











- $rst_tx_pointer = -bit_de_stuff_tx \& tx_pointer = = 6'd18) | -bit_de_stuff_tx \& tx_point \& -rx_data \& -extended_mode \& (tx_pointer = 6'd18) | -bit_de_stuff_tx \& tx_point \& -rx_data \& -extended_mode \& (tx_pointer = 6'd18) | -bit_de_stuff_tx \& tx_point \& -rx_data \& -extended_mode \& (tx_pointer = 6'd18) | -bit_de_stuff_tx \& tx_point \& -rx_data \& -extended_mode \& (tx_pointer = 6'd18) | -bit_de_stuff_tx \& tx_point \& -rx_data \& -extended_mode \& (tx_pointer = 6'd18) | -bit_de_stuff_tx \& tx_point \& -rx_data \& -extended_mode \& (tx_pointer = 6'd18) | -bit_de_stuff_tx \& tx_point \& -rx_data \& -extended_mode \& (tx_pointer = 6'd18) | -bit_de_stuff_tx \& tx_point \& -rx_data \& -extended_mode \& (tx_pointer = 6'd18) | -bit_de_stuff_tx \& tx_point \& -rx_data \& -extended_mode \& -exte$