

IFP style proofs in the Coq proof assistant

Holger Thies

Kyoto University

Joint work with Sewon Park and Hideki Tsuiki

Continuity, Computability, Constructivity 2021

September 19-24, Online

IFP

- Intuitionistic first-order logic
- Can add (nc) axioms
- Program Extraction
- Well-suited for proofs over abstract mathematical spaces (real numbers,...)
- Partiality

Coq

- Constructive Type Theory
- Can add axioms
- Program Extraction, Computation
- General purpose, many libraries
- Only total functions

IFP has been developed by U. Berger and collaborators (M. Seisenberger, O. Petrovska, H. Tsuiki) since 2009.

IFP Overview

IFP is a schema for a proof system over different abstract mathematical spaces.

IFP Overview

IFP is a schema for a proof system over different abstract mathematical spaces.

An instance of IFP consists of a language \mathcal{L} and a set of axioms \mathcal{A} .

IFP Overview

IFP is a schema for a proof system over different abstract mathematical spaces.

An instance of IFP consists of a language \mathcal{L} and a set of axioms \mathcal{A} .

The Language \mathcal{L} consists of

1. Sorts ι, ι_1, \dots as names for abstract mathematical spaces

IFP Overview

IFP is a schema for a proof system over different abstract mathematical spaces.

An instance of IFP consists of a language \mathcal{L} and a set of axioms \mathcal{A} .

The Language \mathcal{L} consists of

1. Sorts ι, ι_1, \dots as names for abstract mathematical spaces
2. Terms s, t consisting of variables, constants and function symbols

IFP Overview

IFP is a schema for a proof system over different abstract mathematical spaces.

An instance of IFP consists of a language \mathcal{L} and a set of axioms \mathcal{A} .

The Language \mathcal{L} consists of

1. Sorts ι, ι_1, \dots as names for abstract mathematical spaces
2. Terms s, t consisting of variables, constants and function symbols
3. Predicate constants of fixed arity

IFP Overview

IFP is a schema for a proof system over different abstract mathematical spaces.

An instance of IFP consists of a language \mathcal{L} and a set of axioms \mathcal{A} .

The Language \mathcal{L} consists of

1. Sorts ι, ι_1, \dots as names for abstract mathematical spaces
2. Terms s, t consisting of variables, constants and function symbols
3. Predicate constants of fixed arity

IFP Overview

IFP is a schema for a proof system over different abstract mathematical spaces.

An instance of IFP consists of a language \mathcal{L} and a set of axioms \mathcal{A} .

The Language \mathcal{L} consists of

1. Sorts ι, ι_1, \dots as names for abstract mathematical spaces
2. Terms s, t consisting of variables, constants and function symbols
3. Predicate constants of fixed arity

Relative to \mathcal{L} we define

- Formulas: $s = t, P(t), A \wedge B, A \vee B, A \rightarrow B, \forall x A, \exists x A$.

IFP Overview

IFP is a schema for a proof system over different abstract mathematical spaces.

An instance of IFP consists of a language \mathcal{L} and a set of axioms \mathcal{A} .

The Language \mathcal{L} consists of

1. Sorts ι, ι_1, \dots as names for abstract mathematical spaces
2. Terms s, t consisting of variables, constants and function symbols
3. Predicate constants of fixed arity

Relative to \mathcal{L} we define

- Formulas: $s = t$, $P(t)$, $A \wedge B$, $A \vee B$, $A \rightarrow B$, $\forall x A$, $\exists x A$.
- Predicates: Variables, constants, $\lambda x A$, $\mu(\Phi)$, $\nu(\Phi)$.

IFP Overview

IFP is a schema for a proof system over different abstract mathematical spaces.

An instance of IFP consists of a language \mathcal{L} and a set of axioms \mathcal{A} .

The Language \mathcal{L} consists of

1. Sorts ι, ι_1, \dots as names for abstract mathematical spaces
2. Terms s, t consisting of variables, constants and function symbols
3. Predicate constants of fixed arity

Relative to \mathcal{L} we define

- Formulas: $s = t, P(t), A \wedge B, A \vee B, A \rightarrow B, \forall x A, \exists x A$.
- Predicates: Variables, constants, $\lambda x A, \mu(\Phi), \nu(\Phi)$.
- Operators: $\lambda X P$ (P strictly positive in X)

A formula is called non-computational if it is disjunction-free and contains no free predicate variables.

A formula is called non-computational if it is disjunction-free and contains no free predicate variables.

Axioms in IFP are closed non-computational (disjunction-free) formulas.

Example:

$$\forall x \forall y \neg(x < y) \rightarrow y \leq x$$

is OK but

$$\forall x \forall y x < y \vee y \leq x$$

is not.

Induction rules

IFP contains the following rules for strictly positive induction and coinduction:

$$\frac{}{\Phi(\mu(\Phi)) \subseteq \mu(\Phi)} \text{CL}(\Phi)$$

$$\frac{\Phi(P) \subseteq P}{\mu(\Phi) \subseteq P} \text{IND}(\Phi, P)$$

$$\frac{}{\nu(\Phi) \subseteq \Phi(\nu(\Phi))} \text{COCL}(\Phi)$$

$$\frac{P \subseteq \Phi(P)}{P \subseteq \nu(\Phi)} \text{COIND}(\Phi, P)$$

$A \subseteq B$ is short for $\forall x A x \rightarrow B x$.

Program Extraction

- IFP's primary goal is program extraction

Program Extraction

- IFP's primary goal is program extraction
- Careful distinction between computational and non-computational (Harrop) formulas

Program Extraction

- IFP's primary goal is program extraction
- Careful distinction between computational and non-computational (Harrop) formulas
- Harrop expressions are realized by **Nil**

Program Extraction

- IFP's primary goal is program extraction
- Careful distinction between computational and non-computational (Harrop) formulas
- Harrop expressions are realized by **Nil**
- Uniform interpretation of quantifiers:

$$a R \Diamond x A = \Diamond x (a R A) \text{ for } \Diamond \in \{\exists, \forall\}$$

Program Extraction

- IFP's primary goal is program extraction
- Careful distinction between computational and non-computational (Harrop) formulas
- Harrop expressions are realized by **Nil**
- Uniform interpretation of quantifiers:

$$a R \Diamond x A = \Diamond x (a R A) \text{ for } \Diamond \in \{\exists, \forall\}$$

- Implemented in the Prawf proof assistant (U. Berger, O. Petrovska, H. Tsuiki)

Example: The language of real numbers

Language:

- Sorts: one sort R
- Constants: $-1, 0, 1$
- Functions: $+, -, *, /, \dots$
- Predicate constants: $<, \leq$

Axioms:

- Disjunction-free formulation of axioms of real closed field etc.

Example: Natural numbers

We can define natural numbers inductively by

$$N(x) = \mu(\lambda X \lambda x (x = 0 \vee X(x - 1)))$$

Induction and Closure rules:

$$\frac{}{\forall x ((x = 0 \vee N(x - 1)) \rightarrow N(x))} \text{CL}(N)$$

$$\frac{\forall x (x = 0 \vee P(x - 1)) \rightarrow P(x)}{\forall x N(x) \rightarrow P(x)} \text{IND}(N, P)$$

For each language \mathcal{L} and set of axioms \mathcal{A} , we define a set of Coq axioms by

1. For each sort ι in \mathcal{L} , define ι as a term constant (axiom) of Prop.

For each language \mathcal{L} and set of axioms \mathcal{A} , we define a set of Coq axioms by

1. For each sort ι in \mathcal{L} , define ι as a term constant (axiom) of Prop.
2. For each constant c of sort ι , define c as a term constant (axiom) of type ι .

For each language \mathcal{L} and set of axioms \mathcal{A} , we define a set of Coq axioms by

1. For each sort ι in \mathcal{L} , define ι as a term constant (axiom) of Prop.
2. For each constant c of sort ι , define c as a term constant (axiom) of type ι .
3. For each function symbol f of arity $\iota_1 \times \cdots \times \iota_n \rightarrow \iota$, define f as a term constant (axiom) of type $\iota_1 \rightarrow \cdots \rightarrow \iota_n \rightarrow \iota$.

For each language \mathcal{L} and set of axioms \mathcal{A} , we define a set of Coq axioms by

1. For each sort ι in \mathcal{L} , define ι as a term constant (axiom) of Prop.
2. For each constant c of sort ι , define c as a term constant (axiom) of type ι .
3. For each function symbol f of arity $\iota_1 \times \cdots \times \iota_n \rightarrow \iota$, define f as a term constant (axiom) of type $\iota_1 \rightarrow \cdots \rightarrow \iota_n \rightarrow \iota$.
4. For each predicate symbol P of arity $(\iota_1, \cdots \iota_n)$, define P as a term constant (axiom) of type $\iota_1 \rightarrow \cdots \rightarrow \iota_n \rightarrow \text{Prop}$.

For each language \mathcal{L} and set of axioms \mathcal{A} , we define a set of Coq axioms by

1. For each sort ι in \mathcal{L} , define ι as a term constant (axiom) of Prop .
2. For each constant c of sort ι , define c as a term constant (axiom) of type ι .
3. For each function symbol f of arity $\iota_1 \times \cdots \times \iota_n \rightarrow \iota$, define f as a term constant (axiom) of type $\iota_1 \rightarrow \cdots \rightarrow \iota_n \rightarrow \iota$.
4. For each predicate symbol P of arity $(\iota_1, \cdots \iota_n)$, define P as a term constant (axiom) of type $\iota_1 \rightarrow \cdots \rightarrow \iota_n \rightarrow \text{Prop}$.
5. For each operator symbol Q of arity $(\iota_1, \cdots \iota_n)$, define Q as a term constant (axiom) of type $(\iota_1 \rightarrow \cdots \rightarrow \iota_n \rightarrow \text{Prop}) \rightarrow (\iota_1 \rightarrow \cdots \rightarrow \iota_n \rightarrow \text{Prop})$.

Translating Formulas i

1. $H(c : \iota) = \vdash c : \iota,$
2. $H(f : \iota_1 \times \cdots \times \iota_n \rightarrow \iota) = \vdash f : \iota_1 \rightarrow \cdots \rightarrow \iota_n \rightarrow \iota,$
3. $H(x : \iota) = x : \iota \vdash x : \iota,$
4. $H(C : \text{predicate}(\iota_1, \dots, \iota_d)) = \vdash C : \iota_1 \rightarrow \cdots \rightarrow \iota_n \rightarrow \text{Prop},$
5. $H(X : \text{predicate}(\iota_1, \dots, \iota_d)) = X : \iota_1 \rightarrow \cdots \rightarrow \iota_d \rightarrow \text{Prop} \vdash X : \iota_1 \rightarrow \cdots \rightarrow \iota_d \rightarrow \text{Prop},$
6. $H(f(t_1, \dots, t_n) : \iota) = \Gamma \vdash f \ t'_1 \ \cdots \ t'_n : \iota$ when $H(t_i : \iota_i) = \Gamma_i \vdash t'_i : \iota_i$ and $\Gamma = \bigcup_i \Gamma_i,$
7. $H(t_1 = t_2) = \Gamma \vdash t'_1 = t'_2 : \text{Prop}$ when $H(t_1) = \Gamma_1 \vdash t'_1 : \iota,$
 $H(t_2) = \Gamma_2 \vdash t'_2 : \iota,$ and $\Gamma = \Gamma_1 \cup \Gamma_2,$

Translating Formulas ii

8. $H(P \vee Q) = \Gamma \vdash P' \vee Q'$ when $H(P) = \Gamma_1 \vdash P' : \text{Prop}$,
 $H(Q) = \Gamma_2 \vdash Q' : \text{Prop}$, and $\Gamma = \Gamma_1 \cup \Gamma_2$,
9. $H(P \wedge Q) = \Gamma \vdash P' \wedge Q'$ when $H(P) = \Gamma_1 \vdash P' : \text{Prop}$,
 $H(Q) = \Gamma_2 \vdash Q' : \text{Prop}$, and $\Gamma = \Gamma_1 \cup \Gamma_2$,
10. $H(P \rightarrow Q) = \Gamma \vdash P' \rightarrow Q'$ when $H(P) = \Gamma_1 \vdash P' : \text{Prop}$,
 $H(Q) = \Gamma_2 \vdash Q' : \text{Prop}$, and $\Gamma = \Gamma_1 \cup \Gamma_2$,
11. $H(\exists x P) = \Gamma \setminus (x : \iota) \vdash \exists(x : \iota). P'$ when $H(x) = x : \iota$ and
 $H(P) = \Gamma \vdash P' : \text{Prop}$,
12. $H(\forall x P) = \Gamma \setminus (x : \iota) \vdash \forall(x : \iota). P'$ when $H(x) = x : \iota$ and
 $H(P) = \Gamma \vdash P' : \text{Prop}$,
13. $H(\lambda x P) = \Gamma \setminus (x : \iota) \vdash \lambda(x : \iota). P'$ when $H(x) = x : \iota$ and
 $H(P) = \Gamma \vdash P' : \text{Prop}$,

14. $H(\lambda X P) = \Gamma \setminus (X : (\iota_1 \rightarrow \cdots \rightarrow \iota_n \rightarrow \text{Prop})) \vdash \lambda(X : (\iota_1 \cdots \rightarrow \iota_n \rightarrow \text{Prop})). P'$ when
 $H(X) = X : \iota_1 \rightarrow \cdots \rightarrow \iota_n \rightarrow \text{Prop}$ and
 $H(P) = \Gamma \vdash P' : \text{Prop},$

Inductive Types

For each expression $\mu(\Phi)$ in IFP we define an inductive type in Coq:

```
Inductive MPhi : ( $\iota$  -> Prop) :=  
  MPhic: forall x, (Phi Mphi x) -> Mphi x.
```

where Phi is the translation of Φ .

Inductive Types

For each expression $\mu(\Phi)$ in IFP we define an inductive type in Coq:

```
Inductive MPhi : ( $\iota$  -> Prop) :=  
  MPhic: forall x, (Phi Mphi x) -> Mphi x.
```

where Phi is the translation of Φ .

The right induction principle will in general not be generated by Coq but

```
Lemma ind_Phi: forall (P :  $\iota$  -> Prop),  
  forall x, ((Phi P x) -> P x) -> Mphi x -> P x.
```

can be proven.

Example

We formalized the real number examples from



Ulrich Berger, Hideki Tsuiki: **Intuitionistic Fixed Point Logic.**

Annals of Pure and Applied Logic 172.3 (2021): 102903.

Example

We formalized the real number examples from



Ulrich Berger, Hideki Tsuiki: **Intuitionistic Fixed Point Logic.**

Annals of Pure and Applied Logic 172.3 (2021): 102903.

Recall the definition of natural numbers in IFP:

$$N(x) = \mu(\lambda X \lambda x (x = 0 \vee X(x - 1)))$$

\Rightarrow Demo in Coq.

Gray Code and Signed Digit Representation

The signed-digit representation for a real number $x \in [-1, 1]$ can be defined by $\nu(\Phi_{SD})$ with

$$\Phi_{SD} := \lambda X \lambda x \exists d \in SD \ |2x - d| \leq 1 \wedge X(2x - d)$$

The infinite gray-code representation can be defined by $\nu(\Phi_G)$ with

$$\Phi_G := \lambda X \lambda x \ |x| \leq 1 \wedge (x \neq 0 \rightarrow x \leq 0 \vee x \geq 0) \wedge X(1 - 2|x|)$$

Mixed Induction/Coinduction

Nested inductive/coinductive definitions are used in IFP e.g. to define uniformly continuous functions.

For $d \in \mathbb{R}$, let $av_d(x) := \frac{d+x}{2}$ and

$$C_1 := \nu F \mu G \lambda h \exists i \in \text{SD} \exists f \in F(h = av_e \circ f) \vee \forall d \in \text{SD} h \circ av_d \in G.$$

Mixed Induction/Coinduction

Nested inductive/coinductive definitions are used in IFP e.g. to define uniformly continuous functions.

For $d \in \mathbb{R}$, let $av_d(x) := \frac{d+x}{2}$ and

$$C_1 := \nu F \mu G \lambda h \exists i \in \text{SD} \exists f \in F(h = av_e \circ f) \vee \forall d \in \text{SD} h \circ av_d \in G.$$

Coq does not accept the coinductive proof because it is not formally guarded.

Future work

- Formalization of RIFP in Coq
- Program extraction
- Translation from Coq proofs to IFP proofs
- Extension to CFP



Happy Birthday, Ulrich!