

a quiver of vectors

Quiver, Explained

From “what is a vector?” to a production vector database — a complete, plain-English tour of how a secure, memory-frugal ANN engine actually works.

VECTOR SEARCH

RUST ENGINE

SECURITY-FIRST

MEMORY-FRUGAL

```
quiver@cockpit:~$ ./read --audience=everyone --depth=full
```

The security-first vector database
Open-source • AGPL-3.0 • single static binary

Authored for engineers & the curious
github.com/achref-soua/quiver

How to read this guide & what's inside

One document, written for two readers at once — the newcomer and the engineer.

This guide explains a real, production-grade vector database — **Quiver** — from absolute first principles all the way down to its on-disk format and cryptography. It is deliberately written so that two very different readers get value from the *same* pages.

TWO READING PATHS

If you have never touched AI or databases: read straight through. Every concept is introduced with a real-world analogy and a concrete example before any jargon appears. You can skip the dashed “Under the hood” boxes and still understand everything.

If you build software: the same sections carry the depth — algorithms, data structures, trade-offs, and the real numbers, with the design *decisions* explained, not just stated. The dashed boxes go all the way down.

We keep one running example throughout: a **movie-recommendation search** — “find me films that *feel like* Blade Runner.” By the end you will know precisely what happens, step by step, when that query runs.

Contents

- | | | |
|---|---|-----|
| 1 | The Big Idea – Turning Meaning into Numbers | p4 |
| | <i>Embeddings, similarity metrics, and why brute force fails.</i> | |
| 2 | What Quiver Is, and Why It's Different | p8 |
| | <i>The three-point wedge, and the honest non-goals.</i> | |
| 3 | The Architecture, Top to Bottom | p10 |
| | <i>The whole system on one page, the crates, the run modes, the request lifecycles.</i> | |
| 4 | The Engine, Block by Block | p15 |
| | <i>SIMD kernels, the indexes, quantization, filtering & hybrid search.</i> | |

5	Durability — How It Survives	<code>kill -9</code>	p 22
	<i>The write-ahead log, checksummed pages, recovery, and the off-lock rebuild.</i>		
6	Security, the Defining Feature		p 27
	<i>Encryption-at-rest, envelope keys, crypto-shredding, encrypted vectors.</i>		
7	Benchmarking Quiver — Method, Results, Verdict		p 30
	<i>The 7-competitor head-to-head, plus the v0.22.0 recall, concurrency & filter sweeps.</i>		
8	The Decisions Behind the Code		p 38
	<i>The choices — and the restraint — that define the project.</i>		
9	Beyond Search — RAG, Full-Text & Operations		p 39
	<i>Embedding & rerank, BM25, snapshots, replication, OTLP, the SDKs & the cockpit.</i>		
A	Glossary for the newcomer		p 47
B	References & repository documentation		p 49

The Big Idea: Turning Meaning into Numbers

Before any database, one question: how do you make a computer understand that two different things mean the same thing?

1.1 The problem with keywords

Imagine you run a movie site. A user types: “a moody sci-fi about androids and identity.” A traditional database searches with **keywords** — it looks for the literal words “moody,” “sci-fi,” “androids.” But Blade Runner’s description might say “a replicant hunter in a neon dystopia.” Zero shared keywords — yet it is a perfect match. Keyword search is **blind to meaning**.

What we actually want is **search by meaning, not by spelling**. That is the entire reason vector databases exist.

1.2 What is an “embedding”? — the single most important idea

THE CORE IDEA

You can turn any piece of content — a sentence, an image, a song, a product — into a list of numbers that captures its *meaning*. That list of numbers is called an **embedding** (or a **vector**).

A vector is just an ordered list of numbers, for example:

```
● ● ● EMBEDDING

# a movie, as a vector of ~768 numbers
Blade Runner → [ 0.91, -0.20, 0.74, 0.05, 0.61, -0.42, ... ]
```

Each number is a coordinate along some invisible “axis of meaning.” Loosely, you can think of these axes as “how sci-fi is it? how romantic? how violent? how hopeful?” — except a real AI model discovers thousands of subtle axes on its own, far richer than words we would name.

The magic property: things that *mean* similar things get *nearby* numbers. Blade Runner and Ghost in the Shell end up close together; Blade Runner and Paddington 2 end up far apart. Meaning becomes **geometry**.

THE MENTAL MODEL

Picture a giant map. Every movie is a pin. Similar movies cluster into neighbourhoods — the “gritty sci-fi” district, the “feel-good comedy” district. Searching “find films like Blade Runner” becomes: **drop a pin where the query lands, and look at its nearest neighbours**. A real map has 2 dimensions; an embedding map has hundreds or thousands. The idea is identical.

Who makes these numbers? An **embedding model** — a neural network like OpenAI’s `text-embedding-3`, Cohere, or an open model. You feed it text or an image; it returns the vector.

🔍 UNDER THE HOOD

Quiver is deliberately **model-agnostic**: you produce the embeddings with whatever model you like, and Quiver stores and searches them. It never bundles a model — a conscious choice, because embedding models change monthly and tying a database to one would age it instantly. Quiver’s job starts the moment you have vectors.

1.3 “Similar” means “close” — but close *how?*

If meaning is geometry, then **similarity is distance**. Two questions follow: how do we measure distance, and which measure is right? There are three standard answers, and Quiver supports all three.




FIG. 1 — Cosine asks “do the arrows point the same way?”; L2 asks “how far apart are the points?”.

Table 1 – the three similarity metrics Quiver supports

METRIC	PLAIN-ENGLISH MEANING	BEST FOR	“CLOSER” MEANS
Cosine	Do the two arrows point the <i>same direction</i> ? (ignores length)	Text / semantic search — the common default	Higher (max 1.0)
Euclidean / L2	How far apart are the points, by a ruler?	Image embeddings, spatial data	Smaller distance
Dot product	Direction <i>and</i> magnitude together	Recommenders, “maximum inner product”	Higher

WHY COSINE WINS FOR TEXT

A long document and a short tweet about the same topic point the *same direction* but have very different *lengths*. Cosine ignores length and asks only “same topic?” — exactly what you want. That is why it is the default for semantic search.

🔍 UNDER THE HOOD

Quiver normalises cosine internally: it scales every vector to length 1, after which **cosine reduces to a plain dot product**. So the engine only needs fast code for two operations (dot product and squared-L2) and cosine comes for free. Internally every metric is converted to a uniform “*smaller is closer*” orientation (similarities are negated), so all the search machinery uses one comparison rule and never confuses direction.

1.4 The scaling wall: why we can’t just compare everything

Naively, finding nearest neighbours is easy: compare the query to *every* stored vector, sort, take the top few. This is **brute force** (also “exact” or “flat” search). It is also a trap. With 1,000 movies it is instant. With **100 million** documents of 768 numbers each, every single query does *~76 billion* multiplications. Per query. Hopeless for a live website.

So vector databases make a bargain:

APPROXIMATE NEAREST NEIGHBOUR (ANN)

Give up *guaranteeing* the perfect top-10, in exchange for being **100–1000× faster** while still being right ~95–99% of the time.

That trade — a tiny, controllable sacrifice in accuracy for an enormous speed-up — is the heart of every vector database. The accuracy you keep is called **recall**, and it is the number to watch.

RECALL, DEFINED ONCE

Recall@10 = “of the 10 truly nearest items, how many did the fast approximate search actually find?” Recall of 0.96 means it found 9.6 of the true top 10 on average. Brute force always has recall 1.0 but is slow; ANN trades a sliver of recall for speed. **Every benchmark in this guide is reported at a fixed recall**, because speed without recall is meaningless — you can be infinitely fast by returning garbage.

What Quiver Is, and Why It's Different

Now that the concepts are clear, here is the product — and the narrow, deliberate edge it competes on.

Quiver is an open-source vector database written in Rust. You give it vectors (plus optional metadata like `{"year":1982,"genre":"sci-fi"}`), and it answers “find the k most similar” queries in milliseconds — over a network API, an embeddable in-process library, or as a tool that AI agents can call directly.

There are already excellent vector databases — Pinecone, Milvus, Qdrant, Weaviate, FAISS, pgvector. Quiver does not try to beat them at raw scale. It competes on a **narrow, deliberate edge** — three things, executed well.

2.1 The wedge

1 SECURITY-FIRST, BY DEFAULT

Encryption is on out of the box — every durable byte sealed on disk. You can even encrypt vectors so the server itself never sees them. Only audited, industry-standard cryptography.

2 MEMORY FRUGALITY

Serve hundreds of millions of vectors from a laptop's RAM budget, using disk-resident indexes plus compression (~32× less memory). The headline metric is RAM-at-a-fixed-recall.

3 DEVELOPER EXPERIENCE

A single static binary. Embedded `or` server mode. A retro terminal “cockpit.” Python & TypeScript SDKs. An MCP server so AI agents can drive it.

FIG. 2 — Quiver's defensible edge is the combination of three things, each executed well.

2.2 And — just as important — what Quiver honestly says it does *not* do

A trustworthy system is clear about its limits. Quiver states plainly:

- It is **single-node first**. It will not out-scale a distributed Milvus cluster. (Async read-replicas exist as a clearly-labelled stretch feature.)

- Client-side encryption protects **payloads, not vectors** — unless you opt into a special experimental mode (Part 6), with documented leakage.
- There is **no fully homomorphic “search on encrypted data with zero leakage”** — because no such scheme is fast enough to be practical today, and it will not pretend otherwise.

WHY THIS HONESTY MATTERS

A database is infrastructure you bet your data on. The project’s README carries a striking rule: *“Every performance/memory claim is backed by a reproducible benchmark on documented hardware — until those numbers are recorded, the table stays empty rather than guess.”* That discipline — never fabricating a number — is itself a feature.

The Architecture, Top to Bottom

A large codebase stays understandable only when each piece has one job and the dependencies point one way.

3.1 The whole system on one page

Before the parts, the *whole*. Everything Quiver does fits in five layers, and exactly two journeys cross them: a **write** travelling down to durable disk, and a **query** travelling down to the index and back. Keep this map in mind as you read — every later section zooms into one box on it.




FIG. 3 – The five layers, and the two journeys that cross them. A **write** takes the exclusive lock, is appended to the WAL and fsync'd through the crypto layer to disk, *then* acknowledged; a **query** takes the shared lock (so many run at once), plans its filter, searches the index, and re-ranks against full-precision vectors. Followers replicate asynchronously; every layer emits metrics and traces.

3.2 The shape of the system

Quiver is a **Cargo workspace**: a collection of small, focused Rust libraries (“crates”), each with one job, stacked so the low-level engine pieces never depend on the high-level network pieces. The rule the arrows enforce is that **the engine knows nothing about HTTP, gRPC, or terminals** — the network code is a thin shell around the same engine the embeddable library exposes.

FIG. 4 – CRATE DEPENDENCY GRAPH (ACYCLIC BY CONSTRUCTION)




FIG. 4 – The engine (bottom) is reusable and testable in isolation; framework code stays at the edges.

quiver-simd (~640 lines) — raw arithmetic: distance between two vectors, as fast as the CPU allows. Pure compute, no I/O. **quiver-crypto** (~2,650) — thin, careful wrappers over *audited* cryptography; never a home-grown cipher. **quiver-core** (~6,200) — the storage engine built from scratch: pages, the write-ahead log, segments, the catalog, compaction. *No embedded database (no RocksDB/SQLite/LMDB) is used.* **quiver-index** (~5,700) — the ANN indexes and the quantizers. **quiver-query** (~490) — the query planner: filtering, hybrid search, merge & re-rank. **quiver-embed** (~3,400) — stitches it into one clean `Database` API. The rest are edges. The whole thing is **Rust (edition 2024)**, AGPL-3.0, shipping as **one static binary**; a workspace lint policy even *forbids* `unwrap()` / `expect()`, forcing every error to be handled.

3.3 Two ways to run it

Table 2 — embedded library vs server

MODE	WHAT IT IS	WHEN TO USE
Embedded library	<code>Database::open(path)</code> — an in-process handle. No network, no auth surface, but encryption-at-rest still on.	Tests, notebooks, desktop apps, anything local.
Server	<code>quiver serve</code> — gRPC + REST with authentication, role-based access, multi-tenant namespaces, audit logging, query cost limits.	Production, shared services.

The same binary does both. The terminal cockpit (`quiver tui`) and the AI-agent server (`quiver mcp`) are just **clients** of the server API, so they work against a local *or* a remote Quiver.

3.4 What happens when you write, and when you search

Let us trace our movie example end to end. First, **writing a movie** (“upsert”). The crucial line is *append* → *fsync* → *durable*: the write is acknowledged only *after* it is flushed to disk.

FIG. 5 — THE WRITE (UPSERT) PATH

- 1 Client → Server upsert “Blade Runner” with its vector and {year:1982}
- 2 Server terminate TLS · authenticate · check role & scope · cost-limit
- 3 Server → Engine hand off the validated request
- 4 Engine → WAL (disk) DURABILITY BOUNDARY ✓
append the encrypted, checksummed record, then **fsync** — from here the write survives **kill -9** and power loss
- 5 Engine → Index insert the vector into the live index
- 6 Engine → Client acknowledged — the client hears “ok” only now

FIG. 5 — The write is acknowledged only **after** the record is physically on disk.

Now **searching** — “films like Blade Runner, but only sci-fi after 1980.” Notice the two-phase pattern that recurs *everywhere* in Quiver: a fast approximate pass to get a shortlist, then a slow exact pass on just that shortlist.

FIG. 6 — THE SEARCH (TOP-K + FILTER) PATH

- 1 Client → Planner search(query vector, k=10, filter: genre=sci-fi AND year>1980)
- 2 Query planner choose the filter strategy — **pre-filter** if selective, else **post-filter**
- 3 Planner → Index FAST · APPROXIMATE
ANN search over the compressed (quantized) vectors
- 4 Index → Storage fetch the full-precision vectors for the shortlist only
- 5 Query planner EXACT · PRECISE ✓
re-rank the shortlist with **exact** distances and re-check the filter on every survivor
- 6 Planner → Client true top-10 with payloads + a cursor for pagination

FIG. 6 — The two-phase pattern: cheap approximate narrowing, then exact precision on the shortlist.

The Engine, Block by Block

From the bottom — raw arithmetic — up to the clever data structures that make search fast.

4.1 The speed floor: SIMD distance kernels

Every search, no matter how clever, eventually computes “how far apart are these two vectors?” thousands of times. If that one operation is slow, *everything* is slow. The naïve way multiplies element by element, 768 times. The fast way — **SIMD** (“Single Instruction, Multiple Data”) — multiplies *eight numbers at once* with a single CPU instruction. It is the difference between a cashier scanning one item at a time and a scanner that reads eight barcodes in one pass.



FIG. 7 — The foundational speed-up every index is built on top of.

🔍 UNDER THE HOOD

`quiver-simd` provides hand-written kernels for cosine, squared-L2, dot product (over 32-bit floats and 8-bit integers), and **Hamming distance** (bit-counting, for binary compression — §4.3). At runtime it *detects the CPU's features* and dispatches to the AVX2 / AVX+FMA path if present, falling back to portable scalar code otherwise — so one binary runs fast on a modern server and *correctly* on an old one. Every SIMD path is **differential-tested**: random vectors of awkward lengths (0, 1, 7, 769 — deliberately not multiples of 8, to exercise the leftover “tail”) are fed to both versions and asserted equal. Fast code you cannot trust is worthless; this is how it earns the trust.

4.2 The core trick of ANN: navigable graphs

How do you find nearest neighbours among 100 million vectors *without* comparing them all? The most successful answer is a **proximity graph**.

THE IDEA

Build a network where each vector is a node, connected by “friendship” links to a handful of nearby vectors. To search, **start anywhere and keep walking to whichever friend is closer to your query, until you can’t get closer**. Like finding a house by repeatedly asking “which of your neighbours lives closest to this address?” — you converge in a few hops, never visiting the whole city.

Quiver implements the two best-known proximity-graph families: **HNSW** and **Vamana (DiskANN)**, plus the cluster-based **IVF**.

HNSW – the “skip-list of maps”

HNSW (Hierarchical Navigable Small World) adds one idea to the proximity graph: **layers**, like a zoomed-out highway map laid over a detailed street map. You enter at the sparse top, take big leaps into the right region, then drop down layer by layer, refining, until the dense bottom layer where every vector lives. Coarse-to-fine, geographically.




FIG. 8 – Big leaps up top, careful local search at the bottom – few comparisons, high recall.

🔧 UNDER THE HOOD — THE KNOBS

M (default 16): how many friends each node keeps — more friends, better recall, more memory.

efConstruction (default 200): how hard it searches *while building*. **ef_search**: how hard it searches *at query time* — the size of the candidate “beam,” and your live **recall ↔ speed dial** (you will see this exact knob in the benchmarks). Two refinements lift Quiver above a textbook version: (1) the **diversity heuristic** — when choosing friends, prefer ones pointing in *different directions*, so edges span the space instead of clumping, materially improving recall on clustered data; (2) **soft deletes** — a deleted point is tombstoned (kept as a navigation stepping-stone, never returned), and the search widens its beam to compensate, so recall holds even after many deletes.

Vamana / DiskANN — the graph built for *disk*

HNSW assumes the graph lives in RAM. **Vamana** (behind Microsoft’s DiskANN) builds a single flat graph engineered so it can live on an **SSD** and still answer queries in very few disk reads — the key to Quiver’s memory wedge. Its secret is the **RobustPrune α -slack rule**: when picking a node’s neighbours it keeps the closest, then drops any candidate the chosen one is already $\alpha\times$ closer to — forcing edges to span *long* distances, so greedy search reaches anywhere in very few hops (very few SSD page reads).

IVF — the “library card catalogue”

IVF (Inverted File) divides and conquers by neighbourhood: cluster all vectors into cells, and at query time scan only the few cells nearest the query.




FIG. 9 — **nprobe** (how many cells to check) is IVF’s recall ↔ speed dial.

Table 3 – choosing an index

INDEX	LIVES IN	STRENGTH	USE WHEN
HNSW	RAM	Highest QPS at high recall	You have the RAM and want raw speed
Vamana / DiskANN	SSD (compressed in RAM)	Tiny RAM footprint	Datasets bigger than your RAM budget
IVF	RAM or SSD	Fast build, predictable memory, easy updates	Streaming data, simpler tuning

🔍 UNDER THE HOOD — ALL THREE UPDATE INCREMENTALLY

A naïve ANN index rebuilds from scratch on every write, which is fatal for streaming data. Quiver’s three families all avoid that: HNSW inserts and **soft-deletes** in place (tombstones, §4.2); IVF uses **SpFresh-style LIRE** rebalancing so cells split and merge as data streams in; and the Vamana graphs use **FreshDiskANN’s StreamingMerge** — a read-only base graph plus a small in-memory delta graph and an O(1) deletion set, searched together and consolidated only past a churn threshold. So graph writes are size-independent, the index stays a *derived* structure (the WAL is the source of truth, so the crash gate is untouched), and the only rebuild that ever happens is the deferred, off-lock one of §5.4.

4.3 Quantization: the memory-frugality superpower

One million 768-d vectors at 4 bytes each is **3 GB** of RAM just for the vectors; ten million is **31 GB** — it does not fit on a laptop. **Quantization** is lossy compression for vectors: shrink each into a tiny “code,” search on the codes, accept slightly fuzzy distances.

Table 4 – Quiver’s three quantizers

QUANTIZER	CODE SIZE	COMPRESSION	HOW IT WORKS
Scalar (SQ)	dim bytes	~4×	Each number stored as an 8-bit int, not a 32-bit float
Product (PQ)	m bytes	up to 32×	Split into chunks; replace each with the ID of its nearest learned prototype
Binary (BQ)	dim/8 bytes	~32×	Keep only the <i>sign</i> of each number (1 bit); compare by fast bit-counting

Product Quantization, simply. Imagine describing a face not with exact measurements but as “nose type #7, eyes type #3, jaw type #12.” If everyone shares a catalogue of types, those three small numbers reconstruct the face approximately. PQ learns a *codebook* of prototype chunks, then stores each vector as a handful of prototype IDs — a 3072-byte vector becomes ~96 bytes, **32× smaller**. The genius that makes lossy compression safe:

THE APPROXIMATE-THEN-RE-RANK PATTERN – THE ENGINE’S GOLDEN RULE

1. **Rank cheaply on the tiny codes.** Use the compressed vectors to quickly find the top 100–800 candidates. Fast, but fuzzy.
2. **Re-rank precisely on the originals.** Fetch the full-precision vectors for only that shortlist, compute exact distances, return the true top 10. You recover almost all the recall “lost” to compression.




FIG. 10 – The shortlist depth (`rerank_factor`) is the master recall ↔ latency dial. A deeper pool can only *add* true matches.

🔍 UNDER THE HOOD

PQ uses **asymmetric distance computation (ADC)**: the query stays full-precision and a small lookup table is precomputed once per query, so scoring each code is a few table lookups and adds — extremely fast. Binary quantization leans on the SIMD **Hamming kernel** from §4.1: XOR the sign-bit codes, count differing bits, which a CPU does blisteringly fast — an ideal coarse pre-filter before the exact re-rank.

4.4 Putting it together: the disk-resident path *(the “32×” headline)*

Combine the **Vamana graph** (built for SSD) with **Product Quantization** (32× smaller), and you get Quiver’s signature feature.




FIG. 11 — Only tiny PQ codes stay in RAM; full vectors and the graph live encrypted on SSD, touched only when visited.

The result, in Quiver’s measured terms: a dataset serves from **roughly its PQ-code footprint** instead of the full vectors. For a 10M × 768-d collection that is about **~1 GB resident instead of ~31 GB** — exact arithmetic, and why “hundreds of millions of vectors on a laptop” is a real claim, not marketing.

The in-memory floor — and what v0.23.0 fixed. “Roughly the PQ-code footprint” is a *floor*, not zero: what stays resident is the **PQ codes + the id map + the PQ codebook + a small in-memory FreshDiskANN delta** (recent writes not yet folded into the base graph); the full-precision vectors and base graph are `mmap`’d on disk and demand-paged. A subtlety undercut the claim *in practice* until **v0.23.0**: a restarted server **rebuild the disk index from every full-precision vector on open**, so its post-restart RSS briefly looked like the in-memory path. The **durable on-disk DiskVamana index** (ADR-0063) fixes that — the server `mmap`s its frugal base and replays only the post-checkpoint WAL tail on open (falling back to the authoritative rebuild on any mismatch, so the `kill -9` gate is untouched) — so it serves from the resident-PQ floor *immediately after a restart*, and the wedge benchmark now **cold-reopens the server before sampling RSS** to measure exactly that floor.

4.5 Filtering: search by meaning *and* by rules

Real queries are hybrid: “films like Blade Runner, **but only sci-fi released after 1980**.” That is a similarity search **plus** a structured filter on metadata. Quiver expresses filters as a **typed predicate tree** you can nest arbitrarily (`eq, ne, in, lt, lte, gt, gte, exists` plus `and/or/not`, over dot-paths like `user.age`):

FILTER — JSON WIRE FORM

```

{ "and": [
  { "eq": { "field": "genre", "value": "sci-fi" } },
  { "gt": { "field": "year", "value": 1980 } },
  { "not": { "eq": { "field": "rating", "value": "G" } } }
] }
  
```

The interesting part is *how* it runs the filter — the planner picks one of two strategies:

STRATEGY	WHAT IT DOES	CHOSEN WHEN
Pre-filter	Find rows matching the filter first (via a secondary index), then search similarity only over those	The filter is selective (few rows) — e.g. <code>user_id = 42</code>
Post-filter	Search similarity first, then drop results that fail the filter	The filter is broad (many rows) — e.g. <code>year > 1980</code>

WHY BOTH

Pre-filtering a *broad* filter wastes time building a huge candidate set; post-filtering a *selective* filter risks all candidates being filtered out, leaving nothing. The filter is **re-checked on every surviving result**, so the answer is always exact — the planner only affects speed, never correctness.

4.6 Hybrid search: combining meaning with keywords (RRF)

Sometimes pure semantic search is not enough — someone searching a product code like “SKU-4417” wants that *exact* term, not “vibes.” **Hybrid search** runs both a **dense** (embedding) search and a **sparse** (keyword/term-weight) search, then merges the two ranked lists. But their scores live on incomparable scales. The elegant fix is **Reciprocal Rank Fusion (RRF)**: ignore scores, use only *rank*.

● ● ● RECIPROCAL RANK FUSION

```
# each list gives a doc 1/(k0 + rank) points; sum across lists
RRF(doc) = Σ 1 / (k0 + rank_in_list)      (k0 = 60, the standard constant)
            over each result list
```

Because it is purely rank-based, RRF needs **no score normalisation** — which is exactly why it is the robust, industry-standard fuser. A document ranking high in *both* lists wins. A sparse vector (e.g. from a SPLADE model) rides inside the point’s payload, so enabling hybrid search needs *no change to the on-disk format*.

🔍 UNDER THE HOOD — MULTI-VECTOR / COLBERT

Quiver also supports **late-interaction (ColBERT-style)** retrieval: a document is stored as a *set* of token vectors and ranked by **MaxSim** (for each query token, find its best-matching document token, then sum). Cleverly, each document is modelled as a *group of ordinary rows* in the same storage engine — so there is no new on-disk format and the crash-safety guarantees are untouched. A ColBERT corpus (many small token vectors) is exactly the pool the IVF+PQ compression path was built for.

How It Survives `kill -9`

A database has one sacred promise: if it told you a write succeeded, that write is not lost — not to a crash, not to a power cut.

5.1 The Write-Ahead Log (WAL)

The idea is older than databases and simple: **write down what you are about to do *before* you do it**. Like a ship's logbook — before changing course, log the new heading. If interrupted, the log tells you exactly where things stood. In Quiver, every mutation is encoded, **appended** to the WAL, **fsync'd** (forced all the way to physical disk, not just the OS cache), and *only then* acknowledged. That ordering is the entire guarantee: once you get “ok,” the record is physically on disk. The index update happens *after* the ack — and if the machine dies first, recovery replays the log to redo it.

5.2 Catching corruption: checksums and torn writes

What if a crash happens *mid-write*, leaving a half-written record? Or a disk bit silently rots? Every WAL record is framed with a length prefix and a **CRC32C checksum**:




FIG. 12 — Length + checksum framing turns a torn tail into a clean, detectable boundary.

On recovery, Quiver reads frames until one **fails its check** — the unmistakable signature of a crash mid-append — and treats everything from that point on as “never happened.” Because the log is append-only and every record was fsync'd before its ack, the *only* place a broken frame can legitimately appear is the very tail. A torn trailing record was, by definition, never acknowledged, so discarding it loses nothing. The same discipline applies to the 16 KiB data pages: each carries its own CRC, so **corruption is detected on read and never silently served**.

THE BOTTOM LINE

Acknowledged writes survive `kill -9` and power loss; corruption is always *detected* rather than served as a wrong answer; and all of this holds **whether or not encryption is on**, because the checksums guard the plaintext path and encryption sits on top. Quiver’s test suite literally kills the process with `kill -9` mid-operation and asserts the data is intact on restart — the “crash gate.”

5.3 Many readers, one writer

Durability is about *not losing* writes; throughput is about *serving* reads. Quiver is **single-writer, many-reader**: the server guards the engine with a reader–writer lock (ADR-0057). A search takes the *shared* lock, so many searches run **in parallel** — read throughput scales with cores instead of serializing on one mutex. A write takes the *exclusive* lock; the single-writer model, and everything in §5.1–5.2, is unchanged.

There is one subtlety, and it is the whole story of this section. Some writes — an HNSW in-place update, a bulk load, a delete, a replicated write — cannot be absorbed into the index in place, so the engine **defers** the rebuild: it marks the collection stale and leaves the prior, still-valid index in place. The question is what the *next* reader does about it. The naïve answer (what v0.21.0 shipped) is: take the exclusive lock and rebuild before serving. That is correct, but it has a brutal failure mode — measured below.

5.4 The rebuild that doesn’t stop the world

Rebuilding an ANN index is not cheap: it is roughly a single-threaded build pass over the whole collection. If a reader does it *under the exclusive lock*, every other reader blocks for the entire build. We measured exactly that, with a reproducible harness (`mvcc_measurement.rs`, ADR-0062):

Table 5 — the deferred-rebuild reader stall, before the fix (dev box · WSL2 · HNSW · dim 128 · indicative)

COLLECTION SIZE	SINGLE-THREAD REBUILD	STEADY READ P99 (CONCURRENT)	READER STALL DURING REBUILD
20 000 vectors	7.3 s	422 µs	8.1 s
50 000 vectors	26.7 s	379 µs	29.7 s
100 000 vectors	68.7 s	408 µs	76.6 s

The stall tracks the rebuild duration and is **four to five orders of magnitude** above the steady-state p99 — borne by *every* read that arrives during the window, and worse at scale (a 1 M disk-Vamana rebuild is minutes). So the fix is not a micro-optimization; it is the difference between a database and a doorstop under write-then-read load.

THE FIX — REBUILD OFF THE EXCLUSIVE LOCK (ADR-0062)

Serve the prior snapshot, build with no lock held, swap at the end. A stale reader returns results from the *prior* index (still a valid graph over the prior ids) instead of blocking. Meanwhile one rebuild is driven off-lock: its inputs are captured under the *shared* lock (other reads continue), the new index is built holding **no lock at all**, and only the final pointer-swap takes a brief exclusive lock. A per-collection **write-generation counter** guards against a write that lands mid-build: if the generation moved, the collection stays stale and another rebuild is scheduled — so no write is ever lost.




FIG. 13 — The seconds-long stall (top) collapses to the cost of serving the prior snapshot plus a brief swap (bottom). No `unsafe`, no lock-free data structure — just `Arc` and the existing `RwLock`.

VISIBILITY, NEVER DURABILITY

This moves read *visibility*: a server read may briefly miss a write committed a millisecond ago (snapshot isolation, sanctioned by ADR-0053), but it never sees a half-applied one, and the WAL-fsync acknowledgement of §5.1 is byte-for-byte unchanged. Embedded `&mut` callers still rebuild synchronously, so an in-process program always reads its own writes. That fixed the rebuild's *lock scope*; §5.5 closes the remaining gap — the *write's* lock window.

5.5 Reads that never wait on a writer — lock-free MVCC

The off-lock rebuild solved the worst case. But even an *ordinary* write has to briefly lock the index to record itself — and a “lock” here means exactly what it sounds like: while the writer holds it, every reader waits at the door. The window is short (milliseconds), but it adds up. We measured how much, by running searches and writes at the same time and asking *what fraction of its read speed does the database keep?* (1.0× would mean

writes cost reads nothing.) The answer was sobering: **one** steady writer dropped reads to about a tenth of their speed, and a **second** writer collapsed them to almost nothing — the readers spend their time waiting at the door, not searching.

The fix is a classic database trick called **MVCC** — **multi-version concurrency control**. Picture a librarian reorganising a shelf. The slow way: she closes the whole reading room while she works, and everyone waits. The MVCC way: she leaves the current shelf untouched for readers, prepares an updated copy off to the side, and swaps it in the instant it's ready — readers never stop, and never catch the shelf half-finished. Quiver does exactly this with a search index (ADR-0064), behind an off-by-default `QUIVER_MVCC_READS` switch.

KEEP A FROZEN COPY; KEEP RECENT EDITS ON A STICKY NOTE

The writer keeps the last fully-built index frozen as a **snapshot**. New writes that arrive afterwards don't disturb it — they go onto a small **overlay**, like a sticky note that says *“also include these few new points, and ignore those deleted ones”* (a deleted point is marked with a **tombstone** — a note that it's gone, rather than erasing it on the spot). A reader picks up the current snapshot in a single, instant step that needs no lock — that lock-free hand-off is what the `arc-swap` library gives us — then searches the frozen index, glances at the short sticky note, and combines the two. Because the note stays small, the writer can rewrite it cheaply on every write; once it grows past a threshold, the next off-lock rebuild folds it into a fresh frozen copy and the note starts blank again. Old copies tidy themselves up: Rust counts how many readers still hold each one and drops it automatically when the last reader walks away — no manual cleanup, no `unsafe` code. And a reader always sees one whole, consistent version — never a write applied halfway.

This is split by *what the read needs*. A plain **vector search** (just “find the nearest points”) needs only the snapshot, so it runs entirely lock-free and never waits on a writer. A search that also returns each point's stored data — its payload, or a filter on it — still has to read the main store, which isn't safe to read while the writer is changing it, so those reads take the shared lock as before (but still answer from the snapshot). The common, hot path — nearest-neighbour search — is the one that goes fully lock-free.



FIG. 14 — Retained read-QPS at batch 1 (the worst case for the lock), off → on. The multi-writer collapse is gone: under the `RwLock` a second small-upsert writer starves readers to ~0; lock-free MVCC holds ~0.67×-0.79×. The *ratio* on identical hardware is the proof; absolute QPS is reference-hardware-pending.

The full grid, `QUIVER_MVCC_READS` off → on (retained read-QPS, 1.0× = no penalty):

Table 6 — read-during-write, RwLock vs MVCC (SIFTSMALL, dev box, same sweep)

READERS VS.	BATCH 1 (OFF→ON)	BATCH 64 (OFF→ON)	BATCH 512 (OFF→ON)
1 writer	0.80× → 0.87×	0.66× → 0.71×	0.50× → 0.74×
2 writers	0.00× → 0.79×	0.35× → 0.75×	0.30× → 0.75×
4 writers	0.01× → 0.67×	0.06× → 0.69×	0.07× → 0.71×

Durability is untouched: MVCC changes *visibility*, *not durability* — the overlay is derived from the same WAL the store replays, and the `kill -9` gate holds by construction. It ships **opt-in**: the proven `RwLock` path stays the default until the win is confirmed on dedicated hardware (on a shared dev box only the ratio is honest; the absolute QPS is reference-hardware-pending).

Security, the Defining Feature

This is where Quiver makes its strongest claim. We go from the disk outward.

6.1 Encryption at rest – on by default

Most databases make you opt *in* to encryption. Quiver makes you opt *out* — and won't let you, on a non-loopback bind. Out of the box the server demands a 256-bit master key and **seals every durable byte** — segments, the manifest, *and* the write-ahead log — with **XChaCha20-Poly1305**, a modern, audited authenticated cipher. “Authenticated” (AEAD) matters: it not only hides data, it **detects tampering** — flip a single bit and decryption fails loudly instead of returning subtly wrong data.

🔍 UNDER THE HOOD

Only audited cryptography is used — RustCrypto's AEAD/KDF and **rustls** (backed by the audited **ring** library) for TLS. **No home-grown primitives, ever** — the cardinal rule of applied cryptography. Key material is wrapped in zeroizing types so it is scrubbed from memory when dropped.

6.2 Envelope encryption + crypto-shredding

Instead of encrypting everything with the one master key, Quiver uses a **two-level key hierarchy**. Each collection gets its own random **Data-Encryption Key (DEK)**, itself stored encrypted (“wrapped”) under the master key.

FIG. 15 — THE ENVELOPE KEY HIERARCHY




FIG. 15 — Per-collection keys, each wrapped by the master key — the structure that makes instant, provable deletion possible.

CRYPTO-SHREDDING — INSTANT, PROVABLE DELETION

To permanently delete a collection, Quiver does not overwrite gigabytes. It just **deletes that collection's tiny wrapped DEK file**. The DEK existed nowhere else. Once gone, the collection's encrypted bytes are **mathematically unrecoverable — even by the holder of the master key, even from a backup tape that still has the ciphertext**.

This is the gold-standard pattern for the GDPR “right to erasure”: you can *prove* deletion happened (the key is provably gone) without trusting that every copy on every disk and backup got physically scrubbed. Quiver's tests demonstrate exactly this — seal a page, shred the collection, then show a fresh key-ring with the correct master key can no longer decrypt it.

6.3 In transit and access control

- **TLS / mTLS:** encrypted connections required for any non-loopback bind; optional mutual TLS makes clients prove identity with a certificate too.
- **Default-deny RBAC:** access by scoped API key, with a **role** (`read` $\subseteq$ `write` $\subseteq$ `admin`) and a **collection scope** (exact names, or an `acme.*` prefix for per-tenant isolation). Over-reach returns `403`; listing even *hides* out-of-scope collections.
- **Append-only audit log:** every mutating/admin operation and every denial is recorded — who, what, which resource, what outcome — but **never the secret**.
- **Query cost limits:** the server caps how expensive a single query can be, closing off “authenticated denial-of-service.”

6.4 The frontier: encrypting the *vectors* themselves

By default, client-side encryption protects **payloads** (metadata): you can seal `{"ssn": "..."}` with a key the server never sees, while leaving `{"genre": "sci-fi"}` cleartext so the server can still filter on it. But can a server rank vectors it cannot read? Quiver offers two honest, opt-in answers — and is scrupulous about the trade-offs, because **no scheme gives fast server-side ranking, zero leakage, and good performance all at once.**

Table 7 — the two encrypted-vector modes

MODE	SERVER SEES	SERVER RANKS?	SECURITY	HONEST COST
client_side	Only opaque ciphertext + a zero placeholder	No — learns <i>nothing</i>	Strongest (IND-CPA)	Client fetches the (pre-filtered) set and ranks locally
dcpe (experimental)	Ciphertext it can compare by approximate L2	Yes — without the plaintext or key	Weaker — not semantically secure	Leaks the approximate distance-ordering <i>by design</i> ; L2-only

The DCPE mode implements a *published* academic scheme (“Scale-And-Perturb” distance-comparison-preserving encryption) built only from audited primitives, with the paper’s hardening steps; the docs tell you to read the threat model before using it.

THE SECURITY-FIRST ETHOS IN MINIATURE

A lesser project would ship DCPE and call it “encrypted search,” full stop. Quiver ships it behind an experimental flag, names the exact academic paper, and spells out precisely what it leaks and which attacker breaks it. That candour is the point.

Benchmarking Quiver – Method, Results, Verdict

Performance claims are worth only the methodology behind them. Here is how we measured, what we found, and what it proves about Quiver’s value.

7.1 Why we benchmark at a fixed recall

It is trivial to make a vector search “fast” — just return less-accurate results. So a throughput number on its own is meaningless. Every figure here is reported **at a fixed recall bar** (recall@10 $\geq$ 0.95 unless noted): the systems are tuned until they all find ~the same fraction of the true nearest neighbours, and only *then* is their speed compared. That is the only honest way to compare ANN engines.

7.2 The method

- **Same box, every system.** An `ann-benchmarks`-style harness runs each database on one machine — an Intel i7-12700H laptop, 20 threads, 15.5 GB RAM — so the comparison is apples-to-apples.
- **Seven competitors:** FAISS, Qdrant, Milvus, Chroma, pgvector, LanceDB, Weaviate. Milvus is run as the full server (Docker), not the in-process Lite build.
- **Honest caveats, stated up front:** FAISS/Chroma/LanceDB run *in-process*, so their reported RAM is inflated by the Python harness (not directly comparable to the isolated-server numbers); Qdrant memory-maps vectors to disk by default (so its RAM looks tiny); and Quiver’s “build” time is the *bulk-ingest* path (`points:bulk`) measured as honest *time-until-queryable* — ingest plus the deferred index build forced by the first query, the same thing every competitor’s build column captures.
- **Never fabricate.** Absolute RSS on reference hardware and the 10M-scale disk path are explicitly marked “pending” rather than guessed.

7.3 Quiver’s own recall ↔ speed curve (SIFT1M, 1M × 128-d, in-memory HNSW)

This single table shows the central trade-off of the whole field: as you turn the `ef_search` dial up, recall climbs and throughput falls.

Table 8 – Quiver SIFT1M, HNSW (M=16, efC=200), single thread

EF_SEARCH	16	32	64	128	256
recall@10	0.793	0.895	0.958	0.986	0.995
QPS (1T)	1539	1424	1222	955	701
p95 latency (ms)	0.8	0.8	1.0	1.3	1.7




FIG. 16 – RAG pipeline that re-ranks anyway? Run at ef=64. Legal discovery where a miss is unacceptable? ef=256.

7.4 Head-to-head (SIFT1M, peak single-thread QPS at recall@10 ≥ 0.95)

Table 9 – every system on the same box; ¹ in-process RSS inflated · ³ Qdrant disk-backed

SYSTEM	RECALL@10	QPS (1T)	P95 (MS)	RSS (MB)	BUILD
FAISS 1.14	0.968	3842	0.4	1234 ¹	82 s
Quiver v0.20	0.958	1222	1.0	2069	581 s ²
Chroma 1.5	0.977	1009	1.1	3752 ¹	153 s
Weaviate 1.27	0.983	663	1.7	2218	38 min
Milvus 2.5 (server)	0.986	649	1.9	2075	26 s
Qdrant 1.13	0.974	358	4.5	258 ³	98 s
pgvector 0.7	0.980	118	11.8	1291	132 s
LanceDB 0.33	0.557 ⁴	219	5.3	2475 ¹	15 s




FIG. 17 — Single-thread QPS at recall@10 $\geq$ 0.95 (v0.20.0). Quiver is **second only to FAISS**, with the field’s second-best tail latency (1.0 ms).

7.5 The harder test: GIST1M (1M × 960-d)

GIST1M is higher-dimensional and far more demanding — most systems plateau below recall 0.95 in a bounded sweep. Here Quiver **matches FAISS on recall (0.923 vs 0.919)**, and on the v0.20.0 engine is markedly faster than v0.18.0 at the same recall (182 → 268 QPS, p95 7.7 → 4.4 ms).

Table 10 — GIST1M, each system at its most efficient config (best point at ef_search $\leq$ 256)

SYSTEM	RECALL@10	QPS (1T)	P95 (MS)	RSS (MB)
Quiver v0.20	0.923	268	4.4	10117
FAISS 1.14	0.919	471	2.7	7526 ¹
Chroma 1.5	0.790	577	2.1	8156 ¹
Weaviate 1.27	0.828	418	2.8	8880
Qdrant 1.13	0.955	185	6.3	391 ³
Milvus 2.5 (server)	0.961	53	29.4	6821
pgvector 0.7	0.980	8	194	4393

The three systems that clear 0.95 here (Qdrant, Milvus, pgvector) pay for it in latency/QPS. LanceDB did not complete GIST1M — building a 960-d/1M index in-process exhausted memory (an honest DNF even with 27 GB of swap, not a fabricated row).

7.6 The v0.22.0 dimensions: recall depth, concurrency, and filtering

The v0.22.0 release added four measurement dimensions (ADR-0061), all on the same SIFT1M, all *dev-box* · *indicative*, and **every number below traces to a committed CSV** in [docs/benchmarks/results/comparison-v0.22.0/](https://github.com/achref-soua/quiver/blob/main/docs/benchmarks/results/comparison-v0.22.0/) .

Recall depth – how far down the list stays right

Recall@10 is the headline, but a RAG pipeline that re-ranks 50 candidates cares about recall@100. Measuring all three at once shows where the beam runs out: at a fixed `ef_search`, recall@100 needs a *deeper* candidate beam than recall@10, so it only catches up once you widen the search.

Table 11 – Quiver SIFT1M recall at depth 1 / 10 / 100 (HNSW, single thread)

EF_SEARCH	16	32	64	128	256
recall@1	0.853	0.928	0.966	0.984	0.988
recall@10	0.793	0.895	0.958	0.986	0.995
recall@100	0.918	0.918	0.918	0.944	0.983

Saturated concurrency – the payoff of the reader-writer lock

This is the dimension the §5.3 concurrent-reads work exists to move: **QPS under 8 saturating client threads (NT) versus one (1T)**. Read it *honestly*. A single Python client process (the GIL plus one HTTP socket) is itself a concurrency ceiling, so for *light* queries (low `ef`, sub-2 ms) the client saturates first and NT sits at or below 1T. The server-side win appears on *heavier* queries, where the client is no longer the bottleneck and the parallel readers pull ahead — up to **1.76× at ef=256** (recall 0.995). It is not a fabricated “8×”; it is the real, client-limited shape of the speed-up.

Table 12 – SIFT1M throughput, 1 thread vs 8 saturating threads (NT), same recall per column

EF_SEARCH	16	32	64	128	256
recall@10	0.793	0.895	0.958	0.986	0.995
QPS (1T)	1131	1001	855	673	506
QPS (8T)	949	968	928	938	892
speed-up	0.84×	0.97×	1.08×	1.39×	1.76×




FIG. 18 – As queries get heavier, the single client thread (bronze) falls from 1131 to 506 QPS while the 8-thread server throughput (verdigris) holds near 900 – so the lines cross and saturated throughput pulls ahead, 1.76× at ef=256.

Filtered selectivity – the planner switching regimes

A payload pre-filter (`bucket < s`) keeps `s`% of the collection; recall is measured against the *filtered* exact ground truth (brute force over the matching subset). The planner crosses between two regimes, and the curve shows it: a **very selective** filter pre-filters to an *exact scan* (recall ≈ 1.0 , but the scan to find the subset is the latency cost — ~142 ms); a **looser** filter post-filters an ANN result, which dips into a **recall valley** at mid-selectivity before recovering as more candidates survive the filter; and an empty filter is just pure ANN again (878 QPS).

Table 13 – SIFT1M recall & latency vs filter selectivity (ef_search = 128)

KEPT BY FILTER	RECALL@10	QPS (1T)	P50 (MS)	P95 (MS)	REGIME
1%	1.000	7	142.3	156.1	pre-filter · exact scan
5%	0.618	7	134.6	147.0	post-filter · recall valley
25%	0.970	5	189.2	205.4	post-filter · recovering
50%	0.981	4	253.6	273.7	post-filter
100%	0.986	878	1.1	1.4	no filter · pure ANN



FIG. 19 — Always correct, never wrong: the filter is re-checked on every survivor (§4.5), so the “valley” is a *recall* dip the planner trades for speed, not an incorrect answer. Very selective filters pay in scan latency instead.

7.7 The real wedge: memory at a fixed recall

Critically — and Quiver says this itself — the tables above are an **in-memory HNSW** comparison, so they are *not* where Quiver’s memory wedge shows up. The wedge is the **disk-resident path** (Part 4.4), which holds only PQ codes in RAM. The v0.22.0 quantization sweep shows the trade it makes, honestly: the disk-Vamana + PQ path holds recall@10 close to in-memory HNSW, but PQ trades away the *deep* tail — recall@100 falls from 0.94 to 0.71.

Table 14 — SIFT1M index/quantization trade-off, each built in its own fresh server (ef_search = 128)

CONFIG	RECALL@1	RECALL@10	RECALL@100	BUILD (S)	QPS (1T)
hnsw (in-memory)	0.984	0.986	0.944	619	883
disk_vamana + pq16	0.974	0.966	0.709	1025	598



FIG. 20 — Compression keeps the head (recall@10 barely moves) but trades the tail (recall@100 collapses). The serving-RAM number is **reference-hardware-pending** on the shared dev box: post-build RSS here is the build’s allocator high-water mark, while the representative figure is the **cold-reopen** footprint where only the PQ codes (plus the small delta and codebook) stay resident — the metric the durable disk index (ADR-0063) finally makes real and the wedge runner now samples after a cold restart. So it is omitted, not estimated.



FIG. 21 — On SIFTSMALL the disk path serves recall@10 up to 1.000 while holding only PQ codes in RAM. The head-to-head RSS vs Qdrant/LanceDB is explicitly reference-hardware-pending — never fabricated.

7.8 The verdict — the value of Quiver

WHAT THE NUMBERS PROVE

On a like-for-like in-memory test, Quiver is **second only to FAISS** in throughput-at-recall and second-best in tail latency — ahead of Chroma, Weaviate, Milvus, Qdrant, pgvector, and LanceDB — and on the punishing 960-d GIST1M it **matches FAISS on recall**. For a from-scratch engine, that is genuinely competitive territory.

But raw QPS was never the point. Quiver’s value is the **combination** the benchmarks bracket:

- **Competitive speed & recall** — you are not trading performance away to get the other benefits. It holds its own against purpose-built C++ engines.
- **The memory wedge** — the differentiator the head-to-head table deliberately does *not* capture: ~32× less RAM at a fixed recall via the disk-resident PQ path, turning a “needs a big server” dataset into a “runs on a laptop” one.
- **Security by default** — encryption-at-rest on, crypto-shredding, optional encrypted vectors, audited crypto only. No competitor in this table makes that its default posture.

- **One binary, two modes, agent-native** — embeddable *and* server, with SDKs, a cockpit, and an MCP server, from a single static binary.
- **Trustworthy numbers** — every caveat is stated; absolute figures pending reference hardware are marked, not guessed. You can reproduce the comparative standings yourself.

Put plainly: if you want competitive ANN performance with security on by default and a memory footprint small enough to self-host on modest hardware, Quiver occupies a niche the incumbents leave open.

The Decisions Behind the Code

Great engineering is visible in the choices — especially the restraint. Each is recorded as an Architecture Decision Record (ADR) in the repo.

Table 15 — the decisions that define Quiver

DECISION	WHAT THEY CHOSE	WHY
Language	Rust	Memory safety without a garbage collector → predictable low latency and no whole classes of security bugs.
Storage engine	Built from scratch (no RocksDB/SQLite/LMDB)	Full control over the on-disk format, encryption, and crash semantics — the core differentiators.
Cryptography	Only audited libraries (RustCrypto, ring/rustls)	“Don’t roll your own crypto” — the one universal rule of security engineering.
Crash safety	WAL + fsync-before-ack + CRC + point-in-time recovery	The non-negotiable database promise, proven by a <code>kill -9</code> test gate.
Scope	Single-node excellence first; distribution is a labelled stretch	Do one thing superbly before doing everything adequately.
Honesty	No number ships unless reproducible on documented hardware	Trust is the product when you store someone’s data.
Error handling	<code>unwrap()</code> / <code>expect()</code> banned by lint	Force every failure to be handled — no surprise panics in production.

THE THROUGHLINE

Correctness and security first, performance second, features last — and never lie about any of them.

Beyond Search: RAG, Full-Text & Operations

A search engine is only half a product. The rest is the work of using it — turning text into vectors, mixing keyword and meaning, backing data up, watching the system breathe, and keeping one noisy client from starving the others.

9.1 Bring your own *nothing*: server-side embedding

The number-one friction in retrieval is the embedding step: “I have text, but the database wants vectors, so I must run a model myself.” Quiver stays model-agnostic at its core — but at the *edge* (never in the engine) it offers an opt-in, per-collection embedding hook. Configure a provider, then send **text** and let the server embed it.

THE CORE IDEA

upsert_text sends a document’s words; the server embeds them with the collection’s configured provider and stores the vector. **search_text** embeds your query the same way, searches, and can **rerank** the shortlist with a second, sharper model — retrieve-then-rerank in a single call.

The provider is chosen by configuration, never hard-wired to one vendor. Secrets are never stored: a config field names an *environment variable*, resolved at startup so a missing key fails fast.

Table 16 — built-in embedding / rerank providers (opt-in, per collection)

PROVIDER	SHAPE	NOTES
OpenAI	<code>/v1/embeddings</code>	The de-facto standard shape; also used by many local servers.
Ollama	OpenAI-compatible	Local models on your own hardware — no data leaves the box.
HTTP	OpenAI-compatible	Any endpoint that speaks the shape, parameterised by base URL + auth.
Cohere	<code>/v2/embed</code> , <code>/v2/rerank</code>	Its own shape, including a native reranker.
fake	deterministic	A hash-to-vector stub for tests and offline demos — no network.

FIG. 22 — THE EMBEDDING & RERANK PIPELINE (SEARCH_TEXT)

- 1 Client → Server `search_text("a fast fox", rerank: true)` — just words, no vector
- 2 Server → Embedder embed the query with the collection's provider (key from an env var)
- 3 Server → Engine **HYBRID**
dense ANN ⊕ BM25 full-text, fused with RRF → an over-fetched candidate pool
- 4 Server → Reranker **SHARPER, SLOWER ✓**
a cross-encoder scores each (*query, document*) pair and reorders the pool
- 5 Server → Client the reranked top-k — one round trip, no model on the client

FIG. 22 — Embedding and reranking live at the server edge, opt-in and provider-agnostic; the engine still only ever sees vectors.

WORKED EXAMPLE — THE MOVIE CORPUS, END TO END

Our running example, finally as real calls. Point a `movies` collection at an embedding provider, send words (no vectors — payloads like `{"year":1982}` ride along), and ask in plain language:

CINEMA — BUILD & SEARCH A MOVIE CORPUS BY TEXT

```
# the "movies" collection embeds text with its provider (key from $OPENAI_API_KEY)
upsert_text("movies", "br", "Blade Runner — a replicant hunter in a neon dystopia")
upsert_text("movies", "gits", "Ghost in the Shell — a cyborg cop questions identity")
upsert_text("movies", "pad", "Paddington 2 — a kind bear clears his name")

# query by meaning, then rerank the shortlist with a sharper model
search_text("movies", "a moody sci-fi about androids and identity", k=2, rerank=True)
# → [ br (0.83), gits (0.79) ] Paddington is correctly far away
```

🔍 UNDER THE HOOD — THE SAME CALLS DRIVE AN AI AGENT

Those two verbs, `upsert_text` and `search_text`, are not just SDK methods — they are exposed as **MCP tools** (ADR-0058), so an autonomous agent can build and query this corpus with no embedding model of its own, in the same words a human would use. The agent calls the tool; Quiver embeds, searches, reranks, and returns the films. (More on the agent surface in §9.7.)

9.2 Full-text without leaving home: BM25

Meaning search is powerful, but sometimes you want the *exact word* — a product code, a name, an acronym a model has never seen. Quiver indexes text for classic keyword ranking too, with no extra dependency.

TWO KINDS OF RELEVANCE, FUSED

Dense (vector) search finds things that *mean* the same. **BM25** — the lexical workhorse behind Lucene/Elasticsearch — scores by *which rare words two texts share, and how often*. Quiver tokenises text (Unicode split, lowercase, stop-words, a **Snowball/Porter2 stemmer** so “running”, “ran”, and “runs” conflate), builds an inverted index, and scores with Okapi BM25. A single `query_text` can run dense, lexical, or — best of all — both, fused with RRF.

9.3 Backups that don't stop the world

Your data directory is already portable — stop the process and copy it. But you should not have to stop. An **online snapshot** captures a consistent copy of a *running* database, anchored at one point in its history.

FIG. 23 — THE ONLINE SNAPSHOT (CONSISTENT BACKUP)



FIG. 23 — Consistency comes from the checkpoint plus the single-writer lock; the copy itself never parses a segment, so it captures new artifacts for free. The crash gate is untouched.

9.4 Scaling reads: leader & followers

Quiver is single-node first, but reads can still fan out. Point a follower at a leader (`QUIVER_LEADER_URL`) and it bootstraps from a snapshot, then tails the leader's writes **asynchronously** — no consensus, no failover, no write coordination. Followers are read-only warm standbys that absorb query load; the leader stays the single writer, so durability and the crash gate are exactly as Part 5 describes.

FIG. 24 — ASYNCHRONOUS LEADER-FOLLOWER READ REPLICAS




FIG. 24 — A clearly-labelled stretch feature: read scale-out and warm standbys *without* the cost of consensus. Followers are eventually consistent; the leader is the one source of truth.

9.5 Seeing inside: metrics, tracing & OpenTelemetry

An operator needs to see the system breathe. Quiver serves a Prometheus `/metrics` endpoint (open, so a scraper needs no key) with real request counters and latency histograms per route, plus security counters; engine operations carry secret-free `tracing` spans, and an importable Grafana dashboard ships in the repo. New in v0.22.0, those spans can be **exported over OpenTelemetry** (ADR-0059): opt in behind the `otlp` build feature and a runtime endpoint (`QUIVER_OTLP_ENDPOINT`), and the existing spans stream over OTLP/gRPC to Jaeger, Tempo, or Grafana — off by default (a normal build links no extra dependency, and a failed exporter degrades to console logging rather than failing startup). The metrics below are also the vocabulary the rest of this guide measures in.

Table 17 – the metrics that matter, defined (with a worked example)

METRIC	IN PLAIN WORDS	WORKED EXAMPLE
recall@k	Of the <i>true</i> k nearest neighbours, what fraction did the (approximate) search actually return?	Ask for 10; 9 of the true top-10 come back → recall@10 = 0.90 .
QPS	Queries served per second — raw throughput.	30,000 searches in 20 s → 1,500 QPS .
p50 / p95 / p99	Tail latency: the time under which 50 / 95 / 99 % of requests finish. p99 is what your slowest users feel.	p95 = 8 ms means 95 of 100 queries answered within 8 ms.
RRF	Reciprocal Rank Fusion — merge two ranked lists using only ranks: score = $\sum 1/(k_o + \text{rank})$.	Rank 1 on the dense list + rank 3 on BM25 ($k_o=60$) → $1/61 + 1/63$.
IDF	Inverse Document Frequency — rare words carry more signal than common ones; the heart of BM25.	“the” appears everywhere → ~0 weight; “xylophone” is rare → high weight.
RSS	Resident Set Size — the physical RAM a process actually holds. The memory-frugality headline.	Disk path: ~1 GB resident for 10 M vectors vs ~31 GB fully in RAM.
build time	Wall-clock time to ingest a dataset and build its index — the “time to first query.”	One bulk load: one WAL fsync + one index pass, not N round trips.

9.6 Fairness under load: per-key rate limiting

THE TOKEN BUCKET

Each API key gets a bucket that refills at a steady rate up to a burst capacity; every request spends one token. Spend faster than the refill and the bucket empties — further requests get `429 Too Many Requests` with a `Retry-After` and the standard `RateLimit-*` headers. It is opt-in (off by default), enforced at one auth choke point so every REST and gRPC call is covered, and per-node in memory — a clustered limiter is a job for the distributed-mode design.

9.7 The client fleet: SDKs, agents, and the cockpit

One engine, many front doors. Beyond REST and gRPC, Quiver ships SDKs for **Python** (sync + async), **TypeScript**, and **Go** (standard-library only), each mirroring the same surface — collections, points, search, hybrid, full-text, server-side embedding, and snapshots. The three are kept at **method parity**: alongside the core calls, each carries the same bulk/maintenance helpers — batched upload (`upsertIter` / `UpsertBatch`), a `scroll` over a whole collection for export and re-embedding, and a paged `deleteByFilter` for GDPR erasure — with the TypeScript client taking a sync or async iterable and the Go client a context on every call. For AI agents, an **MCP server** exposes the database as tools — `create`, `upsert`, `search`, `hybrid`, `database_stats`, `delete_collection`, `snapshot`, and (v0.22.0) the text tools `upsert_text` / `search_text` — so an autonomous agent can not only query Quiver but *operate* it, in plain words.

The cockpit you can fly

The last front door is for humans. `quiver tui` opens a retro terminal **cockpit** in the Bronze Quiver palette — a live dashboard of connection health, a collections table with per-collection load bars, points-trend and ingest-rate sparklines, and a severity-tagged activity log. New in v0.22.0 (ADR-0060) it became *interactive*: press `/` to open a **query runner**, type a question, run a server-side embed-and-search, and inspect any result's payload in a side pane; `?` shows a keybinding overlay and `Ctrl-t` toggles a cool Slate theme. Pressing `v` on a collection opens the **constellation view** — a 2-D projection of the vector space you can pan and zoom to *see* how your data clusters. Every screen renders to a buffer behind a render-to-buffer API, so each is unit-tested with ratatui's `TestBackend` and the screenshots below are generated from the *real* render — they never go stale.



FIG. 25 – The cockpit: a live dashboard (top) and the interactive query runner (bottom) – a server-side `search_text` from the terminal, with ranked results, a payload inspector, and a recent-searches strip. Both are the *real* render, screenshotted from seeded demo data, never a mock-up.

9.8 Fitting into your stack: migration & integrations

You rarely start empty. Quiver ships **migration importers** that pull data straight from a *running* source — `quiver admin import --qdrant-url / --chroma-url / --postgres-url` stream collections from Qdrant, Chroma, and pgvector/Postgres with no manual export step (a file-based path covers the rest). Vectors, ids, and payloads come across together, so a switch is one command, not a project.

And because the SDKs mirror the common retrieval interfaces, Quiver drops into the popular RAG frameworks: it is usable as a **LangChain** and **LlamaIndex** vector store and a **Haystack** `DocumentStore`, so an existing pipeline can point at Quiver by swapping one component — keeping the security, frugality, and self-hosting it was built for.

9.9 Distribution: one binary, the `quiverdb-*` namespace

Everything above ships in **one static binary** — `quiver serve`, `quiver tui`, `quiver mcp`, and `quiver admin` are the same executable. For source and registry distribution, the crates publish under the `quiverdb-*` namespace (ADR-0056) — each package is `quiverdb-<crate>` while its library name stays `quiver-<crate>` and the binary stays `quiver`, so imports and `cargo install --path` are unchanged. A multi-stage Docker image, a docker-compose, and a Helm chart for Kubernetes round out the deploy story; secure defaults mean the server refuses to start on a non-loopback bind without a master key and TLS.

9.10 The roads not (yet) taken

Restraint is a feature. Two large capabilities are *designed* — written up as architecture records — but deliberately unbuilt until the single-node story is unbeatable and a real need appears: **distributed / sharded mode** (hash sharding + scatter-gather + per-shard Raft for write HA) and **GPU acceleration** (behind the index trait, CPU-default). A third — **concurrent reads** — is now *built end to end*: reads run in parallel behind a reader-writer lock (§5.3), rebuilds run off the exclusive lock (§5.4), and the fully **lock-free MVCC** read path (§5.5, ADR-0064) — an `arc-swap` snapshot plus a small overlay, so pure-vector reads never wait on the writer at all — ships **opt-in** (`QUIVER_MVCC_READS`), with the proven `RwLock` path the default until it is validated on dedicated hardware. Each began as a design ADR; none compromises the single static binary.

🔍 A DESIGN-ONLY WALKTHROUGH — SHARDING A CATALOGUE ACROSS THREE NODES

Suppose the movie catalogue grows past one node's RAM-at-recall budget. The ADR-0051 design (not built — sketched here so the shape is concrete) would hash each point's id into one of three **shards**, each an ordinary Quiver node that owns $\sim\frac{1}{3}$ of the vectors and builds its own index. A write routes to the owning shard. A query is a **scatter-gather**: the coordinator sends the query vector to all three shards in parallel, each returns its local top- k , and the coordinator merges the three lists by exact distance into a global top- k — the same approximate-then-re-rank shape as a single node, one level up. Write availability would come from a small **per-shard Raft** group (a leader plus replicas), so losing a node loses neither data nor writes. The reason it stays on paper: per-shard consensus is a multi-quarter commitment, and Quiver's rule is to be unbeatable at one node first — the off-lock rebuild of §5.4 is exactly the kind of intra-node win that buys time before reaching for distribution.

Glossary for the Newcomer

Every term this guide leans on, defined once, in plain language.

Vector / Embedding

A list of numbers representing the *meaning* of content.
Similar meanings → nearby numbers.

Embedding model

The neural network that turns text/images into vectors.
(You bring your own.)

Metric

How “distance” is measured: cosine (angle), L2 (ruler), dot product (angle + length).

ANN

Approximate Nearest Neighbour — finding the *almost*-perfect closest vectors fast.

Recall

Accuracy of approximate search: of the true top-K, how many were found. (1.0 = perfect.)

k / top-k

How many results you want (“the 10 most similar movies”).

Index

The data structure that makes search fast (HNSW, Vamana/DiskANN, IVF).

HNSW

A layered “navigable graph” index; fast, lives in RAM.

Vamana / DiskANN

A graph index engineered to live on SSD with a tiny RAM footprint.

IVF

An index that clusters vectors into cells and searches only the relevant ones.

Quantization

Lossy compression of vectors into tiny codes (Scalar ~4×, Product/Binary ~32×).

Re-ranking

After a fast fuzzy pass, recomputing exact distances on the shortlist.

WAL

Write-Ahead Log — the “write it down before doing it” log that survives crashes.

fsync

The command that forces data all the way onto physical disk.

AEAD

Encryption (e.g. XChaCha20-Poly1305) that also detects tampering.

Crypto-shredding

Deleting data permanently by destroying its (tiny) key.

RBAC

Role-Based Access Control: who may do what, to which data.

RRF

Reciprocal Rank Fusion — merging two ranked lists using only their ranks.

Payload / metadata

Structured data attached to a vector (`{"year":1982}`), used for filtering.

MCP

Model Context Protocol — lets AI agents call tools; Quiver exposes itself as such.

BM25

The classic keyword-ranking formula (Lucene/Elasticsearch): scores by which *rare* shared words two texts have, and how often.

IDF

Inverse Document Frequency — how rare (and therefore informative) a word is across the corpus.

Stemmer (Snowball/Porter2)

Reduces words to a root so “running”, “runs”, and “ran” match as one.

Rerank

A second, sharper pass (a cross-encoder) that reorders a retrieved shortlist for precision.

Embedding provider

An external model (OpenAI/Cohere/Ollama/HTTP) Quiver can call, at the edge, to turn your text into vectors.

Snapshot / checkpoint

An online, consistent backup of the whole database; the checkpoint seals memory to disk so the copy needs no replay.

Token bucket

A rate limiter: a bucket refills at a fixed rate; each request spends a token; empty → 429.

Prometheus / OpenTelemetry

Standard formats for metrics (scraped from /metrics) and traces (spans) — what dashboards and alerting consume.

recall@k

The fraction of the *true* k nearest neighbours an approximate search actually returns — search quality.

p95 / p99

Tail latency — the time under which 95 % / 99 % of requests complete; what slow users feel.

RSS

Resident Set Size — the physical RAM a process actually uses; Quiver’s memory-frugality headline.

RwLock (reader-writer lock)

A lock that lets many readers in at once but a writer alone — how Quiver runs searches in parallel.

Snapshot isolation / MVCC

A read sees one consistent version of the data; it may miss a just-committed write but never a half-applied one.

Off-lock rebuild

Rebuilding a stale index without holding the exclusive lock — the prior index is served while the new one is built, then swapped in.

Lock-free MVCC reads

Serving reads from an `arc-swap` snapshot (base index + a small overlay of recent writes) with no lock, so reads never block on the writer (§5.5, ADR-0064; opt-in via `QUIVER_MVCC_READS`).

Overlay

The small, immutable set of writes (recent vectors + tombstones) layered on a published base index so an MVCC read stays fresh without rebuilding the index.

Saturated throughput (NT)

QPS measured under many concurrent client threads, versus one (1T) — the test for whether parallel reads actually help.

Selectivity

The fraction of a collection a filter keeps; it decides whether the planner pre-filters (selective) or post-filters (broad).

recall@1 / recall@100

Recall measured at different depths — recall@100 needs a deeper search beam than recall@10.

Replication (leader-follower)

Asynchronous read replicas: a follower tails a leader’s writes to scale reads, with no consensus.

Sharding / scatter-gather

Splitting data across nodes (designed, not built); a query fans out to all shards and merges their results.

Cockpit (TUI)

The retro terminal interface (`quiver tui`): a live dashboard plus an interactive query runner.

OTLP

OpenTelemetry’s wire protocol for exporting traces to a collector (Jaeger/Tempo/Grafana); opt-in in Quiver.

ColBERT / MaxSim

Late-interaction retrieval: a document is many token vectors, ranked by summing each query token’s best match.

PQ / ADC

Product Quantization compresses vectors into codes; Asymmetric Distance Computation scores them with a per-query lookup table.

References & Repository Documentation

Every claim in this guide traces to source code or to a documented, reproducible benchmark. The primary sources live in the Quiver repository.

Architecture & overview

- R1 **Architecture overview & crate map**
docs/architecture/overview.md
- R2 **C4 container view** · C4 system context
docs/architecture/c4-container.md · c4-context.md
- R3 **Project README** — positioning, quickstart, benchmark tables
README.md

Indexes, kernels & quantization

- R4 **HNSW** (Malkov & Yashunin, 2020; arXiv:1603.09320)
crates/quiver-index/src/hnsw.rs · ADR-0007
- R5 **Vamana / DiskANN** (Subramanya et al., NeurIPS 2019)
crates/quiver-index/src/vamana.rs · disk.rs · ADR-0019
- R6 **IVF coarse Voronoi partitioning** · SpFresh/LIRE updates
crates/quiver-index/src/ivf.rs · ADR-0007 · ADR-0023
- R7 **Quantization** — scalar / product / binary
crates/quiver-index/src/quant/ · ADR-0008
- R8 **SIMD distance kernels** — runtime dispatch + scalar fallback
crates/quiver-simd/src/ · ADR-0009
- R9 **Hybrid (dense + sparse) search** · RRF fusion
crates/quiver-query/src/sparse.rs · ADR-0043
- R10 **Multi-vector / late-interaction** (ColBERT, MaxSim)
crates/quiver-index/src/colbert.rs · ADR-0028 · ADR-0034

Storage, durability & security

- R11 **Write-ahead log & page format** — CRC, recovery
crates/quiver-core/src/wal.rs · page.rs · ADR-0004 · ADR-0005
- R12 **Envelope encryption & crypto-shredding**
crates/quiver-crypto/src/envelope.rs · docs/security/crypto.md · ADR-0010

R13 **Encrypted vectors** — client-side & DCPE
docs/security/dcpe.md · client-side-vectors.md · ADR-0031 · ADR-0032

R14 **Auth, RBAC, tenancy & threat model**
docs/security/threat-model.md · ADR-0011 · ADR-0013

Benchmarks & method

R15 **Head-to-head comparison (v0.20.0)** — SIFT1M + GIST1M, 7 competitors
docs/benchmarks/results/comparison-v0.20.0/

R16 **v0.22.0 dimensions** — recall@{1,10,100}, saturated concurrency, quantization & filter sweeps
docs/benchmarks/results/comparison-v0.22.0/ · ADR-0061

R17 **Benchmark methodology & harness** · disk-path memory results · reference-hardware runbook
docs/benchmarks/methodology.md · bench/

Concurrency, operability & v0.22.0 features

R18 **Concurrent reads (RwLock) · off-lock index rebuild**
crates/quiver-server/src/lib.rs · ADR-0057 · ADR-0062

R19 **Interactive TUI cockpit · OTLP traces exporter · MCP text tools**
crates/quiver-tui · quiver-server · quiver-mcp · ADR-0060 · 0059 · 0058

R20 **Replication · packaging & the `quiverdb-*` namespace**
docs/security/threat-model.md · CHANGELOG.md · ADR-0056

Decisions & project

R21 **Architecture Decision Records (ADR-0001 ... ADR-0062)**
docs/adr/

R22 **Documentation site (mdBook)** — concepts → API → security → architecture
apps/docs/ · build with `just docs`

R23 **Security policy · roadmap · contributing**
SECURITY.md · docs/roadmap.md · CONTRIBUTING.md

Repository — github.com/achref-soua/quiver · License: AGPL-3.0-only · Edition v0.24.0 · All paths are relative to the repository root.



"A quiver holds arrows, and an arrow is a vector.
In mathematics a quiver is a directed graph –
which is exactly what an HNSW or Vamana index is."

```
quiver@cockpit:~$ ./read --status=complete ✓
```

The security-first vector database
Client-side-encryptable • memory-frugal • runs on a
laptop

github.com/achref-soua/quiver
Open-source • AGPL-3.0-only