

An introduction to the **reshape2** package

BISC 888–1 Simon Fraser University

Sean C. Anderson
`sean@seananderson.ca`

October 2, 2013

reshape2 is an R package written by Hadley Wickham that makes it easy to transform data between “wide” and “long” format. It is based around two key functions: **melt** and **cast**:

melt takes wide-format data and melts it into long-format data.

cast takes long-format data and casts it into wide-format data.

Think of working with metal: if you melt metal, it drips and becomes long. If you cast it into a mould, it becomes wide.

It turns out that you need wide-format data for some types of data analysis and long-format data for others. In reality, you need long-format data much more commonly than wide-format data. For example, **ggplot2** requires long-format data, **plyr** requires long-format data, and most modelling functions (such as **lm()**, **glm()**, and **gam()**) require long-format data. But people often find it easier to record their data in wide format.

1 What makes data wide or long?

Wide data has a column for each variable. For example, this is wide-format data:

```
> head(d)
```

	ozone	wind	temp
1	23.61538	11.622581	65.54839
2	29.44444	10.266667	79.10000
3	59.11538	8.941935	83.90323
4	59.96154	8.793548	83.96774

And this is long-format data:

```
> melt(d)
```

	variable	value
1	ozone	23.615385
2	ozone	29.444444
3	ozone	59.115385
4	ozone	59.961538
5	wind	11.622581
6	wind	10.266667
7	wind	8.941935
8	wind	8.793548
9	temp	65.548387
10	temp	79.100000
11	temp	83.903226
12	temp	83.967742

Long-format data has a column for possible variable types and a column for the values of those variables. Long-format data isn't necessarily only two columns. For example, we might have ozone measurements for each day of the year. In that case, we could have another column for day. In other words, there are different levels of "longness". The ultimate shape you want to get your data into will depend on what you are doing with it.

2 Wide- to long-format data: the melt function

For this example we'll work with the `airquality` dataset that is built into R. First we'll change the column names to lower case to make them easier to work with. Then we'll look at the data:

```
> names(airquality) <- tolower(names(airquality))
> head(airquality)
```

	ozone	solar.r	wind	temp	month	day
1	41	190	7.4	67	5	1
2	36	118	8.0	72	5	2
3	12	149	12.6	74	5	3
4	18	313	11.5	62	5	4
5	NA	NA	14.3	56	5	5
6	28	NA	14.9	66	5	6

What happens if we run the function `melt` with all the default argument values?

```
> aql <- melt(airquality) # [a]ir [q]uality [l]ong format
> head(aql)
```

	variable	value
1	ozone	41
2	ozone	36
3	ozone	12
4	ozone	18
5	ozone	NA
6	ozone	28

```
> tail(aql)
```

	variable	value
913	day	25
914	day	26
915	day	27

```

916      day    28
917      day    29
918      day    30

```

By default, `melt` has assumed that all columns with numeric values are variables with values. Often this is what you want. Maybe here we want to know the values of `ozone`, `solar.r`, `wind`, and `temp` for each `month` and `day`. We can do that with `melt` by telling it that we want `month` and `day` to be “ID variables”. ID variables are the variables that identify individual rows of data.

```

> aql <- melt(airquality, id.vars = c("month", "day"))
> head(aql)

```

	month	day	variable	value
1	5	1	ozone	41
2	5	2	ozone	36
3	5	3	ozone	12
4	5	4	ozone	18
5	5	5	ozone	NA
6	5	6	ozone	28

What if we wanted to control the column names in our long-format data? `melt` lets us set those too all in one step:

```

> aql <- melt(airquality, id.vars = c("month", "day"),
+   variable.name = "climate_variable", value.name = "climate_value")
> head(aql)

```

	month	day	climate_variable	climate_value
1	5	1	ozone	41
2	5	2	ozone	36
3	5	3	ozone	12
4	5	4	ozone	18
5	5	5	ozone	NA
6	5	6	ozone	28

That’s about all there is to `melt`!

3 Long- to wide-format data: the cast functions

Whereas going from wide- to long-format data is pretty straightforward, going from long- to wide-format data can take a bit more thought. It usually involves some head scratching and some trial and error for all but the simplest cases. Let's go through some examples.

In `reshape2` there are multiple `cast` functions. We're going to work with `dcast`, which returns a `data.frames`, which you will most commonly work with. (There is also `acast` to return a vector, matrix, or array.)

Let's take the long-format `airquality` data and `cast` it into some different wide formats. To start with, we'll recover the same format we started with and compare the two:

```
> aql <- melt(airquality, id.vars = c("month", "day"))
> aqw <- dcast(aql, month + day ~ variable) # [a]ir [q]uality [w]ide
> head(airquality)
```

	ozone	solar.r	wind	temp	month	day
1	41	190	7.4	67	5	1
2	36	118	8.0	72	5	2
3	12	149	12.6	74	5	3
4	18	313	11.5	62	5	4
5	NA	NA	14.3	56	5	5
6	28	NA	14.9	66	5	6

```
> head(aqw)
```

	month	day	ozone	solar.r	wind	temp
1	5	1	41	190	7.4	67
2	5	2	36	118	8.0	72
3	5	3	12	149	12.6	74
4	5	4	18	313	11.5	62
5	5	5	NA	NA	14.3	56
6	5	6	28	NA	14.9	66

So, besides re-arranging the columns, we've recovered our original data.

One “mistake” you might find yourself making is casting a data set in which there is more than one value per data cell. For example:

```
> dcast(aql, month ~ variable)
```

	month	ozone	solar.r	wind	temp
1	5	31	31	31	31
2	6	30	30	30	30
3	7	31	31	31	31
4	8	31	31	31	31
5	9	30	30	30	30

When you run this in R, you’ll notice the warning message:

Aggregation function missing: defaulting to length

And if you look at the output you got, the cells are filled with the number of data rows for each month-climate combination. When you `cast` your data and there are multiple values per cell, you also need to tell `dcast` how to aggregate the data. For example, maybe you want to take the `mean`, or the `median`, or the `sum`. Let’s try the last example, but this time we’ll take the mean of the climate values. We’ll also pass the option `na.rm = TRUE` through the `...` argument to remove NA values.

```
> dcast(aql, month ~ variable, fun.aggregate = mean, na.rm = TRUE)
```

	month	ozone	solar.r	wind	temp
1	5	23.61538	181.2963	11.622581	65.54839
2	6	29.44444	190.1667	10.266667	79.10000
3	7	59.11538	216.4839	8.941935	83.90323
4	8	59.96154	171.8571	8.793548	83.96774
5	9	31.44828	167.4333	10.180000	76.90000

Unlike `melt`, there are some other fancy things you can do with `dcast` that I’m not going to cover here. It’s well worth reading the help file `?dcast`. For example, you can compute summaries for rows and columns, subset the columns, and fill in missing cells in one call to `dcast`.

4 Additional help

Read the package help:

```
help(package = "reshape2")
```

See the `reshape2` website:

<http://had.co.nz/reshape/>

And read the paper on `reshape`:

Wickham, H. (2007). Reshaping data with the `reshape` package. 21(12):1–20.

<http://www.jstatsoft.org/v21/i12>

(But note that the paper is written for the `reshape` package not the `reshape2` package.)