OpenCore

Reference Manual (1.0~~.7~~.8)

[2026.05.03]

Copyright ©2018-2026 vit9696

AppleHDA kext will function correctly only if `TCSEL` register is configured to use `TC0` traffic class. Refer to Intel I/O Controller Hub 9 (ICH9) Family Datasheet (or any other ICH datasheet) for more details about this register.

Note: This option is independent from `AudioSupport`. If AppleALC is used it is preferred to use AppleALC `alctcsel` property instead.

11. `SetupDelay`
    Type: `plist integer`
    Failsafe: `0`
    Description: Audio codec reconfiguration delay in milliseconds.

    Some codecs require a vendor-specific delay after the reconfiguration (e.g. volume setting). This option makes it configurable. A typical delay can be up to 0.5 seconds.

11.16 Drivers Properties

1. `Arguments`
   Type: `plist string`
   Failsafe: Empty
   Description: Some OpenCore plugins accept optional additional arguments which may be specified as a string here.

2. `Comment`
   Type: `plist string`
   Failsafe: Empty
   Description: Arbitrary ASCII string used to provide human readable reference for the entry. Whether this value is used is implementation defined.

3. `Enabled`
   Type: `plist boolean`
   Failsafe: `false`
   Description: If `false` this driver entry will be ignored.

4. `HideVerbose`
   Type: `plist boolean`
   Failsafe: `false`
   Description: If `true` text output for this driver will be disabled.

5. `LoadEarly`
   Type: `plist boolean`
   Failsafe: `false`
   Description: Load the driver early in the OpenCore boot process, before NVRAM setup.

   Note: Do not enable this option unless specifically recommended to do so for a given driver and purpose.

6. `Path`
   Type: `plist string`
   Failsafe: Empty
   Description: Path of file to be loaded as a UEFI driver from `OC/Drivers` directory.

11.17 Input Properties

1. `KeyFiltering`
   Type: `plist boolean`
   Failsafe: `false`
   Description: Enable keyboard input sanity checking.

   Apparently some boards such as the GA Z77P-D3 may return uninitialised data in `EFI_INPUT_KEY` with all input protocols. This option discards keys that are neither ASCII, nor are defined in the UEFI specification (see tables 107 and 108 in version 2.8).

2. `KeyForgetThreshold`
   Type: `plist integer`