

# Model Documentation of the Stable $PT_n$ Element

This document was automatically generated based on the [ACKREP](#) project [system model with OV6ND](#). The Automatic Control Knowledge Repository, short ACKREP, aims to facilitate knowledge transfer of control theory and control engineering.

## 1 Nomenclature

### 1.1 Nomenclature for Model Equations

$K$  proportional factor  
 $T_1, T_2, \dots, T_n$  time constants

## 2 Model Equations

State Vector and Input Vector:

$$\underline{x} = (x_1 \ x_2 \ \dots \ x_n)^T$$
$$\underline{u} = u$$

Model Equations:

$$\dot{x}_1 = x_2 \tag{1a}$$

$$\dot{x}_2 = x_3 \tag{1b}$$

$$\vdots = \vdots \tag{1c}$$

$$\dot{x}_n = Ku - \mathcal{L}^{-1}(X(s) \prod_{i=1}^n (1 + T_i s)) \tag{1d}$$

Parameters:  $T_1, T_2, \dots, T_n$

Outputs: *(not defined)*

### 2.1 Assumptions

1. All Parameters have Real positive values

### 2.2 Exemplary parameter values

For a  $PT_2$  Element:

Parameter Name	Symbol	Value	Unit
Proportional Factor	$K$	3	
Time Constant 1	$T_1$	5	s
Time Constant 2	$T_2$	0.5	s

## 3 Derivation and Explanation

*Not available*

## References

- [1] Janschek, K.: *Mechatronic Systems Design*, p. 795, Springer-Verlag Berlin Heidelberg, 2012