Model Documentation of the Four-Bar Linkage

This document was automatically generated based on the ACKREP project system model with CK7EX. The Automatic Control Knowledge Repository, short ACKREP, aims to facilitate knowledge transfer of control theory and control engineering.

1 Nomenclature

1.1 Nomenclature for Model Equations

s_i	distance from the joint to the center of gravity of link i, where $i = 1, 2, 3$
m_i	mass of link i, where $i = 1, 2, 3$
J_i	moment of inertia of link i, where $i = 1, 2, 3$
l_i	length of (distance between joints) of link i, where $i = 1, 2, 3, 4$
g	acceleration due to gravity
p_1	angle between basis and link 1 (joint 1)
p_2	angle between link 1 and link 2 (joint 2)
q_1	angle between basis and link 3 (joint 4)
u_1	external torgue applied to joint 1
y	array of angles
$\dot{y}$	array of angular velocities

2 Model Equations

DAE Variables and Input Vector:

$$\underline{x} = (x_1\ x_2\ x_3\ \dot{x}_1\ \dot{x}_2\ \dot{x}_3\ \lambda_1\ \lambda_2)^T \qquad = (p_1\ p_2\ q_1\ \dot{p}_1\ \dot{p}_2\ \dot{q}_1\ \lambda_1\ \lambda_2)^T$$
$$\underline{u} = u_1$$

Constraints:

$$l_1 \cos(x_3) + l_2 \cos(x_1 + x_3) - l_3 \cos(x_2) - l_4 \tag{1a}$$
$$l_1 \sin(x_3) + l_2 \sin(x_1 + x_3) - l_3 \sin(x_2) \tag{1b}$$

System Equations:

$$0 = J_2\ddot{x}_1 + J_2\ddot{x}_3 + gm_2s_2\cos(x_1 + x_3) + l_1m_2\ddot{x}_3s_2\cos(x_1) + l_1m_2\dot{x}_3^2s_2\sin(x_1) + l_2\lambda_1\sin(x_1 + x_3) - l_2\lambda_2\cos(x_1 + x_3) + m_2\ddot{x}_1s_2^2 + m_2\ddot{x}_3s_2^2$$

$$0 = J_3\ddot{x}_2 + gm_3s_3\cos(x_2) - l_3\lambda_1\sin(x_2) + l_3\lambda_2\cos(x_2) + m_3\ddot{x}_2s_3^2$$

$$0 = J_1\ddot{x}_3 + J_2\ddot{x}_1 + J_2\ddot{x}_3 + gl_1m_2\cos(x_3) + gm_1s_1\cos(x_3) + gm_2s_2\cos(x_1 + x_3) + l_1^2m_2\ddot{x}_3 + l_1\lambda_1\sin(x_3) - l_1\lambda_2\cos(x_3) + l_1m_2\ddot{x}_1s_2\cos(x_1) - l_1m_2\dot{x}_1^2s_2\sin(x_1) - 2l_1m_2\dot{x}_1\dot{x}_3s_2\sin(x_1) + 2l_1m_2\ddot{x}_3s_2\cos(x_1) + l_2\lambda_1\sin(x_1 + x_3) - l2\lambda_2\cos(x_1 + x_3) + m_1\ddot{x}_3s_1^2 + m_2\ddot{x}_1s_2^2 + m_2\ddot{x}_3s_2^2 - u_1$$

Parameters: $s_1\ s_2\ s_3\ m_1\ m_2\ m_3\ J_1\ J_2\ J_3\ l_1\ l_2\ l_3\ l_4\ g$
Outputs: $y\ \dot{y}$

2.1 Exemplary parameter values

Parameter Name	Symbol	Value	Unit
distance from the joint to the center of gravity of link 1	s_1	0.5	m
distance from the joint to the center of gravity of link 2	s_2	0.5	m
distance from the joint to the center of gravity of link 3	s_3	0.5	m
mass of link 1	m_1	1	kg
mass of link 2	m_2	1	kg
mass of link 3	m_3	3	kg
moment of inertia of link 1	J_1	0.0833333333333333	$\frac{kg}{m^2}$
moment of inertia of link 2	J_2	0.0833333333333333	$\frac{kg}{m^2}$
moment of inertia of link 3	J_3	0.0833333333333333	$\frac{kg}{m^2}$
length of link 1	l_1	0.8	m
length of link 2	l_2	1.5	m
length of link 3	l_3	1.5	m
length of link 4	l_4	2	m
acceleration due to gravity	g	9.81	$\frac{m}{s^2}$

3 Derivation and Explanation

Not available

References

[1] Knoll, Carsten: *Considered model: four-bar linkage (= two link manipulator + one link manipulator + rigid coupling)*, Jupyter Notebook published 2019