

Model Documentation of the Flyback Converter

1 Nomenclature

1.1 Nomenclature for Model Equations

L	inductivity of the inductor
C	capacity of the capacitor
R	resistance of the load
U_E	input voltage
k	transmission ratio of the transformer
i_L	current through the inductor
u_C	voltage over the capacitor
d	duty ratio of the switch

1.2 Circuit Diagram




Figure 1: Circuit

2 Model Equations

State Vector and Input Vector:

$$\underline{x} = (x_1 \ x_2)^T = (i_L \ u_C)^T$$
$$\underline{u} = d$$

System Equations:

$$\dot{x}_1 = -(1 - u) \frac{k}{L} x_2 + \frac{U_E}{L} u \quad (1a)$$

$$\dot{x}_2 = (1 - u) \frac{k}{C} x_1 - \frac{1}{RC} x_2 \quad (1b)$$

Parameters: L, C, R, U_E, k

Outputs: $x_2 = u_C$

2.1 Exemplary parameter values

	Symbol	Value	Unit
Inductivity	L	0.00018	H
Capacity	C	$2.0 \cdot 10^{-5}$	F
Resistance	R	10	Ω
Input Voltage	U_E	24	V
Transmission Ratio	k	0.5	

3 Derivation and Explanation

See boost converter.

4 Simulation




Figure 2: Simulation of the flyback converter.

References

- [1] M. Salimi, J. Soltani, A. Zakipour, and V. Hajbani, Sliding mode control of the DC-DC flyback converter with zero steady-state error, in 4th Annual International Power Electronics, Drive Systems and Technologies Conference, Feb. 2013, pp. 158–163. doi: 10.1109/PEDSTC.2013.6506695.

- [2] K. Röbenack, Nichtlineare Regelungssysteme: Theorie und Anwendung der exakten Linearisierung. Berlin, Heidelberg: Springer Berlin Heidelberg, 2017. doi: 10.1007/978-3-662-44091-9.