

```
In [1]: using Pkg
Pkg.activate(joinpath("../", "environments", "modal-association-rules"))
Pkg.instantiate()
```

Activating project at `~/logic-and-machine-learning/environments/modal-association-rules`

```
In [2]: using Plots
using Random
using Statistics

Random.seed!(1605)
```

Out[2]: TaskLocalRNG()

```
In [3]: # this will be useful later, for loading the Natops dataset
function parse_natops(arffstring::String)
    df = DataFrame()
    classes = String[]

    lines = split(arffstring, "\n")
    for i in 1:length(lines)
        line = lines[i]

        # split the current line;
        # if it is not a data line, starting with DATA_MARK, continue;
        # continue even in the case where checking the first character th
        # out an error.
        sline = nothing
        try
            sline = split(line, " ")
            if sline[1][1] != '\'
                continue
            end
        catch
            continue
        end

        # skip the initial hypen an read the data
        sline[1] = sline[1][2:end]
        data_and_class = split(sline[1], "\'")
        string_data = split(data_and_class[1], "\\n")
        class = data_and_class[2][2:end]

        if isempty(names(df))
            for i in 1:length(string_data)
                insertcols!(df, Symbol("V$(i)") => Array{Float64, 1}[])
            end
        end

        float_data = Dict{Int,Vector{Float64}}{]()

        for i in 1:length(string_data)
            float_data[i] = map(x->parse(Float64,x), split(string_data[i]
        end

        push!(df, [float_data[i] for i in 1:length(string_data)])
        push!(classes, class)
```

```

end

p = sortperm(eachrow(df), by=x->classes[rownumber(x)])

return df[p, :], classes[p]
end

```

Out[3]: parse_natops (generic function with 1 method)

Modal Association Rules

In this notebook, we follow a different paradigm with respect to the supervised one we saw in [day04-learning-with-non-classical-logical](#).

The hypothesis here, is that a logical formula is *interesting*, if it happens to be frequently satisfied across all the instances of a dataset \mathcal{I} .

Given an alphabet \mathcal{P} of propositional literals, the formula we are dealing with are literal conjunctions called *itemsets*.

An itemset that is also frequent is called *frequent itemset*.

More formally, given a dataset \mathcal{I} , a propositional alphabet \mathcal{P} and a minimum threshold s , a frequent pattern $P \subseteq \mathcal{P}$ is such that:

$$\text{support}(\mathcal{I}, P) = \frac{|\{I \in \mathcal{I} \mid I \models P\}|}{|\mathcal{I}|} \geq s$$

The ratio above is called *support*.

In [4]: `using` ModalAssociationRules

In [5]: `# these are just three toy atoms`
`p = Atom(ScalarCondition(VariableMax(4), >=, 2)) |> Item`
`q = Atom(ScalarCondition(VariableMin(5), <=, 1.5)) |> Item`
`r = Atom(ScalarCondition(VariableMax(6), >=, 0.0)) |> Item`

Out[5]: `max[V6] ≥ 0.0`

In [6]: `# an Itemset encodes a conjunction of SoleLogics.Formula,`
`# but has two advantages:`

`# 1) performance considerations`
`# https://towardsdev.com/set-vs-vector-lookup-in-julia-a-closer-look-9d10`
`# 2) type piracy prevention!`

`pq = Itemset([p, q])`
`pr = Itemset([p, r])`
`qr = Itemset([q, r])`
`pqr = Itemset([p, q, r])`

```
Out[6]: 3-element Vector{Item}:
  max[V4] ≥ 2
  min[V5] ≤ 1.5
  max[V6] ≥ 0.0
```

```
In [7]: # an Itemset can wrap any SoleLogics.Formula type;
formula(pq)
```

```
Out[7]: LeftmostConjunctiveForm with 2 Atom grandchildren:
  max[V4] ≥ 2
  min[V5] ≤ 1.5
```

Exercise:

Define your own `mysupport` function.

Its argument must be of type `SoleLogics.Formula`,
`SoleData.AbstractLogiset` and `SoleLogics.AbstractWorld`.

We only want to consider the instances that were originally associated with the `I`
`have` command class.

We want to treat the Kripke model as a degenerate propositional logiset.

Then compute the support of the following itemsets: p , q , r , $p \wedge q$, $p \wedge r$,
 $r \wedge q$, $p \wedge q \wedge r$.

The support must be rounded to the second decimal digit.

Solution (Base64):

ZnVuY3Rpb24gbXlzdXBwb3J0KHBoaTo6RiwgWGs6OkwsIHdvcmxkOjpXKSB3aGVyZSB7C

```
In [8]: # Write your definition here
```

```
In [9]: try
  for phi in [p, q, r, pq, pr, qr, pqr]
    println(
      mysupport(
        formula(phi),
        SoleData.slicedataset(Xk, 1:30),
        Interval(1, X_ndatapoints)
      )
    )
  end
catch e
  if e isa UndefVarError
    println("You need to implement mysupport.")
  end
end
```

You need to implement `mysupport`.

Let us consider an alphabet of propositional literals \mathcal{P} , and let us suppose that
 $P \subseteq \mathcal{P}$ is a frequent pattern we found.

We can partition P in two smaller frequent patterns, Q, R , such that $Q \cap R = \emptyset$.

We denote with $Q \Rightarrow R$ the fact that an *interesting* statistical relation occurs between the antecedent and the consequent: if this is the case, then we have an *association rule*.

Similarly to the case of frequent patterns, the interestingness must be established with specific measures, which are called *meaningfulness measures* in the jargon.

```
In [10]: # beware of the difference between an Item (such as p) and an Itemset;
# we need to cast p to Itemset, even if it is a trivial 1-length Itemset.
println(typeof(p))
ARule(Itemset(p), qr)
```

```
Item{Atom{ScalarCondition{Int64, VariableMax{Int64}, ScalarMetaCondition{VariableMax{Int64}, typeof(>=)}}}}
```

```
Out[10]: max[V4] ≥ 2 => (min[V5] ≤ 1.5) ∧ (max[V6] ≥ 0.0)
```

```
In [11]: try
          ARule(pq, qr)
        catch e
          if e isa ArgumentError
            println("Beware: pq n qr is not empty.")
          end
        end
```

Beware: pq n qr is not empty.

```
In [12]: rule = ARule(Itemset(p), qr)
```

```
Out[12]: max[V4] ≥ 2 => (min[V5] ≤ 1.5) ∧ (max[V6] ≥ 0.0)
```

```
In [13]: ModalAssociationRules.ancestor(rule)
```

```
Out[13]: 1-element Vector{Item{Atom{ScalarCondition{Int64, VariableMax{Int64}, ScalarMetaCondition{VariableMax{Int64}, typeof(>=)}}}}}:
max[V4] ≥ 2
```

```
In [14]: ModalAssociationRules.consequent(rule)
```

```
Out[14]: 2-element Vector{Item}:
min[V5] ≤ 1.5
max[V6] ≥ 0.0
```

```
In [15]: # get the generator Itemset back
Itemset(rule)
```

```
Out[15]: 3-element Vector{Item}:
max[V4] ≥ 2
min[V5] ≤ 1.5
max[V6] ≥ 0.0
```

Quiz

Try to explain the ratio below, which is commonly called *confidence*.

$$\text{confidence}(\mathcal{I}, P \Rightarrow Q) = \frac{\text{support}(\mathcal{I}, P \cap Q)}{\text{support}(\mathcal{I}, P)}$$

Exercise

Implement your own `myconfidence` function.

Solution (Base 64):

ZnVuY3Rpb24gbXljb25maWRlbnNlKHJ1bGU6OkFSdWxILCBYazo6TCwgd29ybGQ6OlcpIf

```
In [16]: # Insert your solution here
```

```
In [17]: try
          for phi in [p, q, r, pq, pr, qr, pqr]
            println(
              myconfidence(
                rule,
                SoleData.slicedataset(Xk, 1:30),
                Interval(1, X_ndatapoints)
              )
            )
          end
        catch e
          if e isa UndefVarError
            println("You need to implement myconfidence.")
          end
        end
```

You need to implement `myconfidence`.

Enhancing Modal Association Rules with Modalities

When dealing with Kripke models, a natural dichotomy pops up!

Let us consider an alphabet of modal literals $\Lambda_{\mathcal{P}}$, obtained by enriching a standard, propositional alphabet \mathcal{P} with modal operators.

Let us also consider a modal dataset \mathcal{I} and an instance $I = (W, R, v) \in \mathcal{I}$ in it, as well as a pattern P .

We can assess the interestingness of P within an instance by computing its *local support*, and comparing it with respect to a *minimum local support threshold* s_l .

$$\text{lsupport}(I, P) = \frac{|\{w \in W \mid I, w \models P\}|}{|W|}$$

The other part of the dichotomy, that is, the notion of *global support*, is left as an exercise (see the Quiz below).

```
In [18]: lsupport
```

```
Out[18]: lsupport (generic function with 1 method)
```

```
In [19]: gsupport
```

```
Out[19]: gsupport (generic function with 1 method)
```

```
In [20]: lconfidence
```

Out[20]: lconfidence (generic function with 1 method)

In [21]: gconfidence

Out[21]: gconfidence (generic function with 1 method)

Quiz

How would you aggregate many local support computations, to compute a *global* support?

Mining Association Rules from Time Series Items

We want to probe our instances with considerations on the shape of the signal in a certain interval, for a given feature.

We also want to increase the expressiveness of the result association rules with the help of HS logic.

In [22]: `X, y = read(
 joinpath(@__DIR__, "..", "datasets", "natops.arff"), String) |> parse`

Out[22]: (360×24 DataFrame

Row	V1	V2
V ...	Array...	Array...
A ...		
1	[-0.519771, -0.52758, -0.531415, ...	[-2.14011, -2.18043, -2.18425,
...	[...	
2	[-0.489753, -0.48607, -0.484529, ...	[-1.55293, -1.54966, -1.55206,
...	[
3	[-0.521346, -0.518394, -0.522321...	[-1.72326, -1.72407, -1.72326,
...	[
4	[-0.57022, -0.562064, -0.565967, ...	[-1.91196, -1.90369, -1.90527,
...	[
5	[-0.624417, -0.626031, -0.625388...	[-1.84287, -1.84026, -1.84688,
...	[...	
6	[-0.502501, -0.502525, -0.499415...	[-2.17556, -2.15613, -2.18516,
...	[
7	[-0.488461, -0.489463, -0.487539...	[-2.17242, -2.18203, -2.18057,
...	[
8	[-0.468105, -0.410602, -0.473909...	[-1.86535, -1.89011, -1.87105,
...	[
9	[-0.568195, -0.572936, -0.571337...	[-1.79059, -1.78162, -1.78303,
...	[...	
10	[-0.517579, -0.515374, -0.517325...	[-1.73887, -1.74072, -1.7397,
-1...	[
11	[-0.631494, -0.629032, -0.630474...	[-1.98071, -1.98581, -1.98407,
...	[
:	:	:
...		
351	[-0.937442, -1.02995, -0.985338, ...	[-2.10495, -1.96835, -1.95082,
...	[
352	[-0.595625, -0.593605, -0.588495...	[-1.93897, -1.93641, -1.93761,
...	[...	
353	[-0.466582, -0.469372, -0.43454, ...	[-1.71874, -1.72861, -1.58691,
...	[
354	[-0.500404, -0.502824, -0.504771...	[-1.89209, -1.88986, -1.89188,
...	[
355	[-0.686893, -0.690966, -0.710514...	[-2.04375, -2.05011, -2.07035,
...	[
356	[-0.525938, -0.516073, -0.5177, ...	[-1.69259, -1.70519, -1.70824,
...	[...	
357	[-0.440887, -0.452221, -0.447185...	[-1.90444, -1.91917, -1.91652,
...	[
358	[-0.647672, -0.653511, -0.642305...	[-1.6173, -1.61051, -1.60491,
-1...	[
359	[-0.476117, -0.4705, -0.474443, ...	[-1.70846, -1.7099, -1.70912,
-1...	[
360	[-0.553245, -0.551704, -0.548044...	[-1.69493, -1.69349, -1.69951,
...	[...	

22 columns and 339 rows omitted, ["1.0", "1.0", "1.0", "1.0", "1.0", "1.0", "1.0", "1.0", "1.0", "1.0" ... "6.0", "6.0", "6.0", "6.0", "6.0", "6.0", "6.0", "6.0", "6.0", "6.0"])

```
In [23]: function _normalize(x::Vector{R}) where {R <: Real}
          eps = 1e-10
          return (x .- mean(x)) ./ (std(x) + eps)
end
```

```

function zeuclidean(x::Vector{R}, y::Vector{R}) where {R}
    # normalize x and y
    meanx = mean(x)
    meany = mean(y)

    # avoid division by zero
    eps = 1e-10

    x_z = _normalize(x)
    y_z = _normalize(y)

    # z-normalized euclidean distance formula
    return sqrt(sum((x_z .- y_z).^2))
end

```

Out[23]: zeuclidean (generic function with 1 method)

```

In [24]: # consider only right hand and right elbow
varids = vcat(collect(4:6), collect(10:12));

```

```

In [25]: mar_res_path = joinpath(@__DIR__, "..", "other-resources", "natops-for-ma

```

Out[25]: "/home/alberto-paparella/logic-and-machine-learning/notebooks/./other-resources/natops-for-mar"

```

In [26]: using Serialization

```

```

function load_motifs(filepath, save_filename_prefix)
    ids = [
        id for id in deserialize(
            joinpath(filepath, "$(save_filename_prefix)-ids")
        )
    ];
    motifs = [
        m for m in deserialize(
            joinpath(filepath, "$(save_filename_prefix)-motifs")
        )
    ];
    featurenames = [
        f for f in deserialize(
            joinpath(filepath, "$(save_filename_prefix)-featurenames")
        )
    ];
    return ids, motifs, featurenames
end

```

```

ids, motifs, featurenames = load_motifs(mar_res_path, "NATOPS-IHCC");

```


In this example, we only consider intervals of length 10 and 20.

In particular, given a world encoding an interval of such length, we compute the (normalized) euclidean distance between it and a pool of particular time series, called "motifs".

If the distance is low enough, then it means that the gesture encoded by the motif is happening.

Try to browse the motifs we are playing with, by tweaking the plot below.

```
In [27]: i = 1
plot(motifs[i], label = "V$(ids[i]) $(featurenames[i])")
```



```
In [28]: _variables = [
    SoleData.VariableDistance(id, m, distance=zeuclidean, featurename=name)
    for (id, m, name) in zip(ids, motifs, featurenames)
]

syntaxstring.(_variables)[1:3]
```

Out[28]: 3-element Vector{String}:
"left[V4]"
"right[V4]"
"inv_left[V4]"

```
In [29]: # we only consider the instances related to the "I have command" class;
# we are not cheating: we just want to describe the instances
IHCC = reduce(vcat, [X[1:30, :], X[(180+1):(180+30), :]]);
IHCCk = scalarlogiset(IHCC, _variables)
```

Out[29]: SupportedLogiset with 1 support (50.02 MBs)

- | worldtype: Interval{Int64}
- | featvaltype: Float64
- | featuretype: VariableDistance{Int64, Vector{Float64}}
- | frametype: FullDimensionalFrame{1, Interval{Int64}}
- | # instances: 60
- | usesfullmemo: true
- | [BASE] UniformFullDimensionalLogiset of channel size (51,) (50.02 MBs)
 - | | size × eltype: (51, 51, 60, 42) × Float64
 - | | features: 42 -> VariableDistance{Int64, Vector{Float64}}[left[V4], right[V4], inv_left[V4], pause_right[V4], ..., pause_front[V12], front_pause[V12], longfront[V12], longbehind[V12], pause_slightlybehind_front[V12]]
- | [SUPPORT 1] FullMemoset (0 memoized values, 5.25 KBs))

```
In [30]: propositionalatoms = [
  Atom(ScalarCondition(v, <=, 1.0))
  for v in _variables
]

syntaxstring.(propositionalatoms)[1:3]
```

```
Out[30]: 3-element Vector{String}:
 "left[V4] ≤ 1.0"
 "right[V4] ≤ 1.0"
 "inv_left[V4] ≤ 1.0"
```

```
In [31]: atoms = Vector{Item}(
  reduce(vcat, [
    propositionalatoms,
    diamond(IA_A).(propositionalatoms),
    diamond(IA_B).(propositionalatoms),
    diamond(IA_E).(propositionalatoms),
    diamond(IA_D).(propositionalatoms),
    diamond(IA_0).(propositionalatoms),
  ])
)

syntaxstring.(atoms)[1:3]
```

```
Out[31]: 3-element Vector{String}:
 "left[V4] ≤ 1.0"
 "right[V4] ≤ 1.0"
 "inv_left[V4] ≤ 1.0"
```

```
In [32]: _items = Vector{Item}(atoms);
```

```
In [33]: miner = Miner(
  # the data from which we want to find all the frequent itemsets
  IHCCk,

  # the strategy we want to leverage for exploring the frequent itemset
  apriori,

  # the initial alphabet of facts
  _items,

  # the interestingness measures for the frequent itemsets
  [(gsupport, 0.1, 0.1)],

  # the meaningfulness measures for the association rules
  [(gconfidence, 0.5, 0.5)];

  worldfilter=SoleLogics.FunctionalWorldFilter(
    x -> (length(x) == 10) || (length(x) == 20), Interval{Int}
  ),

  itemset_policies=Function[
    isanchored_itemset(ignoreuntillength=1),
    isdimensionally_coherent_itemset()
  ],

  arule_policies=Function[
    islimited_length_arule(consequent_maxlength=3),
    isanchored_arule()
  ]
)
```

) 1

```

Out[33]: SupportedLogiset with 1 support (50.02 MBs)
| worldtype:          Interval{Int64}
| featvaltype:        Float64
| featuretype:        VariableDistance{Int64, Vector{Float64}}
| frametype:          FullDimensionalFrame{1, Interval{Int64}}
| # instances:        60
| usesfullmemo:       true
| [BASE] UniformFullDimensionalLogiset of channel size (51,) (50.02 MBs)
| | size × eltype:      (51, 51, 60, 42) × Float64
| | features:          42 -> VariableDistance{Int64, Vector{Flo
at64}}[left[V4], right[V4], inv_left[V4], pause_right[V4], ..., pause_fr
ont[V12], front_pause[V12], longfront[V12], longbehind[V12], pause_sligh
tlybehind_front[V12]]
| [SUPPORT 1] FullMemoset (0 memoized values, 5.25 KBs))

```

Alphabet: [left[V4] ≤ 1.0, right[V4] ≤ 1.0, inv_left[V4] ≤ 1.0, pause_right[V4] ≤ 1.0, inv_left_inv[V4] ≤ 1.0, pause_right_inv[V4] ≤ 1.0, left_inv_right[V4] ≤ 1.0, down[V5] ≤ 1.0, up[V5] ≤ 1.0, down_pause[V5] ≤ 1.0, pause_up[V5] ≤ 1.0, longdown_pause[V5] ≤ 1.0, longup[V5] ≤ 1.0, longpause_up[V5] ≤ 1.0, front[V6] ≤ 1.0, behind[V6] ≤ 1.0, behind_pause[V6] ≤ 1.0, front_pause[V6] ≤ 1.0, longbehind[V6] ≤ 1.0, longfront[V6] ≤ 1.0, front_inv[V6] ≤ 1.0, littleleft[V10] ≤ 1.0, right[V10] ≤ 1.0, inv_left[V10] ≤ 1.0, right_pause[V10] ≤ 1.0, left[V10] ≤ 1.0, pause_right[V10] ≤ 1.0, right_pause[V10] ≤ 1.0, up[V11] ≤ 1.0, down[V11] ≤ 1.0, pause_up[V11] ≤ 1.0, pause_down[V11] ≤ 1.0, longdown[V11] ≤ 1.0, longup[V11] ≤ 1.0, inv_longdown[V11] ≤ 1.0, behind[V12] ≤ 1.0, front[V12] ≤ 1.0, pause_front[V12] ≤ 1.0, front_pause[V12] ≤ 1.0, longfront[V12] ≤ 1.0, longbehind[V12] ≤ 1.0, pause_slightlybehind_front[V12] ≤ 1.0, (A)left[V4] ≤ 1.0, (A)right[V4] ≤ 1.0, (A)inv_left[V4] ≤ 1.0, (A)pause_right[V4] ≤ 1.0, (A)inv_left_inv[V4] ≤ 1.0, (A)pause_right_inv[V4] ≤ 1.0, (A)left_inv_right[V4] ≤ 1.0, (A)down[V5] ≤ 1.0, (A)up[V5] ≤ 1.0, (A)down_pause[V5] ≤ 1.0, (A)pause_up[V5] ≤ 1.0, (A)longdown_pause[V5] ≤ 1.0, (A)longup[V5] ≤ 1.0, (A)longpause_up[V5] ≤ 1.0, (A)front[V6] ≤ 1.0, (A)behind[V6] ≤ 1.0, (A)behind_pause[V6] ≤ 1.0, (A)front_pause[V6] ≤ 1.0, (A)longbehind[V6] ≤ 1.0, (A)longfront[V6] ≤ 1.0, (A)front_inv[V6] ≤ 1.0, (A)littleleft[V10] ≤ 1.0, (A)right[V10] ≤ 1.0, (A)inv_left[V10] ≤ 1.0, (A)right_pause[V10] ≤ 1.0, (A)left[V10] ≤ 1.0, (A)pause_right[V10] ≤ 1.0, (A)right_pause[V10] ≤ 1.0, (A)up[V11] ≤ 1.0, (A)down[V11] ≤ 1.0, (A)pause_up[V11] ≤ 1.0, (A)pause_down[V11] ≤ 1.0, (A)longdown[V11] ≤ 1.0, (A)longup[V11] ≤ 1.0, (A)inv_longdown[V11] ≤ 1.0, (A)behind[V12] ≤ 1.0, (A)front[V12] ≤ 1.0, (A)pause_front[V12] ≤ 1.0, (A)front_pause[V12] ≤ 1.0, (A)longfront[V12] ≤ 1.0, (A)longbehind[V12] ≤ 1.0, (A)pause_slightlybehind_front[V12] ≤ 1.0, (B)left[V4] ≤ 1.0, (B)right[V4] ≤ 1.0, (B)inv_left[V4] ≤ 1.0, (B)pause_right[V4] ≤ 1.0, (B)inv_left_inv[V4] ≤ 1.0, (B)pause_right_inv[V4] ≤ 1.0, (B)left_inv_right[V4] ≤ 1.0, (B)down[V5] ≤ 1.0, (B)up[V5] ≤ 1.0, (B)down_pause[V5] ≤ 1.0, (B)pause_up[V5] ≤ 1.0, (B)longdown_pause[V5] ≤ 1.0, (B)longup[V5] ≤ 1.0, (B)longpause_up[V5] ≤ 1.0, (B)front[V6] ≤ 1.0, (B)behind[V6] ≤ 1.0, (B)behind_pause[V6] ≤ 1.0, (B)front_pause[V6] ≤ 1.0, (B)longbehind[V6] ≤ 1.0, (B)longfront[V6] ≤ 1.0, (B)front_inv[V6] ≤ 1.0, (B)littleleft[V10] ≤ 1.0, (B)right[V10] ≤ 1.0, (B)inv_left[V10] ≤ 1.0, (B)right_pause[V10] ≤ 1.0, (B)left[V10] ≤ 1.0, (B)pause_right[V10] ≤ 1.0, (B)right_pause[V10] ≤ 1.0, (B)up[V11] ≤ 1.0, (B)down[V11] ≤ 1.0, (B)pause_up[V11] ≤ 1.0, (B)pause_down[V11] ≤ 1.0, (B)longdown[V11] ≤ 1.0, (B)longup[V11] ≤ 1.0, (B)inv_longdown[V11] ≤ 1.0, (B)behind[V12] ≤ 1.0, (B)front[V12] ≤ 1.0, (B)pause_front[V12] ≤ 1.0, (B)front_pause[V12] ≤ 1.0, (B)longfront[V12] ≤ 1.0, (B)longbehind[V12] ≤ 1.0, (B)pause_slightlybehind_front[V12] ≤ 1.0, (E)left[V4] ≤ 1.0, (E)right[V4] ≤ 1.0, (E)inv_left[V4] ≤ 1.0, (E)pause_right[V4] ≤ 1.0, (E)inv_left_inv[V4] ≤ 1.0, (E)pause_right_inv[V4] ≤ 1.0, (E)left_inv_right[V4] ≤ 1.0, (E)down[V5] ≤ 1.0, (E)up[V5] ≤ 1.0, (E)down_pause[V5] ≤ 1.0, (E)pause_up[V5] ≤ 1.0, (E)longdown_pa

```

use[V5] ≤ 1.0, (E)longup[V5] ≤ 1.0, (E)longpause_up[V5] ≤ 1.0, (E)front
[V6] ≤ 1.0, (E)behind[V6] ≤ 1.0, (E)behind_pause[V6] ≤ 1.0, (E)front_pau
se[V6] ≤ 1.0, (E)longbehind[V6] ≤ 1.0, (E)longfront[V6] ≤ 1.0, (E)front_
inv[V6] ≤ 1.0, (E)littleleft[V10] ≤ 1.0, (E)right[V10] ≤ 1.0, (E)inv_lef
t[V10] ≤ 1.0, (E)right_pause[V10] ≤ 1.0, (E)left[V10] ≤ 1.0, (E)pause_r
ight[V10] ≤ 1.0, (E)right_pause[V10] ≤ 1.0, (E)up[V11] ≤ 1.0, (E)down[V1
1] ≤ 1.0, (E)pause_up[V11] ≤ 1.0, (E)pause_down[V11] ≤ 1.0, (E)longdown
[V11] ≤ 1.0, (E)longup[V11] ≤ 1.0, (E)inv_longdown[V11] ≤ 1.0, (E)behind
[V12] ≤ 1.0, (E)front[V12] ≤ 1.0, (E)pause_front[V12] ≤ 1.0, (E)front_pa
use[V12] ≤ 1.0, (E)longfront[V12] ≤ 1.0, (E)longbehind[V12] ≤ 1.0, (E)pa
use_slightlybehind_front[V12] ≤ 1.0, (D)left[V4] ≤ 1.0, (D)right[V4] ≤ 1
.0, (D)inv_left[V4] ≤ 1.0, (D)pause_right[V4] ≤ 1.0, (D)inv_left_inv[V4]
≤ 1.0, (D)pause_right_inv[V4] ≤ 1.0, (D)left_inv_right[V4] ≤ 1.0, (D)dow
n[V5] ≤ 1.0, (D)up[V5] ≤ 1.0, (D)down_pause[V5] ≤ 1.0, (D)pause_up[V5] ≤
1.0, (D)longdown_pause[V5] ≤ 1.0, (D)longup[V5] ≤ 1.0, (D)longpause_up[V
5] ≤ 1.0, (D)front[V6] ≤ 1.0, (D)behind[V6] ≤ 1.0, (D)behind_pause[V6] ≤
1.0, (D)front_pause[V6] ≤ 1.0, (D)longbehind[V6] ≤ 1.0, (D)longfront[V6]
≤ 1.0, (D)front_inv[V6] ≤ 1.0, (D)littleleft[V10] ≤ 1.0, (D)right[V10] ≤
1.0, (D)inv_left[V10] ≤ 1.0, (D)right_pause[V10] ≤ 1.0, (D)left[V10] ≤ 1
.0, (D)pause_right[V10] ≤ 1.0, (D)right_pause[V10] ≤ 1.0, (D)up[V11] ≤ 1
.0, (D)down[V11] ≤ 1.0, (D)pause_up[V11] ≤ 1.0, (D)pause_down[V11] ≤ 1.0
, (D)longdown[V11] ≤ 1.0, (D)longup[V11] ≤ 1.0, (D)inv_longdown[V11] ≤ 1
.0, (D)behind[V12] ≤ 1.0, (D)front[V12] ≤ 1.0, (D)pause_front[V12] ≤ 1.0
, (D)front_pause[V12] ≤ 1.0, (D)longfront[V12] ≤ 1.0, (D)longbehind[V12]
≤ 1.0, (D)pause_slightlybehind_front[V12] ≤ 1.0, (O)left[V4] ≤ 1.0, (O)r
ight[V4] ≤ 1.0, (O)inv_left[V4] ≤ 1.0, (O)pause_right[V4] ≤ 1.0, (O)inv_
left_inv[V4] ≤ 1.0, (O)pause_right_inv[V4] ≤ 1.0, (O)left_inv_right[V4]
≤ 1.0, (O)down[V5] ≤ 1.0, (O)up[V5] ≤ 1.0, (O)down_pause[V5] ≤ 1.0, (O)p
ause_up[V5] ≤ 1.0, (O)longdown_pause[V5] ≤ 1.0, (O)longup[V5] ≤ 1.0, (O)
longpause_up[V5] ≤ 1.0, (O)front[V6] ≤ 1.0, (O)behind[V6] ≤ 1.0, (O)behi
nd_pause[V6] ≤ 1.0, (O)front_pause[V6] ≤ 1.0, (O)longbehind[V6] ≤ 1.0,
(O)longfront[V6] ≤ 1.0, (O)front_inv[V6] ≤ 1.0, (O)littleleft[V10] ≤ 1.0
, (O)right[V10] ≤ 1.0, (O)inv_left[V10] ≤ 1.0, (O)right_pause[V10] ≤ 1.0
, (O)left[V10] ≤ 1.0, (O)pause_right[V10] ≤ 1.0, (O)right_pause[V10] ≤ 1
.0, (O)up[V11] ≤ 1.0, (O)down[V11] ≤ 1.0, (O)pause_up[V11] ≤ 1.0, (O)pau
se_down[V11] ≤ 1.0, (O)longdown[V11] ≤ 1.0, (O)longup[V11] ≤ 1.0, (O)inv
_longdown[V11] ≤ 1.0, (O)behind[V12] ≤ 1.0, (O)front[V12] ≤ 1.0, (O)pau
se_front[V12] ≤ 1.0, (O)front_pause[V12] ≤ 1.0, (O)longfront[V12] ≤ 1.0,
(O)longbehind[V12] ≤ 1.0, (O)pause_slightlybehind_front[V12] ≤ 1.0]

```

Items measures: [(ModalAssociationRules.gsupport, 0.1, 0.1)]

Rules measures: [(ModalAssociationRules.gconfidence, 0.5, 0.5)]

of frequent patterns mined: 0

of association rules mined: 0

Local measures memoization structure entries: 0

Global measures memoization structure entries: 0

Additional infos: [:size, :istrained]

Specialization fields: Symbol[]

In [34]: mine!(miner)

```

Out[34]: 74-element Vector{ARule}:
  right[V4] ≤ 1.0 => {0}inv_left[V4] ≤ 1.0
  down[V5] ≤ 1.0 => {0}down_pause[V5] ≤ 1.0
  down[V5] ≤ 1.0 => {0}littleleft[V10] ≤ 1.0
  up[V5] ≤ 1.0 => {0}up[V5] ≤ 1.0
  up[V5] ≤ 1.0 => {0}littleleft[V10] ≤ 1.0
  up[V5] ≤ 1.0 => {0}up[V11] ≤ 1.0
  pause_up[V5] ≤ 1.0 => {0}inv_left[V4] ≤ 1.0
  pause_up[V5] ≤ 1.0 => {0}up[V5] ≤ 1.0
  pause_up[V5] ≤ 1.0 => {0}front[V6] ≤ 1.0
  pause_up[V5] ≤ 1.0 => {0}right_pause[V10] ≤ 1.0
  pause_up[V5] ≤ 1.0 => {0}up[V11] ≤ 1.0
  pause_up[V5] ≤ 1.0 => {0}pause_up[V11] ≤ 1.0
  longdown_pause[V5] ≤ 1.0 => {D}inv_left[V4] ≤ 1.0
  :
  longup[V11] ≤ 1.0 => {0}pause_down[V11] ≤ 1.0
  longup[V11] ≤ 1.0 => {0}longup[V11] ≤ 1.0
  longup[V11] ≤ 1.0 => {0}inv_longdown[V11] ≤ 1.0
  behind[V12] ≤ 1.0 => {0}littleleft[V10] ≤ 1.0
  front_pause[V12] ≤ 1.0 => {0}down[V5] ≤ 1.0
  front_pause[V12] ≤ 1.0 => {0}down_pause[V5] ≤ 1.0
  front_pause[V12] ≤ 1.0 => {0}behind[V6] ≤ 1.0
  front_pause[V12] ≤ 1.0 => {0}front_pause[V6] ≤ 1.0
  front_pause[V12] ≤ 1.0 => {0}inv_left[V10] ≤ 1.0
  front_pause[V12] ≤ 1.0 => {0}down[V11] ≤ 1.0
  front_pause[V12] ≤ 1.0 => {0}pause_down[V11] ≤ 1.0
  longfront[V12] ≤ 1.0 => {D}front[V12] ≤ 1.0

```

```
In [35]: length(freqitems(miner))
```

```
Out[35]: 370
```

```
In [36]: length(arules(miner))
```

```
Out[36]: 74
```

```
In [37]: arules(miner)
```

```

Out[37]: 74-element Vector{ARule}:
right[V4] ≤ 1.0 => {0}inv_left[V4] ≤ 1.0
down[V5] ≤ 1.0 => {0}down_pause[V5] ≤ 1.0
down[V5] ≤ 1.0 => {0}littleleft[V10] ≤ 1.0
up[V5] ≤ 1.0 => {0}up[V5] ≤ 1.0
up[V5] ≤ 1.0 => {0}littleleft[V10] ≤ 1.0
up[V5] ≤ 1.0 => {0}up[V11] ≤ 1.0
pause_up[V5] ≤ 1.0 => {0}inv_left[V4] ≤ 1.0
pause_up[V5] ≤ 1.0 => {0}up[V5] ≤ 1.0
pause_up[V5] ≤ 1.0 => {0}front[V6] ≤ 1.0
pause_up[V5] ≤ 1.0 => {0}right_pause[V10] ≤ 1.0
pause_up[V5] ≤ 1.0 => {0}up[V11] ≤ 1.0
pause_up[V5] ≤ 1.0 => {0}pause_up[V11] ≤ 1.0
longdown_pause[V5] ≤ 1.0 => {D}inv_left[V4] ≤ 1.0
:
longup[V11] ≤ 1.0 => {0}pause_down[V11] ≤ 1.0
longup[V11] ≤ 1.0 => {0}longup[V11] ≤ 1.0
longup[V11] ≤ 1.0 => {0}inv_longdown[V11] ≤ 1.0
behind[V12] ≤ 1.0 => {0}littleleft[V10] ≤ 1.0
front_pause[V12] ≤ 1.0 => {0}down[V5] ≤ 1.0
front_pause[V12] ≤ 1.0 => {0}down_pause[V5] ≤ 1.0
front_pause[V12] ≤ 1.0 => {0}behind[V6] ≤ 1.0
front_pause[V12] ≤ 1.0 => {0}front_pause[V6] ≤ 1.0
front_pause[V12] ≤ 1.0 => {0}inv_left[V10] ≤ 1.0
front_pause[V12] ≤ 1.0 => {0}down[V11] ≤ 1.0
front_pause[V12] ≤ 1.0 => {0}pause_down[V11] ≤ 1.0
longfront[V12] ≤ 1.0 => {D}front[V12] ≤ 1.0

```