```
#include "Proj_1E_header_file.h"


volatile int m;                                         //volatile apparently not needed?
unsigned int PORT_1, PORT_2;

int main (void){
unsigned long counter_squared, counter=1;               //32 bits are reserved for each of these variables

m=0;
setup_HW;
PORT_1=0xFFFF;                                          //Equivalent to 0b1111111111111111
PORT_2 = 0;
I2C_Tx_2_integers(PORT_1, PORT_2);
sei();
T1_65ms_clock_tick();                                   //This subroutine starts HW clock Timer 1 that generates an interrupt every 65mS


while(1){                                               //Interrupts enable several process to take place  simultaneously
counter_squared = counter*counter;                      //In this case squares are calculated some of which are printed out
if((!(counter%33))&& (switch_2_down)){                  //"counter%33" is only zero when counter is 33, 66, 99 etc.
Num_to_PC_U(10, counter); Char_to_PC('\t');           //Only print out results if Switch_2 has been pressed
Num_to_PC_U(10, counter*counter); newline();            //Code in this while-loop could be interrupted at any point
 }counter = (counter + 1)%0x10000;                      //limits the value of counter to avoid overflow and garbage out.
Timer_T2_sub(T2_delay_2ms);}
}


/*********************ISR called evry 65mS to increment the display*****************************************/
ISR(TIMER1_OVF_vect) {

if(m <=15){PORT_2 = (PORT_2 << 1) | 1;                  //PORT_2 is shifted one place to the left
        PORT_1 = PORT_1 << 1;}                          //An additional 1 is placed in the most RH bit using "|1".

        else
        {PORT_2 = (PORT_2 >> 1);                        //PORT_2 now shifts right
        PORT_1 = ~(~PORT_1 >> 1);}                      //see below for quick look at the logic

        I2C_Tx_2_integers(PORT_1, PORT_2);m++;      //increment "m";
if (m==32)m=0;}                                         //Reset "m" when it gets to 32
```