

---

# A Basis for Narrative Reframing Agents

**Daniel T. Kessler**

Massachusetts Institute of  
Technology  
Cambridge, MA 02139, USA  
Kessler1@media.mit.edu

Permission to make digital or hard copies of part or all of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for third-party components of this work must be honored. For all other uses, contact the owner/author(s).

*CHI 2023 Extended Abstracts, April 23, 2023, Hamburg, Germany*

© 2023 Copyright is held by the owner/author(s).

ACM ISBN 978-1-4503-6819-3/20/04.

DOI: <https://doi.org/10.1145/3334480.XXXXXXX>

*\*update the above block & DOI per your rights review confirmation (provided after acceptance)*

## Abstract

While now used in the screening and management of a wide range of mental health conditions, conversational user interfaces (CUIs) have yet to become commonplace in trauma recovery contexts. However, they may be ideally suited to facilitate narrative reframing tasks: trauma-focused therapeutic interventions in which individuals recall, reflect upon, and reconstruct traumatic events in order to reduce their recurring adverse effects (e.g., intrusive thoughts). To improve the utility of CUIs for individuals recovering from traumatic lived experiences, this paper introduces the novel concept of Narrative Reframing Agents, CUIs that are specialized to facilitate narrative reframing tasks.

## Author Keywords

Conversational user interfaces; narrative conversational agents; narrative therapies; trauma-informed care

## CSS Concepts

•**Human-centered computing** → **Human computer interaction (HCI)**; HCI theory, concepts and models  
•**Human-centered computing** → **Accessibility**;  
Accessibility design and evaluation methods

## Introduction

Narrative mental constructs play a key role in both the acquisition and treatment of trauma [12]. As such, trauma-informed therapies have been developed that

center around the narration [29] and subsequent “processing” [40] of traumatic memories. One core feature of this processing is narrative reframing [42], through which individuals challenge dominant and harmful portrayals of these experiences and, in many cases, intentionally modify them [22,42]. But while such approaches have proven effective [3,18,31], the involvement of human facilitators (e.g., therapists) carries with it inherent risks and limitations for individuals with a history of trauma. Triggers for trauma may arise suddenly, at times or in places where human professionals are not available. The independent perceptions and value positions of therapists can also strip storytellers of agency or even invalidate their lived experiences [35]. Likewise, the intrusive nature of human listeners’ response styles can reduce the accuracy and integrity of episodic recollections [37].

To address some of the limitations of human clinicians, conversational user interfaces (CUIs) have been developed in mental health contexts to perform automated diagnosis [19,25], counseling [2,11], and stress reduction tasks [33]. But while many of these CUIs are capable of generic forms of cognitive reframing [5]—a precursor to narrative reframing—few have been developed to perform “trauma work” [10] or related narrative interviewing tasks [47]. Inspired by the novel popularity of viral CUIs for self-therapy [8] and the recent development of a CUI [24] capable of inner child work—a type of narrative reframing in which patients “speak” to their inner child in order to heal unresolved traumas [7]—this paper introduces the novel concept and describes the basic functions of specialized narrative reframing agents (NRAs).

### **What are Narrative Reframing Agents?**

As imagined here, NRAs are trauma-informed conversational agents designed to help users gain greater control over their own adverse and recurrent narrative constructs, based on the premise that “all too often, the stories we believe about ourselves have been written by others” [11]. While NRAs may take many forms, their central aim should be to assist users in the sensitive process of recalling adverse experiences, reconstructing them verbally, and manipulating and interacting with them to achieve novel insights [38] and states of reflective catharsis [6,45]. To accomplish this, NRAs must be capable of narrative interviewing [49], modeling [28], and co-construction tasks [50], as well as augmenting their models on the basis of new information presented by users [15]. NRAs may benefit from a triangulated system architecture accounting for a primary narrative engine (to collect and manage narrative data), a visualization module (to visualize narrative data for users), and an interaction module, comprising the primary expressive agent [12]. Since NRAs are designed in part to “draw out” narrative-form user disclosures, they should possess discursive skills comparable to those of an experienced human interviewer [30,36,49], such that they can retain user attention and engagement as well as engender trust and effectively navigate conversational shifts. Consequently, NRAs should be capable of interacting with users in nonlinear ways that replicate natural human discourse [17]. NRAs should be capable of identifying when users may be avoiding disclosure as a result of known psycho-behavioral barriers, such as feelings of shame, which are common for trauma patients [48]. To better identify these cases, NRAs may independently measure a narrative’s coherence [1] to identify potential gaps within a larger episodic matrix. Importantly, however, NRAs should be capable of

knowing which hidden information to surface and which to isolate until users are better positioned to address them [35]. To ensure applicability of their prompts and recommendations, NRAs should develop trauma-informed user profiles [13] that cater to users' unique experiences, understanding that people recovering from trauma encounter a wide range of challenges including emotional dysregulation and numbing [27]; lowered self-esteem [10]; poorer physical health [39]; cognitive distortions [12]; and feelings of social isolation [40], among other issues [21].

### **Affordances**

NRAs may possess several unique affordances that make them ideally suited to address ongoing treatment gaps. They may be used effectively to elicit information [46,51] and may gather higher quality information than agentless data collection approaches (e.g., surveys; [26]), perhaps especially through the use of active listening skills [4], which may cause NRAs to appear more socially attractive [49]. NRAs may also perform both user interviews and interventions [41,43], allowing them to respond immediately to emergent needs with responsive and appropriate dialectical interactions (e.g., questions). They may also be designed to embody therapeutic agents who are culturally sensitive and responsive to a wide range of user identities [9]. NRAs may be developed to perform story construction tasks [15] and may be helpful for users who have a need for story completion—such as those with a history of trauma, whose memories of traumatic events are subject to impaired recollection processes [27]. Consequently, similar implementations have proven effective at identifying user emotional states [14,19,34]; reducing trauma-induced stress [32,33]; and aiding those who feel stigmatized by

healthcare settings, including those recovering from traumatic experiences, in disclosing their experiences and actively seeking treatment [37].

### **Ethical Challenges**

Ageism [44], gender inclusivity, stereotyping, and discrimination [23] are all outstanding challenges of advanced CUI applications. In designing NRAs for the present population, developers should consider testing methods of “debiasing” their agents [16] as well as identifying when users are expressing hate speech or other harmful language in their own statements [21]. As Reeves [39] points out, people with traumatic life experiences may also become retraumatized as a result of healthcare experiences, including those designed to address their traumas directly.

### **Conclusion**

There is significant potential for the development of NRAs in virtual trauma management. However, there remain few examples of functioning and effective NRAs, and while this paper highlights the utility of such agents, there are many considerations still to be discussed. Narrative reframing tasks are complex, involving rounds of narrative interviewing, modeling, and manipulation tasks. They also require sensitive agents who can ethically support the disclosure of individuals experiencing difficult emotional traumas while engaging them through dynamic, human-like conversations to establish trust. Ultimately, recent developments in viral chat agents [20] may open the door for more effective NRAs that are capable of both advanced narrative modeling and realistic dialogue tasks, allowing for improved CUIs to support this underserved user population.

## References

- [1] Jonathan M Adler. 2012. Living into the story: agency and coherence in a longitudinal study of narrative identity development and mental health over the course of psychotherapy. *J. Pers. Soc. Psychol.* 102, 2 (2012), 367.
- [2] Yuna Ahn, Yilin Zhang, Yujin Park, and Joonhwan Lee. 2020. A chatbot solution to chat app problems: Envisioning a chatbot counseling system for teenage victims of online sexual exploitation. *Extended Abstracts of the 2020 CHI Conference on Human Factors in Computing Systems*. 1–7.
- [3] Giovanna Artioli, Chiara Cosentino, Chiara Taffurelli, Paola Ferri, and Chiara Foà. 2019. The narrative interview for the assessment of the assisted person: structure, method and data analysis. *Acta Bio Medica Atenei Parm.* 90, 6-S (July 2019), 7–16. DOI: 10.23750/abm.v90i6-S.8640
- [4] Christine Bauer and Kathrin Figl. 2008. Active listening” in written online communication-a case study in a course on “soft skills for computer scientists. *IEEE*, F2C-1.
- [5] Clare Beatty, Tanya Malik, Saha Meheli, and Chaitali Sinha. 2022. Evaluating the Therapeutic Alliance With a Free-Text CBT Conversational Agent (Wysa): A Mixed-Methods Study. *Front. Digit. Health* 4, (2022), 847991.
- [6] Nurit Betzalel and Zipora Shechtman. 2017. The impact of bibliotherapy superheroes on youth who experience parental absence. *Sch. Psychol. Int.* 38, 5 (October 2017), 473–490. DOI: 10.1177/0143034317719943
- [7] John Bradshaw. 2013. Homecoming: Reclaiming and healing your inner child. Bantam.
- [8] Ryan Broderick. 2023. People are using AI for therapy, whether the tech is ready for it or not. *Fast Company*. Retrieved February 20, 2023 from <https://www.fastcompany.com/90836906/ai-therapy-koko-chatgpt>
- [9] Laura A Brooks, Elizabeth Manias, and Melissa J Bloomer. 2019. Culturally sensitive communication in healthcare: A concept analysis. *Collegian* 26, 3 (2019), 383–391.
- [10] Bonnie Burstow. 2003. Toward a radical understanding of trauma and trauma work. *Violence Women* 9, 11 (2003), 1293–1317.
- [11] Gillian Cameron, David Cameron, Gavin Megaw, Raymond Bond, Maurice Mulvenna, Siobhan O’Neill, Cherie Armour, and Michael McTear. 2017. Towards a chatbot for digital counselling. In *Proceedings of the 31st International BCS Human Computer Interaction Conference (HCI 2017)* 31. 1–7.
- [12] Marc Cavazza, David Pizzi, Fred Charles, Thurid Vogt, and Elisabeth André. 2009. Emotional input for character-based interactive storytelling. (2009).
- [13] Janet X. Chen, Allison McDonald, Yixin Zou, Emily Tseng, Kevin A Roundy, Acar Tamersoy, Florian Schaub, Thomas Ristenpart, and Nicola Dell. 2022. Trauma-Informed Computing: Towards Safer Technology Experiences for All. In *CHI Conference on Human Factors in Computing Systems*, ACM, New Orleans LA USA, 1–20. DOI: 10.1145/3491102.3517475
- [14] Stefano Neto Jai Hyun Choi, Ana Luiza Fontes de Azevedo Costa, Rita Simone Lopes Moreira, Caio Vinicius Saito Regatieri, and Vagner Rogério dos Santos. 2022. Development of a Chatbot to Identify Depression Through a Questionnaire. *J. Psychiatry Psychiatr. Disord.* 6, 1 (2022), 25–35.
- [15] Jessica Falk, Steven Poulakos, Mubbasir Kapadia, and Robert W. Sumner. 2018. PICA: Proactive Intelligent Conversational Agent for Interactive Narratives. In *Proceedings of the 18th International Conference on Intelligent Virtual*

- Agents, ACM, Sydney NSW Australia, 141–146. DOI: 10.1145/3267851.3267892
- [16] Michael Gira, Ruisu Zhang, and Kangwook Lee. 2022. Debiasing Pre-Trained Language Models via Efficient Fine-Tuning. In *Proceedings of the Second Workshop on Language Technology for Equality, Diversity and Inclusion, Association for Computational Linguistics, Dublin, Ireland*, 59–69. DOI: 10.18653/v1/2022.ltedi-1.8
- [17] Jonathan Grudin and Richard Jacques. 2019. Chatbots, humbots, and the quest for artificial general intelligence. *Proceedings of the 2019 CHI conference on human factors in computing systems*. 1–11.
- [18] Enza Gucciardi, Nicole Jean-Pierre, Grace Karam, and Souraya Sidani. 2016. Designing and delivering facilitated storytelling interventions for chronic disease self-management: a scoping review. *BMC Health Serv. Res.* 16, 1 (December 2016), 249. DOI: 10.1186/s12913-016-1474-7
- [19] Riddhi Hakani, Samiksha Patil, Sakshi Patil, Siddhi Jhunjhunwala, and Khushali Deulkar. 2022. Revivify: A Depression Detection and Control System using Tweets and Automated Chatbot. In *2022 IEEE World Conference on Applied Intelligence and Computing (AIC), IEEE, Sonbhadra, India*, 796–801. DOI: 10.1109/AIC55036.2022.9848978
- [20] Mubin Ul Haque, Isuru Dharmadasa, Zarrin Tasnim Sworna, Roshan Namal Rajapakse, and Hussain Ahmad. 2022. “I think this is the most disruptive technology”: Exploring Sentiments of ChatGPT Early Adopters using Twitter Data. *ArXiv Prepr. ArXiv221205856* (2022).
- [21] Thomas Hartvigsen, Saadia Gabriel, Hamid Palangi, Maarten Sap, Dipankar Ray, and Ece Kamar. 2022. Toxigen: A large-scale machine-generated dataset for adversarial and implicit hate speech detection. *ArXiv Prepr. ArXiv220309509* (2022).
- [22] Hollyn M Johnson. 1994. Processes of successful intentional forgetting. *Psychol. Bull.* 116, 2 (1994), 274.
- [23] Ji-Youn Jung, Sihang Qiu, Alessandro Bozzon, and Ujwal Gadiraju. 2022. Great Chain of Agents: The Role of Metaphorical Representation of Agents in Conversational Crowdsourcing. In *CHI Conference on Human Factors in Computing Systems, ACM, New Orleans LA USA*, 1–22. DOI: 10.1145/3491102.3517653
- [24] Leslie Katz. 2023. She Brought Her Younger Self Back to Life as an AI Chatbot. *CNET*. Retrieved February 19, 2023 from <https://www.cnet.com/science/she-brought-her-younger-self-back-to-life-as-an-ai-chatbot-to-talk-to-her-inner-child/>
- [25] Payam Kaywan, Khandakar Ahmed, Yuan Miao, Ayman Ibaida, and Bruce Gu. 2021. DEPR: An Early Depression Detection Analysis Chatbot. In *Health Information Science, Siuly Siuly, Hua Wang, Lu Chen, Yanhui Guo and Chunxiao Xing (eds.). Springer International Publishing, Cham*, 193–204. DOI: 10.1007/978-3-030-90885-0\_18
- [26] Soomin Kim, Joonhwan Lee, and Gahgene Gweon. 2019. Comparing data from chatbot and web surveys: Effects of platform and conversational style on survey response quality. *Proceedings of the 2019 CHI conference on human factors in computing systems*. 1–12.
- [27] Bessel A. van der Kolk. 1994. The Body Keeps the Score: Memory and the Evolving Psychobiology of Posttraumatic Stress. *Harv. Rev. Psychiatry* 1, 5 (January 1994), 253–265. DOI: 10.3109/10673229409017088
- [28] George Lakoff and Srinu Narayanan. Toward a Computational Model of Narrative. *UC Berkeley Publications*. 8.

- [29] Jeannette CG Lely, Geert E Smid, Ruud A Jongedijk, Jeroen W. Knipscheer, and Rolf J Kleber. 2019. The effectiveness of narrative exposure therapy: a review, meta-analysis and meta-regression analysis. *Eur. J. Psychotraumatology* 10, 1 (2019), 1550344.
- [30] Jingyi Li, Michelle X Zhou, Huahai Yang, and Gloria Mark. 2017. Confiding in and listening to virtual agents: The effect of personality. n *Proceedings of the 22nd International Conference on Intelligent User Interfaces*. 275–286.
- [31] Stephen Madigan. 2019. Recent developments and future directions in narrative therapy. (2019).
- [32] Wookjae Maeng and Joonhwan Lee. 2021. Designing a Chatbot for Survivors of Sexual Violence: Exploratory Study for Hybrid Approach Combining Rule-based Chatbot and ML-based Chatbot. In *Asia CHI Symposium*. 160–166.
- [33] Lenin Medeiros, Tibor Bosse, and Charlotte Gerritsen. 2022. Can a Chatbot Comfort Humans? Studying the Impact of a Supportive Chatbot on Users' Self-Perceived Stress. *IEEE Trans. Hum.-Mach. Syst.* 52, 3 (June 2022), 343–353. DOI: 10.1109/THMS.2021.3113643
- [34] Morten Johan Mygland, Morten Schibbye, Ilias O. Pappas, and Polyxeni Vassilakopoulou. 2021. Affordances in Human-Chatbot Interaction: A Review of the Literature. In *Responsible AI and Analytics for an Ethical and Inclusive Digitized Society*, Denis Dennehy, Anastasia Griva, Nancy Pouloudi, Yogesh K. Dwivedi, Ilias Pappas and Matti Mäntymäki (eds.). *Springer International Publishing, Cham.*, 3–17. DOI: 10.1007/978-3-030-85447-8\_1
- [35] Tatsuya Nomura. 2005. Narratives and therapeutic conversational agents: Their principle problems. 58–61. In *Proc. INTERACT 2005 Workshop on Abuse* (pp. 58-61).
- [36] Jay F Nunamaker, Douglas C Derrick, Aaron C Elkins, Judee K Burgoon, and Mark W Patton. 2011. Embodied conversational agent-based kiosk for automated interviewing. *J. Manag. Inf. Syst.* 28, 1 (2011), 17–48.
- [37] Sumit Pandey, Srishti Sharma, and Samar Wazir. 2022. Mental healthcare chatbot based on natural language processing and deep learning approaches: Ted the therapist. *Int. J. Inf. Technol.* (2022), 1–10.
- [38] Hayatul Khairul Rahmat, Akhmad Muzaki, and Syahti Pernanda. 2021. Bibliotherapy as An Alternative to Reduce Student Anxiety During Covid-19 Pandemic: a Narrative Review. *Proceeding International Conference on Science and Engineering*. (2021), 4.
- [39] Elizabeth Reeves. 2015. A synthesis of the literature on trauma-informed care. *Issues Ment. Health Nurs.* 36, 9 (2015), 698–709.
- [40] Patricia A Resick, Candice M Monson, and Kathleen M Chard. 2016. Cognitive processing therapy for PTSD: A comprehensive manual. *Guilford Publications*.
- [41] Stephen Rollnick and William R Miller. 1995. What is motivational interviewing? *Behav. Cogn. Psychother.* 23, 4 (1995), 325–334.
- [42] Rosalie Samide and Maureen Ritchey. 2021. Reframing the past: Role of memory processes in emotion regulation. *Cogn. Ther. Res.* 45, (2021), 848–857.
- [43] Kyle J Self, Brian Borsari, Benjamin O Ladd, Guerda Nicolas, Carolyn J Gibson, Kristina Jackson, and Jennifer K Manuel. 2022. Cultural adaptations of motivational interviewing: A systematic review. *Psychol. Serv.* (2022).
- [44] Jaisie Sin, Cosmin Munteanu, Numrita Ramanand, and Yi Rong Tan. 2021. VUI influencers: How the media portrays voice user interfaces for older

adults. In *Proceedings of the 3rd Conference on Conversational User Interfaces*. 1-13).

- [45] Emmanuel Stip, Linda Östlundh, and Karim Abdel Aziz. 2020. Bibliotherapy: Reading OVID During COVID. *Front. Psychiatry* 11, (December 2020), 567539. DOI: 10.3389/fpsyt.2020.567539
- [46] Ella Tallyn, Hector Fried, Rory Gianni, Amy Isard, and Chris Speed. 2018. *CHI*. The ethnobot: Gathering ethnographies in the age of IoT. 1–13.
- [47] Myrthe L Tielman, Mark A Neerincx, Rafael Bidarra, Ben Kybartas, and Willem-Paul Brinkman. 2017. A therapy system for post-traumatic stress disorder using a virtual agent and virtual storytelling to reconstruct traumatic memories. *J. Med. Syst.* 41, (2017), 1–10.
- [48] Karen G. Weiss. 2010. Too Ashamed to Report: Deconstructing the Shame of Sexual Victimization. *Fem. Criminol.* 5, 3 (July 2010), 286–310. DOI: 10.1177/1557085110376343
- [49] Ziang Xiao, Michelle X. Zhou, Wenxi Chen, Huahai Yang, and Changyan Chi. 2020. If I Hear You Correctly: Building and Evaluating Interview Chatbots with Active Listening Skills. In *Proceedings of the 2020 CHI Conference on Human Factors in Computing Systems*, ACM, Honolulu HI USA, 1–14. DOI: 10.1145/3313831.3376131
- [50] Ann Yuan, Andy Coenen, Emily Reif, and Daphne Ippolito. 2022. Wordcraft: Story Writing With Large Language Models. In *27th International Conference on Intelligent User Interfaces*, ACM, Helsinki Finland, 841–852. DOI: <https://doi.org/10.1145/3490099.3511105>
- [51] Michelle X. Zhou, Gloria Mark, Jingyi Li, and Huahai Yang. 2019. Trusting Virtual Agents: The Effect of Personality. *ACM Trans. Interact. Intell. Syst.* 9, 2–3 (September 2019), 1–36. DOI: 10.1145/3232077