ALL WORKS SHALL BE CARRIED OUT IN ACCORDANCE WITH B.S.7671, LANDLORDS TERMS AND CONDITIONS AND ALL VALID LEGISLATION. TENDER

A firm accretited to BS EN ISO 9001 - 2000, Reg No. 2006/449

K BAJWA

1:100

STOURBRIDGE LION MEDICAL CENTRE

VERLANE

5 5 5

PROPOSED SECOND FLOOR LIGHTING AND EMERGENCY LIGHTING LAYOUT

Suite 3, Third Floor, 104 - 106 Hagley Road, Edgbaston, Birmingham, West Midlands, B16 8LT TEL: 0121 455 0225 E-Mail - info@absuk.org

Arcobaleno | Consulting Engineers

OTION PIR ON OFF:

COMPRISES A CEILING MOUNTED PASSIVE INFRA RED MOTION SENSOR THAT TURNS THE LIGHTS ON WHEN MOVEMENT IS DETECTED. AFTER A SET PERIOD OF TIME THE LUMINAIRES WILL TURN OFF UNTIL FURTHER MOVEMENT IS SENSED AND WILL THEN AGAIN TURN THE LUMINAIRES ON. NUAL DIMMING: COMPRISES A WALL MOUNTED LIGHTING SWITCH THAT IS MANUALLY ON AND OFF WITH A ROCKER TYPE DIMMING FACILITY ELECTRICAL CONTRACTOR TO ALLOW FOR 4 No. 'K' TYPE LUMINAIRES MOUNTED WITHIN ROOF STRUCTURE AND CONTROLLED FROM LIGHTING SWICTH WITHIN FIRST FLOOR. ELECTRICAL CONTRACTOR TO ALLOW FOR 4 No. 'K' TYPE LUMINAIRES MOUNTED WITHIN ROOF STRUCTURE AND CONTROLLED FROM LIGHTING SWICTH WITHIN FIRST FLOOR PLANT ACCESS ROOM. SWITCHED -----(Z) -\(\tau\) C/6L3 (D)—-77)—-(V)—-AE A A A DBGC/5L3 (W)

ROOM NAME

SEMINAR

SEMINAR

SEMINAR

BOARD ROOM

CORRIDOR

STORAGE

TEA KITCHEN

MALE WC

FEMALE WC

DISABLED WC

DISABLED WC

SF01
SF02
SF02a
SF03
SF04
SF06
SF07
SF08
SF08
SF09

MANUAL DIMMING
MANUAL DIMMING
MANUAL DIMMING
MANUAL DIMMING
MANUAL ON OFF
MANUAL ON OFF
MOTION PIR ON OFF
MOTION PIR ON OFF
MOTION PIR ON OFF
MOTION PIR ON OFF

LEGEND:

This drawing shall be read in conjunction with Arcobaleno Building Services Consulting Engineers Electrical Specification.
 This drawing shall not be used as a working drawing. All scaled dimensions shall be verified on site.
 For architectural and structural details please refer to appropriate specialist drawings

2012 Copyright ©

G

2 x 17W ECO PLR fluorescent lamp recessed downlight complete with high frequency control gear and direct lighting source

2 x 24W T5 fluorescent wall mounted luminaire complete with high frequency control gear and direct / indirect diffuser

2 x 24W T5 fluorescent 600 x 600mm modulo luminaire complete with high frequency control gear and LG7 diffuser

1 1 x 17W ECO PLR fluorescent lamp recessed downlight complete with high frequency control gear and IP44 glass diffuser

J 4 x 14W T5 fluorescent 600 x 600mm modular luminaire complete with high frequency control gear and opal polycarbonate diffuser

ш

Denotes 3 hour emergency co back up to main luminaire

on battery

hour maintained surface mounted emergency minaire complete with appropriatte exit signage gend

Recessed decorative LED downlight mounted above reception desks, style and type to be agreed with client

1 x 55W T5 fluorescent linear luminaire complete with high frequency control gear and IP65 polycarbonate diffuser

3 hour non maintained surface mounted emergency luminaire complete with IP65 polycarbonate diffuser

Wall mounted one way lighting swicth, mour 1100mm AFFL unless otherwise stated, N denotes No. of gangs

Wall mounted two way lighting swicth, mo 1100mm AFFL unless otherwise stated, N denotes No. of gangs

MANUAL ON OFF:

COMPRISES A WAL

ON AND OFF.