WALL 50mm 50mm 146mm 25mm TWIN SWITCHED SOCKET OUTLET
TWIN DATA (RJ45) OUTLET SINGLE BT (RJ45) OUTLET ANIC ALARM SYSTEM OUTLET 146mm 86mm CONSULTING ROOM DESK DADO SETTING OUT DETAIL 25mm 86mm DB1B/1L3
CR Sockets DB1B/3L3 CR Sockets Condensor DBPR/2L3 DBPR/2L2 FOR DISABLED TOILET ALARM REQUIREMENTS REFER TO ABS FIRST FLOOR AREA LIGHTING AND POWER DISTRIBUTION BOARDS DOUBLE STACKED 2 No. 25mmø CONDUITS DROP — WITHIN WALL FROM CEILING VOID TO FLOOR VOID FOR POWER AND DATA CABLING.

CONTRACTOR TO INSTALL A 50mm WIDE BASKET FOR LV AND A 100mm WIDE BASKET FOR DATA WITHIN FLOOR VOID FOR FLOORBOX CABLING DB1B/1L1
CR Sockets DB1B/6L1
CR Sockets DB1B/5L1 CR Sockets DB1B/4L1
CR Sockets
DB1B/3L1
CR Sockets DB1B/2L1 CR Sockets — THE FOLLOWING CIRCUITS ARE REQUENTED IN THE LIFT SHAFT:

6A RCBO — LIFT PIT SOCKETS

6A MCB — LIFT CAR LIGHTING

6A MCB — LIFT SHAFT LIGHTING

BT TELEPHONE LINE — DEDICATED LIFT SHAFT LIGHTING TO BE TWO WAY LOWEST SWITCH TO BE 1300mm FROM GF LEVEL AND SECOND SWITCH 1300mm FROM SECOND FLOOLEVEL INTEGRAL LIFT ISOLATOR, ELECTRICAL TO ALLOW SURPLUS 3M OF SUB MAIN CABLE TO THIS POINT FOR TERMINATION INTO LIFT PANEL. 4 No. 25mmø CONDUITS DROP WITHIN WALL—FROM CEILING VOID TO FLOOR VOID FOR POWER AND DATA CABLING.

CONTRACTOR TO INSTALL A 100mm WIDE BASKET FOR LV AND A 150mm WIDE BASKET FOR DATA WITHIN FLOOR VOID FOR FLOORBOX CABLING

N

P

Q

Q 0/7L1 DBGD/6L1 7 FB DBGD/5L3
DBGD/6L3 DBGD/7L3 000 (5) (D) ALL WORKS SHALL BE CARRIED OUT IN ACCORDANCE WITH B.S.7671, LANDLORDS TERMS AND CONDITIONS AND ALL VALID LEGISLATION. PROPOSED FIRST FLOOR SMALL POWER AND DATA STOURBRIDGE LION MEDICAL CENTRE VERLANE

TENDER

A firm accretited to BS EN ISO 9001 - 2000, Reg No. 2006/449

K BAJWA

1:100

Suite 3, Third Floor, 104 - 106 Hagley Road, Edgbaston, Birmingham, West Midlands, B16 8LT TEL: 0121 455 0225 E-Mail - info@absuk.org

Arcobaleno | Consulting Engineers

LAYOUT

5 5 5

FB

3 Compartment recessed floatfollowing outlets:

TV system outlet, mounted 2000mm AFFL adjacent power supply socket outlet

2 No. Twin switched socket outlets1 No. 4 gang data plate for on site pur

Single data point
Twin data point
Indicates item is loca

SP&N Switched isolator R denotes rating of device

Access Control power supply CCTV Camera power supply in c Self check system Denotes disabled toilet alarm Ps

TP&N Switched isolator R denotes rating of dev

Un—switched fused connection unit, white plastic complete with neon indicator, mounted adjacent equipment it is feeding unless otherwise stated, as follows:

Denotes Refrigerator power supply Denotes dishwasher power supply Denotes Washing Machine supply

Switched fused connection unit (150mm aboc worktop) connected to low level single socket outlet (450mm AFFL), white plastic complete neon indicator, as follows:

This drawing shall not be used as a working drawing. All scaled dimensions shall be verified on site.
 For architectural and structural details please refer to appropriate specialist drawings

uts to be

MC Der

White plastic twin switched socket outlet mo 450mm affl unless otherwise stated

single switched socket or mm affl unless otherwise

Switched fused connection unit, white plastic complete with neon indicator, mounted adjacent equipment it is feeding, as follows:

Water Boiler power supply
Comfort Cooling unit power supply
Examination lamp power supply
Hand Drier power supply
Patient call system
Self check system

This drawing shall be read in conjunction with Arcobaleno Building Services Consulting Enginee Electrical Specification.

0