

Final test checklist AD2CP



Vangskroen 2
N-1351 RUD
Norway
Tel: +47 6712 4500
Fax: +47 6713 6770
inquiry@nortek-as.com
www.nortek.no

Order number:
40112-1-1-82

Name: **Signature 100**
Instrument serial number: **100757**
Frequency: **100 KHz** Main board: **AD2CP-1248**
Firmware versions: **1.4.4792.2206-18 / 165**

Label checked ☒ OK
Dock test ☒ OK
Baudrate 115200 ☒ OK

Comments:

Tilt check
☒ Pitch up
☒ Roll up
☒ Status bit
☒ Pitch down
☒ Roll down
pitch & roll within +/- 0.2 °

Clock
☒ Set clock

Heading
☒ Up
☒ Down
tolerance: +/- 2 °

Pressure
100
Psensortemp ☒ OK
tolerance: +/- 0.1 % of
1500 m

Temperature
☒ OK
tolerance: +/- 0.1 °

Beam check

Correct order	Beam Imp	Noise floor	Amplitude in tank	Range
Beam 1 ☒ OK	68 Ω	25 dB	> 80 dB	☒ OK
Beam 2 ☒ OK	75 Ω	25 dB	> 80 dB	☒ OK
Beam 3 ☒ OK	69 Ω	25 dB	> 80 dB	☒ OK
Beam 4 ☒ OK	69 Ω	25 dB	> 80 dB	☒ OK
Beam 5 ☒ OK	840 Ω	25 dB	> 80 dB	☒ OK

Velocity direction **To heavy to Verify**
XYZ coordinate system **Matrix correct.** ENU coordinate system
X ☐ OK E ☐ OK
Y ☐ OK N ☐ OK
Z ☐ OK U ☐ OK
Z₂ ☐ OK U₂ ☐ OK

Head file
☒ Headfile checked
☒ Saved as read only

Serial communication
☐ RS422
☐ RS232

Recorder erased ☒ OK
Rec size: **128GB**

Ethernet
MAC address: **8C:68:78:00:04:E0**
Static IP address:
Set host name: **100757**

DHCP enabled ☒
FTP OK ☒

Licenses

Averaging mode ☒	Wave mode ☐	Vertical velocity ☐	64GB recorder ☐	Calibration license erased ☒
Burst Five beams ☐	Echo Sounder ☒	Dual frequency low ☐	128GB recorder ☒	Production license erased ☒
Bottom track ☐	Ice Measurement ☐	Dual frequency high ☐	256GB recorder ☐	Default configuration set ☒
High Resolution ☐	Altimeter ☐	16GB recorder ☐		

Cable/Harness
Cable Communication ☒ Harness Communication ☒
Battery ☒ Battery ☒

Electrical isolation test
50V Ok ☒

External sensors

Power down
☒ OK

Date
Day **29** Month **06** Year **18**
Signature

Contents of the shipping box



Vangkrøken 2
N-1351 RUD
Norway
Tel: +47 6717 4500
Fax: +47 6713 6770
inquiry@nortek-as.com
www.nortek.no

Nortek order no:

40112-1-1-82

Type of system:

SIGNATURE 700

Instrument type:

- | | | | | |
|--|---|--|---------------------------------------|--|
| ☐ Aquadopp | ☐ Aquadopp 6000m | ☐ Vector | ☐ Signature55 | ☐ Signature1000 |
| ☐ Aquadopp profiler | ☐ AWAC | ☐ Vectrino | ☐ Signature250 | ☐ NortekDVL |
| ☐ Aquadopp 3000m | ☐ VM AWAC | ☐ Vectrino profiler | ☐ Signature500 | |

Software version:

SIGNATURE
DEPLOYMENT

Firmware version:

1.4.4792.2206-18/165

Other:

Cable:

☒ 10m length

☐ Other:

Connector:

☐ 8-pin Inline

☐ 12-pin UW

☐ 6-pin Inline

☐ 7-pin Souriau

☐ Other:

Communication:

☐ RS232

☒ Ethernet

☐ RS422

☐ Other:

Options:

☐ Analog input

☐ Synch

☐ Analog output

☐ Other:

Battery cannister:

☐ Paradopp battery cannister

☐ Single battery aluminium cannister

☐ Double battery aluminium cannister

Battery cables:

☐ 2pin Inline-2pin

☐ 8pin Inline-2pin

☐ 8pin rectangular-2pin

Accessories:

☒ Toolkit

☐ Quick guide

☐ Warranty card

☒ Final test checklist

☐ Seeding material

☐ USB to serial converter RS232

☐ Altronix AL310 USB driver

☐ Recorder kit/ProLog

☐ Battery harness for 2 batteries

Batteries:

☐ Alkaline 50Wh 13.5V

☐ Alkaline 100Wh 13.5V

☐ Alkaline 540Wh 13.5V

☐ Alkaline 540Wh 18V

☐ Alkaline 90Wh 15V (Signature1000)

☐ Alkaline 180Wh 18V (Signature500)

Extra set:

AC/DC Power supply

☐ 15V standard

☐ 48V Signature55
Online

☐ 24V Vectrino

Plug

☒ 24V DC/DC &
Signature

☐ EU

☐ UK

☒ US

Other:

MIDAS SOFTWARE

Date:

05.07.2005

Responsible:

Taina V. Lamm