

Master SaltStack States: A Beginner's Guide

Configuring servers manually is slow and leads to human errors. SaltStack automates this by letting you define your server's ideal state in simple, reusable text files.

What you'll learn:

- 1 Checking Server Connections with Ping
- 2 Installing Packages Automatically
- 3 Keeping Services Up and Running
- 4 Applying Your First State Configuration

Aman Raj Singh

Cloud Operations Engineer @ iManage

[linkedin.com/in/mramanrajsingh](https://www.linkedin.com/in/mramanrajsingh)

1

TIP 1 OF 4

Checking Server Connections with Ping

Before configuring anything, you need to verify that your central Master server can talk to your Minion servers. The `test.ping` command doesn't just do a standard network ping; it actually verifies that the Salt communication channel is secure, active, and ready for commands.

```
$salt '*' test.ping
```

Cloud & DevOps Daily

SaltStack States: Automate Server Setup Step by Step

Tuesday, September 15, 2026

Swipe to tip 2 >> linkedin.com/in/mramanrajsingh

2

TIP 2 OF 4

Installing Packages Automatically

Instead of running manual installation commands on every machine, you write a State file (.sls) using simple YAML. This tells Salt to ensure a package is installed. If it is already there, Salt safely does nothing; if it is missing, Salt installs it for you.

```
$install_nginx:  
  pkg.installed:  
    - name: nginx
```

Cloud & DevOps Daily

SaltStack States: Automate Server Setup Step by Step

Tuesday, September 15, 2026

Swipe to tip 3 >> linkedin.com/in/mramanrajsingh

3

TIP 3 OF 4

Keeping Services Up and Running

Installing a tool like Nginx is only half the battle; you also need to make sure the service is actively running and configured to start on boot. By using the `service.running` state, Salt constantly monitors the service and restarts it if it unexpectedly stops.

```
$start_nginx:
  service.running:
    - name: nginx
    - enable: True
```

Cloud & DevOps Daily

SaltStack States: Automate Server Setup Step by Step

Tuesday, September 15, 2026

Swipe to tip 4 >> linkedin.com/in/mramanrajsingh

4

TIP 4 OF 4

Applying Your First State Configuration

Once you have defined your packages and services in a state file (for example, `webserver.sls`), you use the `state.apply` command to run it. Salt compiles your instructions, deploys them to the targeted servers, and gives you a clean, color-coded success report.

```
$salt '*' state.apply webserver
```


Cloud & DevOps Daily

SaltStack States: Automate Server Setup Step by Step

Tuesday, September 15, 2026

See Key Takeaways on next page >> linkedin.com/in/mramanrajsingh

Key Takeaways

- + Use 'dry-run' mode (test=True) to see what changes will happen before actually making them.
- + Keep your state files modular by separating database, web, and security configurations.
- + Always use spaces instead of tabs, as Salt is very sensitive to YAML indentation.
- + Name your state IDs clearly so your team knows exactly what each block of code does.
- + Store your Salt state files in Git version control to track changes over time.

Watch Out For

- ! Using tabs instead of spaces in your YAML files, which causes syntax compilation crashes.
- ! Forgetting to accept the Minion's security key on the Master using the 'salt-key' command.
- ! Running commands as a non-root user without proper sudo privileges configured for Salt.
- ! Hardcoding environment-specific values instead of using dynamic pillars or grains.

Follow for daily Cloud & DevOps guides!

linkedin.com/in/mrmanrajsingh