

Mastering SaltStack Pillars and Grains: A Beginner Guide

Managing server configurations across dozens of nodes can quickly become overwhelming without the right tools. SaltStack Grains and Pillars help you inspect system details and deliver secure parameters easily.

What you'll learn:

- 1 Understanding Server Bio with Grains
- 2 Targeting Servers Dynamically Using Grains
- 3 Managing Secrets Centrally with Pillars
- 4 Updating Pillar Configuration Live

Aman Raj Singh

Cloud Operations Engineer @ iManage

linkedin.com/in/mramanrajsingh

1

TIP 1 OF 4

Understanding Server Bio with Grains

Grains are static pieces of information generated automatically when a Salt minion starts up.

They include hardware details, operating system specs, IP addresses, and custom tags you define.

Use grains whenever you need to inspect node hardware or group servers by platform.

```
$salt '*' grains.item os osrelease mem_total
```

Cloud & DevOps Daily

SaltStack Pillars & Grains: Manage Server Config at Scale

Friday, September 11, 2026

Swipe to tip 2 >> linkedin.com/in/mramanrajsingh

2

TIP 2 OF 4

Targeting Servers Dynamically Using Grains

Instead of maintaining lists of IP addresses, target servers based on their grain attributes. This allows you to execute commands across all Ubuntu machines or all servers tagged for staging.

It prevents human error when deploying software patches across complex environments.

```
$salt -G 'os:Ubuntu' pkg.install nginx
```

Cloud & DevOps Daily

SaltStack Pillars & Grains: Manage Server Config at Scale

Friday, September 11, 2026

Swipe to tip 3 >> linkedin.com/in/mramanrajsingh

3

TIP 3 OF 4

Managing Secrets Centrally with Pillars

Pillars store sensitive, dynamic data on the Salt master and distribute it only to designated minions.

Unlike grains, pillar data is strictly kept secret on the master and never broadcasted to unauthorized nodes.

This makes pillars ideal for API keys, passwords, and custom app configs.

```
$salt 'web-server-01' pillar.item db_credentials
```

Cloud & DevOps Daily

SaltStack Pillars & Grains: Manage Server Config at Scale

Friday, September 11, 2026

Swipe to tip 4 >> linkedin.com/in/mramanrajsingh

4

TIP 4 OF 4

Updating Pillar Configuration Live

When you change configuration parameters or credentials inside pillar files on your Salt master, minions don't know immediately.

Executing a pillar refresh forces minions to re-fetch their assigned secrets without rebooting the server.

This allows seamless configuration changes on live production nodes.

```
$salt '*' saltutil.refresh_pillar
```


Cloud & DevOps Daily

SaltStack Pillars & Grains: Manage Server Config at Scale

Friday, September 11, 2026

See Key Takeaways on next page >> linkedin.com/in/mrmanrajsingh

Key Takeaways

- + Use Grains for static attributes like OS, hardware, and custom environment tags.
- + Use Pillars for sensitive information like passwords, API tokens, and SSL certificates.
- + Keep custom grain definitions consistent across all environments.
- + Always run 'saltutil.refresh_pillar' after updating pillar configuration files.
- + Target minion groups with grain flags (-G) to automate environment updates safely.

Watch Out For

- ! Storing sensitive credentials in Grains instead of Pillars.
- ! Forgetting to refresh pillar data on minions after modifying pillar SLS files on the master.
- ! Overusing custom grains for data that frequently changes (use Pillars instead).

Follow for daily Cloud & DevOps guides!

linkedin.com/in/mrmanrajsingh