

Beginner Guide to Docker Registries and Images

A Docker registry is like GitHub for your containers, letting you safely store and distribute runnable software. Understanding how to push, pull, and tag images ensures your applications run smoothly across any environment without surprises.

What you'll learn:

- 1 Logging In to a Registry Securely
- 2 Tagging Images for Cloud Upload
- 3 Pushing and Pulling Container Images
- 4 Setting Up an In-House Local Registry

Aman Raj Singh

Cloud Operations Engineer @ iManage

linkedin.com/in/mramanrajsingh

1

TIP 1 OF 4

Logging In to a Registry Securely

Before you can push images to Docker Hub or any private registry, your terminal must be authenticated. Running docker login prompts for your username and password or access token. Docker stores these credentials locally in your home directory so you do not need to authenticate every time. For automation, avoid entering passwords manually by passing credentials safely via standard input.

```
$echo "$DOCKER_TOKEN" | docker login -u "myusername" --password-stdin
```

Cloud & DevOps Daily

Docker Registry Explained: Push & Pull Images Like a Pro

Saturday, September 26, 2026

Swipe to tip 2 >> linkedin.com/in/mramanrajsingh

2

TIP 2 OF 4

Tagging Images for Cloud Upload

A Docker registry will reject any image that does not follow the correct naming format: registry-address/username/repository:tag. Tagging simply creates an alias pointing to your local image ID without copying data or taking extra disk space. Always replace default tags with clear semantic version numbers or short git commit hashes so team members know what code is inside.

```
$docker tag webapp:dev myusername/webapp:v1.0.0
```

Cloud & DevOps Daily

Docker Registry Explained: Push & Pull Images Like a Pro

Saturday, September 26, 2026

Swipe to tip 3 >> [linkedin.com/in/mramanrajsingh](https://www.linkedin.com/in/mramanrajsingh)

3

TIP 3 OF 4

Pushing and Pulling Container Images

Pulling downloads missing image layers to your machine so you can run containers locally. Pushing uploads your tagged image layers to the remote registry for servers to download later. Docker transfers only modified layers during pushes and pulls, saving significant network bandwidth and build time. Once uploaded, anyone with read access can pull and run the exact same container.

```
$docker push myusername/webapp:v1.0.0  
docker pull myusername/webapp:v1.0.0
```

Cloud & DevOps Daily

Docker Registry Explained: Push & Pull Images Like a Pro

Saturday, September 26, 2026

Swipe to tip 4 >> [linkedin.com/in/mramanrajsingh](https://www.linkedin.com/in/mramanrajsingh)

4

TIP 4 OF 4

Setting Up an In-House Local Registry

You do not need a paid cloud account to learn or test container registries. Docker maintains an official open-source registry image that you can spin up locally in seconds on port 5000. Once running, you can retag your local images with localhost:5000 and push directly to your local machine. This is an ideal setup for testing CI/CD pipelines completely offline.

```
$ docker run -d -p 5000:5000 --name registry-srv registry:2
docker tag webapp:v1.0.0 localhost:5000/webapp:v1.0.0
docker push localhost:5000/webapp:v1.0.0
```

Cloud & DevOps Daily

Docker Registry Explained: Push & Pull Images Like a Pro

Saturday, September 26, 2026

See Key Takeaways on next page >> linkedin.com/in/mramanrajsingh

Key Takeaways

- + Avoid the :latest tag in production; use semantic versions like :1.2.0 instead.
- + Use small base images like Alpine or Distroless to keep pull times fast.
- + Always configure a .dockerignore file to exclude local secrets and logs before building.
- + Create personal access tokens on Docker Hub instead of using your primary account password.
- + Pin mission-critical images using their SHA256 digest to prevent unintended changes.

Watch Out For

- ! Forgetting to include your username in the tag, leading to 'access denied' errors on push.
- ! Accidentally baking API keys or database passwords into images uploaded to public registries.
- ! Overwriting existing version tags instead of incrementing the version number.

Follow for daily Cloud & DevOps guides!

linkedin.com/in/mrmanrajsingh