

# Coding Lab: Reading in data

Ari Anisfeld

Summer 2020

# So you found some data

Say you find a spreadsheet on the internet and want to start exploring it with R.

Sometimes loading data is as easy as

```
texas_housing_data <- read_csv("texas_housing_data.csv")
```

But often you'll need to consider:

- ▶ File location
- ▶ File type
- ▶ Funky formatting

## detour: directory structure

Computer hard drives are organized using a file system. In this way, each file has a unique “address” or **file path**.



```
~/Documents/coding_lab_examples/texas_housing_data.csv
```

The files are stored in folders or directories which are analagous to “zip codes”.

▶ `~/Documents/coding_lab_examples/`

In Windows, file paths start with `C://...`

## detour: working directory

The 'working directory' in an R session is the folder your script knows about. If the data you want is in that folder you can refer to it directly.

```
fed_data <- read_xlsx("SCE-Public-LM-Quarterly-Microdata.xlsx")
```

`getwd()` shows your current working directory .

## detour: directory structure

if the data were not in your current working directory you could:

- ▶ give the full address:  
`read_csv("~/Documents/coding_lab_examples/file.csv")`
- ▶ give a relative address:  
`read_csv("coding_lab_examples/file.csv")`
- ▶ change the current working directory:  
`setwd("~/Documents/coding_lab_examples")`
- ▶ move the file to the current working directory: drag and drop

## loading data of various formats

We can load data into R with different functions depending on the data format.

file type	package	function
.csv	readr	read_csv()
.dta (stata)	haven	read_dta()
.xlsx	readxl	read_xlsx()

Note: readr is loaded with tidyverse

## loading data?

While often you can just load the data directly, we often require finesse

```
fed_data <-  
  read_xlsx("../data/SCE-Public-LM-Quarterly-Microdata.xlsx")  
head(fed_data)
```

```
## # A tibble: 6 x 1  
##   `License for Survey of Consumer Expectations Data and  
##   <chr>  
## 1 <NA>  
## 2 The Survey of Consumer Expectations (the "SCE") was de  
## 3 FRBNY launched the SCE in 2013. The subject matter ar  
## 4 questions have been informed by or adapted from other  
## 5 FRBNY has published the SCE questions and most data it  
## 6 and resuse. FRBNY permits use of the SCE questions and
```



```

fed_data <-
  read_xlsx("../data/SCE-Public-LM-Quarterly-Microdata.xlsx",
            sheet = "Data 2013",
            skip = 1)
head(fed_data)

```

```

## # A tibble: 6 x 488
##   userid weight L1_rc L2_rc     L4     L5   L5b     L6     L6
##   <dbl>   <dbl> <dbl> <dbl> <dbl> <dbl> <dbl> <dbl> <dbl>
## 1 7.00e7  0.662     2     1     0    NA    NA     2     NA
## 2 7.00e7  0.738     1     1     0    NA    NA     3     NA
## 3 7.00e7  0.473     1     3     0    NA    NA     2     NA
## 4 7.00e7  4.62      9    NA    NA     0     2    NA     NA
## 5 7.00e7  0.491     2     1     1    NA    NA    NA     NA
## 6 7.00e7  0.348     1     3     0    NA    NA     1     NA
## # ... with 476 more variables: L9 <dbl>, L10 <dbl>, L11
## #   L11_weekly <dbl>, L11_annual <dbl>, L11_flag <dbl>,
## #   JH9_weekly <dbl>, JH9_annual <dbl>, L14self_1_rc <dbl>,
## #   L14self_3_rc <dbl>, L14self_4_rc <dbl>, L14_1_rc <dbl>,
## #   L14_3_rc <dbl>, L14_4_rc <dbl>, L14_5_rc <dbl>, L14_

```

## looking at data: head(), glimpse() or View()

- ▶ head() and glimpse() provide ways to see part of your data.
- ▶ View() provides a more spreadsheet-like experience.

```
head(texas_housing_data)
```

```
## # A tibble: 6 x 9
##   city      year month sales    volume median listings inv
##   <chr>    <dbl> <dbl> <dbl>    <dbl>   <dbl>    <dbl>
## 1 Abilene  2000     1    72  5380000  71400    701
## 2 Abilene  2000     2    98  6505000  58700    746
## 3 Abilene  2000     3   130  9285000  58100    784
## 4 Abilene  2000     4    98  9730000  68600    785
## 5 Abilene  2000     5   141 10590000  67300    794
## 6 Abilene  2000     6   156 13910000  66900    780
```

## getting meta data

Get number of rows

```
nrow(texas_housing_data)
```

```
## [1] 8602
```

See column names

```
names(texas_housing_data)
```

```
## [1] "city"      "year"      "month"     "sales"     "vol"
```

```
## [7] "listings"  "inventory" "date"
```

## Recap

- ▶ For most file types there's a function of form `read_xxx()` that will get the data into R.
- ▶ Use `getwd()` and `setwd()` to ensure you're in the right directory.
- ▶ When you have funky formatting use `?`  to see if R can help you fix the problem on read.
- ▶ R has useful functions like `View()`, `glimpse()`, `head()`, `names()` and `nrow()` to get to know your data.