

---

**HIRISE\_api**

**unknown**

**Aug 29, 2022**



CONTENTS

1 HIRISE\_api 3

1.1 HIRISE\_api.hirise . . . . . 3

1.2 HIRISE\_api.models . . . . . 4

1.3 HIRISE\_api.preprocessing . . . . . 8

1.4 HIRISE\_api.tests . . . . . 11

Python Module Index 13



HIRISE Api tool

---

*HIRISE\_api*

---



## HIRISE\_API

### Modules

---

*HIRISE\_api.hirise*

---

*HIRISE\_api.models*

---

*HIRISE\_api.preprocessing*

---

*HIRISE\_api.tests*

---

## 1.1 HIRISE\_api.hirise

### Modules

---

*HIRISE\_api.hirise.Hirise\_Image*

---

*HIRISE\_api.hirise.Image\_Client*

---

*HIRISE\_api.hirise.utils*

---

### 1.1.1 HIRISE\_api.hirise.Hirise\_Image

#### Classes

---

<code>HiriseImage(file_name)</code>	Class that creates an HIRISE image object that has specific attributes including latitude longitude
-------------------------------------	---

---

### 1.1.2 HIRISE\_api.hirise.Image\_Client

#### Classes

---

ImageClient()
---------------

---

### 1.1.3 HIRISE\_api.hirise.utils

#### Functions

LBL_parser(label_url)	Function that parses the .LBL file in NASA's Planetary Data System
append_float_data_without_strip(param, ...)	Function that validates floating point data without stripping the last characters
downloadRange(start_range, end, step)	
file_parameters_list()	Function that returns file parameters list
get_website_data(base_url, page_key[, sub_key])	Function that assistes in wescaping the NASA website
image_map_parameters_list()	Function that returns image mapping parameters list
other_parameters_list()	Function that returns scaling factor, offset, center filter wavelength parameters list
timing_parameters_list()	Function that returns timing parameters list
validate_append_float_data(param, list_of_params)	Function that validates floating point data
viewing_parameters_list()	Function that returns viewing parameters list

## 1.2 HIRISE\_api.models



## Modules

---

*HIRISE\_api.models.Affinity\_Propagation*

---

*HIRISE\_api.models.Agglomerative\_Clustering*

---

*HIRISE\_api.models.BIRCH*

---

*HIRISE\_api.models.DBSCAN*

---

*HIRISE\_api.models.Ensemble\_Models*

---

*HIRISE\_api.models.HDBSCAN*

---

*HIRISE\_api.models.KMeans*

---

*HIRISE\_api.models.Mean\_Shift*

---

*HIRISE\_api.models.OPTICS*

---

*HIRISE\_api.models.metrics*

---

*HIRISE\_api.models.utils*

---

### 1.2.1 HIRISE\_api.models.Affinity\_Propagation

#### Functions

---

<code>affinity_propagation_analysis(...[, plot, ...])</code>	Function that uses as input the encoded image samples and clusters the data using affinity propagation.
--	---

---

### 1.2.2 HIRISE\_api.models.Agglomerative\_Clustering

#### Functions

---

<code>agglomerative_clustering_analysis(...[, ...])</code>	Function that uses as input the encoded image samples and clusters the data using agglomerative clustering.
--	---

---

### 1.2.3 HIRISE\_api.models.BIRCH

#### Functions

---

<code>BIRCH_analysis(encoded_samples, ...[, plot, ...])</code>	Function that uses as input the encoded image samples and clusters the data using affinity propagation.
--	---

---

### 1.2.4 HIRISE\_api.models.DBSCAN

#### Functions

---

<code>DBSCAN_analysis(encoded_samples, true_labels)</code>	Function that uses as input the encoded image samples and clusters the data using Density-based spatial clustering of applications with noise.
--	--

---

### 1.2.5 HIRISE\_api.models.Ensemble\_Models

#### Functions

---

<code>ensemble_model(encoded_data, labels, ...[, ...])</code>	
<code>evaluate_model(model, translation_dataframe, ...)</code>	Function that uses cross-validation and evaluates the stacking model.
<code>get_models([discovery])</code>	Function that defines specified models as an input to the ensemble model.
<code>get_stacking([discovery, all_models])</code>	Function that stacks specified models together as an input to the ensemble model.

---

#### Classes

---

<code>AgglomerativeClusteringWrapper([n_clusters, ...])</code>	
<code>DBSCANWrapper([eps, min_samples, metric, ...])</code>	
<code>HDBSCANWrapper([min_cluster_size, ...])</code>	
<code>OpticsWrapper(*[, min_samples, max_eps, ...])</code>	

---

### 1.2.6 HIRISE\_api.models.HDBSCAN

#### Functions

HDBSCAN_analysis(encoded_samples[, ...])	Function that uses as input the encoded image samples and clusters the data using Hierarchical Density-based spatial clustering of applications with noise. The user must specify only the minimum samples, which is the tuning parameters for HDBSCAN.
--	---

### 1.2.7 HIRISE\_api.models.KMeans

#### Functions

kmeans_analysis(encoded_samples[, clusters, ...])	Function that uses as input the encoded image samples and clusters the data using K Means clustering of applications with noise.
---	--

### 1.2.8 HIRISE\_api.models.Mean\_Shift

#### Functions

mean_shift_analysis(encoded_samples[, plot, ...])	Function that uses as input the encoded image samples and clusters the data using Mean Shift Clustering Method.
---	---

### 1.2.9 HIRISE\_api.models.OPTICS

#### Functions

OPTICS_analysis(dataframe[, eps, ...])	Function that uses as input the encoded image samples and clusters the data using Ordering Points To Identify Cluster Structure Method.
--	---

### 1.2.10 HIRISE\_api.models.metrics

**Functions**

<code>calculate_metrics(model, labels[, verbose])</code>	Function that calculates metrics including, rand score, adjusted rand score, mutual information score, normalized mutual information score, adjusted mutual information score, balanced accuracy score, completeness score, homogeneity score and v-score for a given model.
<code>classification_metrics_dataframe(model_list, ...)</code>	Function that creates a metrics dataframe based on the calculated metrics for each model in the model list specified by the user.
<code>generate_precision_dataframe(folder_path, ...)</code>	Function that returns a generated a dataframe of all the precision values evaluated for a true and predicted labels after classification analysis on a dataset.
<code>print_confusion_matrix(folder_path, ...[, ...])</code>	Function that prints the confusion matrix metric for a given set of image clustering results and the associated images.

**1.2.11 HIRISE\_api.models.utils****Functions**

<code>elbow_curve(encoded_samples[, max_values, ...])</code>
<code>generate_precision_dataframe(folder_path, ...)</code>
<code>translate_labels(translation_list, model_results)</code>

**1.3 HIRISE\_api.preprocessing****Modules**

<code><i>HIRISE_api.preprocessing.Data_Preparation</i></code>
<code><i>HIRISE_api.preprocessing. Dimension_Reduction</i></code>
<code><i>HIRISE_api.preprocessing.Encoding</i></code>
<code><i>HIRISE_api.preprocessing.Image_Loader</i></code>
<code><i>HIRISE_api.preprocessing.utils</i></code>

### 1.3.1 HIRISE\_api.preprocessing.Data\_Preparation

#### Classes

DataPreparation()	Class that allows for data preparation as part of the pre-processing of the hirise images.
-------------------	--

### 1.3.2 HIRISE\_api.preprocessing.Dimension\_Reduction

#### Functions

PCA_analysis(encoded_samples, labels[, ...])	The PCA analysis allows the user to understand different aspects of the PCA method.
TSNE_analysis(encoded_samples, labels[, ...])	The T-SNE analysis allows the user to understand different aspects of the TSNE method. The user can choose to plot the 2D and 3D visualisations.
UMAP_analysis(encoded_samples[, components, ...])	The UMAP analysis allows the user to understand different aspects of the UMAP method.

### 1.3.3 HIRISE\_api.preprocessing.Encoding

#### Functions

create_encoded_samples_dataframe(folder_path)	Function that uses the autoencoder to encode the samples and return an encoded samples dataframe to the user based on latent dimensions input by the user
plot_autoencoder_results(encoder, decoder, ...)	Function that plots the original and reconstructed images from the autoencoder results
test_batches(encoder, decoder, device, ...)	Function that is used to test the Convolutional Autoencoder and return the mean loss, averaged over all input batches.
train_CAE(encoder, decoder, device, ...)	Function that is used to train using a single batch input into the autoencoder.
train_batches(encoder, decoder, device, ...)	Function that is used to train the Convolutional Autoencoder and return the mean loss, averaged over all input batches.
transfer_learning_encoding(folder_path[, ...])	The Transfer learning function takes in the folder path of the images to

**Classes**

CAEDecoder(encoded_space_dim, fc2_input_dim)	Class that supports functions needed to define the architecture and forward functions of the decoder in the Convolutional Autoencoder
CAEEncoder(encoded_space_dim, fc2_input_dim)	Class that supports functions needed to define the architecture and forward functions of the encoder in the Convolutional Autoencoder

**1.3.4 HIRISE\_api.preprocessing.Image\_Loader****Functions**

generate_dataloaders(folder_path[, transform])	Function that generates the dataloaders for a HIRISE dataset, given folder path specified by the user
generate_dataset(folder_path[, transform])	Function that generated the HIRISE Dataset given a folderpath of HIRISE Images
initialize_encoder_decoder([latent_dimensions])	Fuction that initialized the encoder and decoder depeining on the latent
show_classes(folder_path[, transform, ...])	Function that shows all classes defined by the user though the Image Folders using the Image Folder dataset
show_encoder_decoder_image_sizes(folder_path)	Function that returns the input and output image sizes of images that have been through the autoencoding process

**Classes**

HiriseImageDataset(path_to_images[, transform])	Hirise Image Dataset Class that initialize the pytorch ImageLoader Dataset with the folder images to return and image and associated folder name( label)
---	--

**1.3.5 HIRISE\_api.preprocessing.utils****Functions**

create_image_list(file_path[, transform])	Function that creates a list of all the images in the specified folder in a PIL format
display_all_images(file_path, ...[, ...])	Function to display all the image in the folder in a flat rasterfied format.
display_image_distributions(image_file_path, ...)	Function to display all the image in the folder as images on a distributed map using TSNE,UMAP or PCA as the preprocessing function
normalize_results(encoded_samples)	Function that is used to normalize the values of the encoded samples.
read_encoded_csv(file_path[, autoencoder])	
show_cluster_images(image_file_path, ...[, ...])	Prints the image in a specified cluster, in the form of a grid with rows and columns specified by the user

## 1.4 HIRISE\_api.tests

### Modules

---

*HIRISE\_api.tests.test\_hirise*

---



---

*HIRISE\_api.tests.test\_models*

---



---

*HIRISE\_api.tests.test\_preprocessing*

---

### 1.4.1 HIRISE\_api.tests.test\_hirise

#### Functions

---

test\_database\_exists()

---



---

test\_filter\_center\_latlon()

---



---

test\_get\_all\_parameters()

---



---

test\_get\_images()

---



---

test\_get\_individual\_parameters()

---

### 1.4.2 HIRISE\_api.tests.test\_models

#### Functions

---

test\_clustering\_results()

---



---

test_metrics_function()	Test if metrics function returns all 9 metrics output as expected
-------------------------	---

---



---

test_translate_labels()	Test if label translation function for classification metrics translated user defined labels as expected
-------------------------	--

---

### 1.4.3 HIRISE\_api.tests.test\_preprocessing

#### Functions

---

test_autoencoder()	Test if output size of the auto-encoded image is as expected
--------------------	--

---



---

test_pca_dimension_reduction()	Test if output of PCA Analysis is as expected
--------------------------------	---

---



---

test_tsne_dimension_reduction()	Test if output of TSNE Analysis is as expected
---------------------------------	--

---



---

test_umap_dimension_reduction()	Test if output of UMAP analysis is as expected
---------------------------------	--

---





## PYTHON MODULE INDEX

### h

- `HIRISE_api`, 3
- `HIRISE_api.hirise`, 3
  - `HIRISE_api.hirise.Hirise_Image`, 3
  - `HIRISE_api.hirise.Image_Client`, 4
  - `HIRISE_api.hirise.utils`, 4
- `HIRISE_api.models`, 4
  - `HIRISE_api.models.Affinity_Propagation`, 5
  - `HIRISE_api.models.Agglomerative_Clustering`, 5
  - `HIRISE_api.models.BIRCH`, 6
  - `HIRISE_api.models.DBSCAN`, 6
  - `HIRISE_api.models.Ensemble_Models`, 6
  - `HIRISE_api.models.HDBSCAN`, 7
  - `HIRISE_api.models.KMeans`, 7
  - `HIRISE_api.models.Mean_Shift`, 7
  - `HIRISE_api.models.metrics`, 7
  - `HIRISE_api.models.OPTICS`, 7
  - `HIRISE_api.models.utils`, 8
- `HIRISE_api.preprocessing`, 8
  - `HIRISE_api.preprocessing.Data_Preparation`, 9
  - `HIRISE_api.preprocessing.Dimension_Reduction`, 9
  - `HIRISE_api.preprocessing.Encoding`, 9
  - `HIRISE_api.preprocessing.Image_Loader`, 10
  - `HIRISE_api.preprocessing.utils`, 10
- `HIRISE_api.tests`, 11
  - `HIRISE_api.tests.test_hirise`, 11
  - `HIRISE_api.tests.test_models`, 11
  - `HIRISE_api.tests.test_preprocessing`, 11