# Documentation

## ness

# February 28, 2020

# Contents

1	Cod	le structure, Class variables and functions	2
	1.1	SPH_particle	2
		1.1.1 Class variables:	2
		1.1.2 Class functions:	3
	1.2	SPH_ main	3
		1.2.1 Class variables:	3
		1.2.2 Class functions:	5
2	Parallelization with OpenMP		8
3	Running the Simulation, Post-processing and Output scripts		
	3.1	file writer.cpp	8
	3.2	post.py	9
4	Testing		
	4.1	C++ Testing	9
	4.2	Python Testing	9
	4.3	Testing pipeline	9

This tool has been implemented in C++ with Python as a means to analyze data and test the output of the code. Bellow is the documentation of the functions used in the tool and an analysis of the testing pipline.

## 1 Code structure, Class variables and functions

The tool is composed of two classes  $SPH\_particle$  and  $SPH\_main$ .  $SPH\_particle$  is an object that represents each individual particle in our simulation and holds parameters and values that are specific to every particle (eg. position, velocity, etc).  $SPH\_main$  represents the domain the simulation is using and holds all the functions, globals and data strucutres needed to run the simulation.

## 1.1 SPH particle

### 1.1.1 Class variables:

- **x**[] (**double**) Particle position variables. This array has two entries, one for the x-direction and one for the y-direction.
- v[] (double) Particle velocity variable. This array has two entries, one for the x-direction and one for the y-direction.
- rho (double) Particle density variable.
- P (double) Particle pressure variable.
- a[] (double) Particle acceleration variable. This array has two entries, one for the x-direction and one for the y-direction.
- **D** (double) Particle rate of change of density variable.
- **rho2 (dobule)** Particle density variable. Used in the *density\_field\_smoothing* function.
- vij half[] (double)
- **x\_half[] (double)** Particle half-step position variable. This is an array that stores the position of the particle after a half step in the second order time-stepping method. This array has two entries, one for the x-direction and one for the y-direction.

- v\_half[] (double) Particle half-step velocity variable. This is an array that stores the velocity of the particle after a half step in the second order time-stepping method. This array has two entries, one for the x-direction and one for the y-direction.
- rho\_half (double) Particle half-step density variable. This is a variable that stores the density of the particle after a half step in the second order time-stepping method.
- a\_half[] (double) Particle half-step acceleration variable. This is an array that stores the acceleration of the particle after a half step in the second order time-stepping method. This array has two entries, one for the x-direction and one for the y-direction.
- **D\_half (double)** Particle half-step rate of change of density variable. This variable stores the rate of change of density after a half step in the second order time-stepping method.
- **numerator (double)** Is (literaly) the numerator from density smoothing function.
- **denominator (double)** Is (literaly) the denominator from the density smoothing function.
- main\_data (staic SPH\_main \*) Link to SPH\_main class so that it can be used to calc\_index
- list num[] (int) Index in neighbour finding array.
- is boundary (bool) Set true if the particle is part of the boundary

### 1.1.2 Class functions:

calc\_index(void) (void) This function is responsible for populating the
 list\_index[] array.

## 1.2 SPH main

## 1.2.1 Class variables:

h (double) Smoothing length

h fac (double)

- **dx (double)** Particles initial spacing. This is a variable that is responsible for the space between neighbouring particles when the initial configuration is set.
- **c0** (double) Speed of sound. As this is a simple simulation, a different speed of sound has been implemented.
- dt (double) Timestep. This is a variable that defines the size of the timestep in the time-stepping solution.
- g[] (double) Gravity constant array. This array stores the initial accelaration values that describe our sytem. In this case it is only gravity and it points in the negative y-direction.
- mu (double) Viscocity variable. This variable holds the viscocity value of our system.
- **rho0** (double) Initial density variable. This variable stores the initial density value for all the particles.
- B (double) Initial, or reference density of the fluid, given by the formula:

$$B = \frac{\rho_o c_o^2}{\gamma} \tag{1}$$

- **gamma (double)** A constant used in a number of formulas throughout the code. The value is given as 7.
- mass (double) Mass variable. This variable stores the mass of each particle in the simulation.

For dynamic time stepping

- v max (double) Maximum velocity of all particles in one iteration.
- a max (double) Maximum acceleration of all particles in one iteration.
- **rho** max (double) Maximum density of all particles in one iteration.
- dt\_cfl (double) Constant used in the dynamic time-stepping, according to the formula:

$$\Delta t_{CFL} = min \left\{ \frac{h}{|v_{ij}|} \right\} \tag{2}$$

 $\mathbf{dt}_{\mathbf{f}}$  (double) Constant used in the dynamic time-stepping, according to the formula:

$$\Delta t_F = min \left\{ \sqrt{\frac{h}{|a_i|}} \right\} \tag{3}$$

dt\_a (double) Constant used in the dynamic time-stepping, according to the formula:

$$\Delta t_A = min \left\{ \frac{h}{c_o \sqrt{(\rho/\rho_o)^{\gamma - 1}}} \right\}$$
 (4)

**cfl** (**double**) A constant used to scale the constants above. Its range should be between 0.1 - 0.3.

 $\min_{\mathbf{x}[]}, \max_{\mathbf{x}[]}$  (double) Dimensions of simulation region

grid count (vector<vector<int»)

max list[] (int) Maximum index of grid.

particle list (vector<SPH particle>) List of all the particles

search\_grid (<vector<vector<vector<SPH\_particle\*>>>) Outer
two vectors are the grid, inner vector is the list.

### 1.2.2 Class functions:

SPH main() Main constructor.

cubic\_spline(double r[]) (double) Cubic Spline calculation function.

• r// contains the distance between two points.

Calculates the cubic spline according to three cases:

$$W(r,h) = \frac{10}{7\pi h^2} \begin{cases} 1 - \frac{3}{2}q^2 + \frac{3}{4}q^3 & \text{if } 0 \le q \le 1\\ \frac{1}{4}(2-q)^3 & \text{if } 1 \le q \le 2 \text{ Where } q = \frac{r}{h} \\ 0 & \text{if } q > 2 \end{cases}$$
 (5)

**cubic\_spline\_first\_derivative**(double r[]) (double) Cubic Spline First Derivative calculation function.

• r// contains the distance between two points.
Calculates the cubic spline according to three cases:

$$\nabla W(r,h) = \frac{10}{7\pi h^3} \begin{cases} -3q + \frac{9}{4}q^2 & \text{if } 0 \le q \le 1\\ -10\frac{3}{4}(2-q)^2 & \text{if } 1 \le q \le 2 \text{ Where } q = \frac{r}{h} \\ 0 & \text{if } q > 2 \end{cases}$$
 (6)

update\_gradients(double r[], SPH\_particle\* part, SPH\_particle\* other\_part) (void)
Updating the values of rate of change of speed (acceleration) and density.

- part is a pointer to the particle that we calculate the change for.
- other\_part is a pointer to the neighbouring particle used in the calculation. The calculations are done according to the following functions:

$$\alpha_{i} = -\sum_{j=1}^{N} m_{j} \left( \frac{P_{i}}{\rho_{i}^{2}} + \frac{P_{j}}{\rho_{j}^{2}} \right) \frac{dW}{dr} (r_{ij}, h) e_{ij} + \sum_{j=1}^{N} m_{j} \left( \frac{1}{\rho_{i}^{2}} + \frac{1}{\rho_{j}^{2}} \right) \frac{dW}{dr} (r_{ij}, h) \frac{v_{ij}}{r_{ij}}$$
(7)

$$D_i = \sum_{j=1}^{N} m_j \frac{dW}{dr}(r_{ij}, h) v_{ij} \cdot e_{ij}$$
(8)

- density\_field\_smoothing(SPH\_particle\* part) (void) Smoothing out the Density/Pressure field. This is done because the integration of the continuity equation will result in variations in density and pressure based on the macroscopic velocity gradients, but also on local variations in particle spacing and velocity; resulting in a "rough" density and pressure distributions. To get around this problem, we implemented a density smoother.
  - part is a pointer to the particle whose density is to be smoothed.

$$\rho_i = \frac{\sum_{j=1}^n W(r_{ij}, h)}{\sum_{j=1}^n \frac{W(r_{ij})}{\rho_j}}$$
(9)

set\_values(double delta\_x) (void) Setting simulation parameters.

- delta x the distance between particles in the initial configuration.
- initialize\_grid(void) (void) This function initializes the search grid used to find neighbours. This is done by dividing the points into cell grids of size double the initial distance between particles and allocating them to the corresponding cell.

- place\_points(double min0, double min1, double max0, double max1, bool type) (void)
  This function is responsible for initializing the points to the domain,
  by setting all the variables (as defined in the SPH\_particle variables).
  - $min\theta$  minimum position value for the x-direction.
  - min1 minimum position value for the y-direction.
  - $max\theta$  maximum position value for the x-direction.
  - max1 maximum position value for the y-direction.
  - type boolean that defines weather or not the particle is on the boundary.
- allocate\_to\_grid(void) (void) Allocates all the points to the search grid (assumes that index has been appropriately updated). This function is called in every iteration step, as the movement of the particles might change their corresponding search grid cell.
- neighbour\_iterate(SPH\_particle\* part) (void) The main function that searches the search grid to find the corresponding neighbours for the given particle.
  - part the particle for which the neighbours are searched.

## !!!NEED TO ADD DESCRIPTION!!!!

- update\_particle(SPH\_particle\* part) (void) Function that updates the position, velocity, density and pressure, according to the results of the update\_gradients functions.
  - part the particle for which the variables are updated.
- reset\_grid\_count() (void) This function resets the grid count of the domain after every iteration.
- update\_rho(SPH\_particle\* part) (void) This function updates the density of the particle after each half and whole timestep.
  - part the particle for which the density is updated.
- store\_initial(SPH\_particle\* part) (void) This function stores the initial velocity, density and position for the second order time-stepping scheme.
  - part input particle to store

time dynamic() (void)

full update(SPH particle\* part) (void) blablabla

• part particle to receive full update.

get new  $\max(SPH \ particle* part)$  (void) blablabla

• part particle to get new max from.

repulsion(SPH particle\* part, double dist) (double) blablabla

- part particle to apply the repulsive force to.
- dist

update particle FE(SPH particle\* part)

## 2 Parallelization with OpenMP

OpenMP was used to parallelize the computation of the simulation. The  $\#pragma\ omp\ for\ loops$  exist on the  $SPH\_Snippet$ , parallelizing the looping over all particles. Since our  $update\_particle$  and  $neighbout\_iterate$  functions operate on two particles in the same time, the  $\#pragma\ omp\ atomic$  directive was added at the parts of the code where we update the particle values, to ensure that no more than one process accesses and edits them at one time.

# 3 Running the Simulation, Post-processing and Output scripts

A sample C++ file  $(SPH\_Snippet.cpp)$  has been provided in the package that runs the simulation for the parameters required for the class excericse. That file is responsible for the entirety of the simulation and serves as a template for any future simulations anyone would want to run using this tool. Moreover, a number of post processing scripts have been implemented in C++ and Python for the purpose of outputing the simulation states in a suitable format for both visualization and data manipulation.

## 3.1 file writer.cpp

A simple C++ file that outputs simulation steps as .vtp files; to be used with ParaView or other software that is build upon the VTK library.

### 3.2 post.py

A simple Python script that takes the .vtp files created by file\_writer.cpp, creates a Pandas DataFrame for every iteration step and outputs them in a HDF5 file (for easy data transport and data manipulation). A similar version of the script is used in the testing pipeline in the step where the testing moves from C++ to Python.

## 4 Testing

Testing on this tool is done by both C++ and Python. For C++ the BOOST library is used and for Python a custom test file has been written.

## 4.1 C++ Testing

The C++ side of the testing handles all the mathematical functions defined in the SPH\_main class. Namely cubic\_spline, cubic\_spline\_first\_derivative and update\_gradients. A set of BOOST test cases has been set that depends on the possible outputs of the spline functions. Note, that the same principle is applied for update\_gradients as the cubic spline functions play an important role in the calculation of acceleration and rate of change of pressure. Moreover, the tests are conducted independently of the model parameters (as they are defined in the set\_vales functions), by setting the desired parameters before the function call.

### 4.2 Python Testing

The Python part of the testing deals with validating the behaviour of the simulator; checking that the particles stay within the boundaries and that the particles are present at their proper positions after N iterations steps. This part of the testing can be used for validating that the input parameters by the user fall within the power of the simulator (ie that the simulator does not become unstable).

### 4.3 Testing pipeline

The teting pipeline goes as follows:

- 1. The objects and C++ classes get compiled.
- 2. The Python script run\_tests.py is being run, which is responsible for running both the C++ and Python tests.

- 3. The C++ test file test\_SPH\_2D.cpp is run, followed by test\_file\_writer.cpp which outputs a set of .vtp files, containing the iteration steps of the test simulator.
- 4.  $test\_post.py$  is called (a specialised version of post.py) which processes the .vtp files and creates the  $output\_test.h5$  file, containing all the Pandas DataFrames to be used by the Python part of the tests.
- 5. python\_tests.py is run with output\_test.h5 as input; completing a number of tests on the behaviour of the simulator.

Note: The following commands are to be entered from the base repository of the package. The complete testing pipeline can be run by using:

#### make runtests

To run only the C++ tests you can use:

### ./tests/bin/test\_SPH\_2D

The  $-log\_level=unit\_scope$  flag can be used to give a detailed report of the testing suite and  $-list\_content$  provides the user for a description of each testing case for easier debugging.

To produce the .vtp files you can use:

### ./tests/bin/test\_file\_writer

To produce the .h5 test files you can use:

### python ./tests/test\_post.py

(It goes without saying that the .vtp files need to already exist for the .h5 files to be produced.)