

SLT12 Pro

Imaging Total Station

See Clearly.
Measure Precisely.

- Coaxial Imaging
- Guidance Light
- Full-Keypad Design




UNLOCK YOUR MOBILITY

SLT12 Pro Imaging Total Station


Powered by an upgraded Android system with expanded memory, SLT12 Pro delivers a faster and smoother field experience. The dual high-definition displays enhance operational efficiency, while the built-in camera, coaxial vision, and guide light enable intuitive visual stakeout and precise target guidance, making SLT12 Pro an ideal solution for efficient and high-precision surveying tasks.



Function




Stake out




Offset



MLM




REM




Repeated




Resection



Road



Area



Bridge



Tunnel

Coaxial Imaging



Integrated HD coaxial imaging system with aligned optical and measurement paths for true what-you-see-is-what-you-measure operation. Real-time target display on the large screen ensures clear observation even in complex or low-light environments. Supports image capture with point association for efficient verification and traceability.

Guidance Light



Equipped with a red and green dual-color guidance light, clearly visible from 1.5–150 m. The rod operator can quickly locate the target by the light indication: red light indicates right deviation, green light indicates left deviation, and alternating flashing means alignment with the line of sight. Ideal for tunnels, underground sites, and nighttime stakeout, improving efficiency by over 20%.

CAD Stakeout



With millisecond-level dynamic response, the high-performance CAD engine simplifies stakeout point and line selection, making the process incredibly intuitive and efficient with just one click.

Full-Keypad Design



Features a full alphanumeric physical keypad with an ergonomic layout for easy operation. Backlit keys ensure clear visibility in dark environments, while the dust- and splash-resistant design is built for harsh field conditions. Unlike touchscreen-only designs, it enables accurate input even in cold, wet, or glove-wearing conditions.

Large Memory



3 GB RAM and 32 GB internal storage ensure smooth operation and multitasking. Easily stores massive measurement data, HD images, and design files for efficient fieldwork.

Key Features



Android operating system



5.5-inch touch screen
Resolution 720*1440



Reflectorless range 1000 m
Speed down to 0.3 s



Support Bluetooth, Wi-Fi
Wi-Fi hotspot



Equipped with 2 cameras
Coaxial camera: 2MP
Off-Axis camera: 8MP



Type-C port with integrated
USB OTG function



Qualcomm octa-core: 1.8 GHz



Free Road, Bridge and Tunnel
measurement software





Headquarters:
GEOSOLUTION I GÖTEBORG AB
Stora Ävägen 21, 436 34 ASKIM,
Sweden
info@satlabgeo.com

Regional Offices:
Budapest, Hungary
Ankara, Turkey
Dubai, UAE
New Delhi, India
Scottsdale, USA
Tokyo, Japan
Hong Kong, China

www.satlabgeo.com



AUTHORIZED DISTRIBUTION PARTNER 26M216

SPECIFICATIONS

Angle Measurement		
Angle Measuring Principle	Absolute Encoding	
Minimum Readout	0.1"	
Accuracy	2"	1"
Telescope		
Image	Erect	
Magnification	30 X	
Field of View	1°30'	
Minimum Focusing Distance	1.5 m	
Effective Aperture	40/50 mm	
Reticle	Illuminated	
Compensation		
System	Dual-axis	
Working Range	±6'	
Accuracy	1"	
Distance Measurement (Prism Mode)		
Single Prism ¹ (General / Ideal Weather Condition)	5000 m	
Accuracy (Fine / Quick / Tracking)	±(2+2×10 ⁻⁶ D)mm	±(1+1×10 ⁻⁶ D)mm
Measuring Time ³ (Repeat / Tracking)	0.5 s / 0.3 s	
Reflectorless		
Range ² (The Target is Kodak White Board with 90% Reflect Rate)	1000 m	
Accuracy	1.5~300m: ±(3+2×10 ⁻⁶ D)mm 300~600m: ±(5+2×10 ⁻⁶ D)mm 600~1000m: ±(10+2×10 ⁻⁶ D)mm	
Measuring Time ³ (Repeat / Tracking)	Approx. 1s	
Communication		
Interfaces	Type-C (OTG), TF Card, RS 232	
WLAN	2.4 GHz Dual-band, Support AP Mode	
Bluetooth	BT2.1+EDR / 3.0 / 4.2 LE	
Microphone / Speaker	Available	
System Configuration		
Operating System	Android	
Memory	RAM: 3 GB; ROM: 32 GB	
Display System		
Display	5.5" Touch Screen, 720*1440, dual/single screen display modes.	
Camera		
Coaxial Camera	2 MP	
Off-Axis Camera	8 MP	
Guidance Light		
Visibility Range	1.5~150m	
Levels		
Tube level	30" / 2 mm	
Circular level	8' / 2 mm	
Plummet		
Type	Laser centering or Image-based centering (Optional)	
Centering Accuracy	1 mm (Instrument Height 1.5 m)	
Instrument Height Measurement Accuracy	Laser:1 mm / Image:2 mm	
Environmental		
Operating Temperature	-20°C~ 50°C	
Storage Temperature	-40°C~55°C	
Temperature and Air Pressure Input	Automatic Sensor	
Dust&Water Proof	IP65	
Power Supply ⁴		
Battery Type	High-energy Lithium Battery	
Voltage / Capacity	7.2 V / 6800 mAh	
Measuring Times	8h(Two Batteries)	
Dimension		
Size	221 mm*223 mm*374 mm	
Weight	Approx. 6 kg(battery included)	

Reminders:

*1. Good Conditions: good visibility of about 20km, the overcast sky without scintillation.

*2. Under Kodak white board(90%), measuring distance may vary according to targets and the conditions.

*3. Measuring time may vary with measuring distance and conditions. For the initial measurement, it may take a longer time.

*4. Battery life performs best at 25°C. It might be shorter in low temperature or if the battery is old.